

Company Name:	
Address:	
City:	
Machine Identification:	

2022

Perchloroethylene (PCE) Dry Cleaner Compliance Calendar

State of Utah
Department of Environmental Quality
Division of Air Quality

PERCHLOROETHYLENE (PCE) DRY CLEANERS FACT SHEET

WHY IS EPA REGULATING DRY CLEANERS?

The Clean Air Act of 1990 directs the United States Environmental Protection Agency (EPA) to regulate the emissions of 188 chemical compounds designated as Hazardous Air Pollutants (HAPs). Perchloroethylene, also known as "perc", "pce" or "tetrachloroethylene", is on the list of HAPs and is the most commonly used chemical solvent at dry cleaners. In September 1993, the EPA issued national regulations to control air emissions of "PCE" from dry cleaners which they revised in July and September 2006. Remember these rules only apply to dry cleaners using PCE.

IS YOUR BUSINESS AFFECTED?

How the business is affected depends on the date of machinery installation, the amount of "PCE" purchased each year and the type of machines at the facility. **December 9, 1991 and December 21, 2005** are important dates for these regulations. When a machine is installed determines applicable rules and the types of control devices that are required.

If a facility has machines initially <u>installed before December 9, 1991</u> the machine will be classified as "existing". If a facility has machines initially <u>installed on or after December 9, 1991</u>, the source will be classified as "new". The amount of PCE purchased determines the facility size: small area, large area or major. Small area sources use less than 140 gallons in a year for a dry-to-dry machine or 200 gallons for a transfer machine.

WHAT REQUIREMENTS APPLY?

- ✓ Air pollution equipment is required for ALL PCE dry cleaning equipment EXCEPT: (1) transfer machines installed prior to September 23, 1993 and which use less than 200 gallons per year AND (2) dry-to-dry machines installed prior to October 9, 1991 and use less than 140 gallons per year.
- ✓Operate and maintain system according to manufacturer's specifications and recommendations. Maintain, onsite, a copy of the design specifications and operating manual for each machine and control device.
- ✓ Refrigerated condensers installed on dryers, dry-to-dry machines or reclaimers may not vent to the atmosphere while the drum is rotating.
- √Keep machine doors closed at all times except when transferring clothes.

- ✓ Store all PCE solvent and waste in sealed containers.
- ✓ Drain cartridge filters in their housings or other sealed container for 24 hours before disposing of them as a hazardous waste.
- ✓Inspect equipment every week (large sources using 140 gallons or more) or every two weeks (small sources using less than 140 gallons) for perceptible leaks, those obvious to sight, smell, or touch, while the dry cleaning system is operating. ONCE each month the inspection must be conducted with a hand-held detector/gas analyzer. Record all inspection and repair findings.
- ✓ Repair perceptible leaks within 24 hours. Parts must be ordered within two working days and installed within five days of receipt. Record all repairs.

IS MONITORING AND RECORDKEEPING REQUIRED?

- ✓ Maintain on-site, for five years, records of inspection dates, name and location of system components where leaks are found, inspection method, dates of repair and record of written or verbal part orders. Record "no leaks" or "leak found", as applicable and record repair method e.g. "repaired by tightening nuts" in a maintenance log.
- ✓ Record your PCE purchases in a log and at the first of each month total the volume purchased in the previous 12 months. Keep purchase receipts and log on-site for a minimum of five years. If the usage exceeds that reported in your initial compliance status, your location changes, or additional machines added, then submit a new Notification of Compliance.
- ✓ For a refrigerated condenser (RC), the primary evaluation method records and evaluates the high and low pressure readings on the compressor unit. The alternate method, when no pressure gauges are present: measure and record weekly the air temperature after the RC. If the RC outlet air temperature is greater than 45° F (7.2° C) during the end of the dry cycle, make repairs and adjustments to meet this requirement.
- ✓For a Carbon adsorber, the amount of PCE vapor in the exhaust and dry cleaner drum need to be measured and recorded weekly. A colorimetric tube is acceptable for these measurements. Take exhaust duct PCE concentration measurement at the end of the last dry cleaning cycle before carbon is desorbed and make repairs or adjustments if the concentration exceeds 100 parts per million (ppm). Take drum PCE concentration measurement at the end of the dry cleaning cycle and make repairs or adjustments if the concentration exceeds 300 ppm.

IS THERE PAPERWORK TO SUBMIT?

All new dry cleaning machinery must have a Notification of Compliance form submitted within 30 days of startup, including an estimate of PCE usage. An updated Notification is required when significant changes occur at a facility. There is a reporting form (rev 12/20086) on the second to last page of this calendar and it indicates what significant changes prompt a new submittal.

OTHER REGULATIONS

Utah Division of Waste Management and Radiation Control - (801) 536-0200

https://deq.utah.gov/waste-management-and-radiation-control/hazardous-waste-management-program

Basic, onsite hazardous waste training is also available through this program.

- ✓If you generate less than 220 pounds of hazardous waste per month, you are a Conditionally Exempt Small Quantity Generator. This allows you to dispose of the hazardous waste at a permitted disposal facility when prior approval is obtained from the facility owner/operator.
- ✓If you generate more than 220 pounds of hazardous waste per month, your facility is more stringently regulated. ALL hazardous waste shipped to a disposal facility must be manifested. The paperwork must be properly filled out with the applicable signatures of the generator, transporter and disposer. You must keep the manifest onsite for a minimum of three years. Contact the Division for further information if you fall within this category.
- ✓If ANY of your solid waste contains PCE, it is ALL considered hazardous. This waste may include still residues, spent cartridges and separator water. These wastes are an EPA F002 listed hazardous waste.
- ✓ All containers holding hazardous waste must be labeled with the words "HAZARDOUS WASTE" and must be kept completely closed except when adding to or taking from a container.

Utah Division of Environmental Response and Remediation - (801) 536-4100

https://deq.utah.gov/division-environmental-response-remediation

- ✓ Any underground storage tank that holds 110 gallons or more of a petroleum product or of a CERCLA hazardous substance (e.g. PCE) must be registered. You will need to register the tanks, pay tank fees and do a onetime minimum site assessment. Also:
 - √The underground tank system must be double walled or have secondary containment and the owner/operator needs to perform and keep records of monthly monitoring of the interstitial space.
 - ✓If the tank or piping is made of metal, the system must be cathodically protected. The cathodic protection system must be tested every 3 years and results of the last two cathodic protection tests must be maintained for inspection.
- ✓ If these requirements apply, visit our website for information on leak detection monitoring requirements.

Utah Division of Water Quality – UPDES Engineering Section 801-536-4300

https://deg.utah.gov/division-water-quality

- ✓ Separator water from your dry cleaning system contains PCE. It cannot be discharged to a sewer or storm sewer system. There are commercially available misters and evaporators with filters that remove the trace amounts of PCE before the water is evaporated. Or, the separator water can go into the sludge bin and be disposed of as hazardous waste.
- ✓ If you have an existing floor drain connected to a septic tank and leach field or dry well, call us to plan the best course of action to monitor or eliminate this type of system. This system is NOT allowed in new construction.
- ✓ If your wastewater discharges directly to a ditch or a stream, give us a call for permit requirements.
- ✓If wastes from floor cleaning, etc. drain to a floor sump connected to a municipal water and sewer system, make sure you are aware of and comply with any pretreatment and cross connection prevention programs. Call your city or local sewer district for more information.

JANUARY 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

	a Largo Firoa Oloanoroj		000 00000.00	o procedio ii procedio gaagee are p			goranion anni
DATE	PRES	PRESSURE (0			sure within	[PCE] in CA	[PCE] in Drum
DAIL	High	Low	(°F or °C)	mfr specs? Or is temp 45° F (7.2° C)		Exhaust	(ppm)
				or	less?	(ppm)	
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM							
PURCHASE	ACT PCE D LAST YEAR NUARY 2021	-					
SUB	TOTAL						
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL					
	+						
	+						

LEAK INSPECTIONS (TEST METHODS: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	NG?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	N Y	N Y	NY	ΝΥ			
Door Gaskets + Seating	NY	N Y	N Y	NY	ΝΥ			
Pump	ΝΥ	NY	NY	NY	ΝΥ			
Solvent Tanks + containers	NY	N Y	N Y	NY	ΝΥ			
Water Separators	ΝΥ	NY	NY	NY	ΝΥ			
Muck Cooker	ΝΥ	NY	NY	NY	ΝΥ			
Still	ΝΥ	NY	NY	NY	ΝΥ			
Exhaust Dampers	ΝΥ	NY	NY	NY	ΝΥ			
Diverter Valves	ΝΥ	NY	NY	NY	ΝΥ			
Filter Gaskets + Seating	ΝΥ	ΝΥ	NY	ΝΥ	ΝΥ			
All Filter Housings	ΝΥ	ΝΥ	NY	ΝΥ	ΝΥ			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	ΝΥ	ΝΥ	LABELED Y N DAT	ED Y N	•

JANUARY 2022

Su	M	Tu	W	Th	F	Sa
30	31					1
2	3	4 Temp logged Inspect logged	5	6	7	8
9	10	11 Temp logged Inspect logged	12	13	14	15
16	17	18 Temp logged Inspect logged	19	20	21	22
23	24	25 Temp logged Inspect logged	26	27	28	29

February 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

DATE	PRESSURE		TEMP	Is press	sure within	[PCE] in CA	[PCE] in Drum
DAIL	High	Low	(1010)	mfr specs? Or is temp 45° F (7.2° C) or less?		Exhaust (ppm)	(ppm)
				Υ	N	(PP)	
				'			
				Y	N		
				Y	N		
				Υ	N		
				Υ	N		

	TOTAL FROM LAST MONTH JANUARY 2022						
PURCHASE	ACT PCE D LAST YEAR BRUARY 2021	-					
SUB	TOTAL						
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL					
	+						
	+						

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

(Small Area Cleaners every other week, Large Area Cleaners every week)

** ONCE EACH MONTH the inspection is REQUIRED to be conducted using a hand-held leak detector, regardless of facility size or equipment installation date **

COMPONENT INSPECTED	LEAKII	NG?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	N Y	N Y	NY	NY			
Door Gaskets + Seating	N Y	N Y	N Y	NY	NY			
Pump	N Y	NY	NY	NY	NY			
Solvent Tanks + containers	N Y	N Y	N Y	NY	NY			
Water Separators	N Y	N Y	N Y	NY	NY			
Muck Cooker	N Y	NY	N Y	NY	NY			
Still	N Y	NY	N Y	NY	NY			
Exhaust Dampers	N Y	N Y	N Y	NY	NY			
Diverter Valves	N Y	NY	NY	NY	NY			
Filter Gaskets + Seating	N Y	N Y	N Y	NY	NY			
All Filter Housings	N Y	ΝΥ	ΝΥ	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

FEBRUARY 2022

Su	M	Tu	W	Th	F	Sa
		Temp logged Inspect logged	2	3	4	5
6	7	8 Temp logged Inspect logged	9	10	11	12
13	14	15 Temp logged Inspect logged	16	17	18	19
20	21	22 Temp logged Inspect logged	23	24	25	26
27	28					

MARCH 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL

(New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

	PRESSURE DATE		TEMP	Is pres	sure within ecs? Or is	[PCE] in CA	[PCE] in Drum
High Low		(10,0)	temp 45	5º F (7.2º C) less?	Exhaust (ppm)	(ppm)	
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM FEBRU							
PURCHASE	ACT PCE D LAST YEAR ARCH 2021	-					
SUB	TOTAL						
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL					
	+						
	+						

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	NG?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	N Y	N Y	NY	NY			
Door Gaskets + Seating	N Y	N Y	N Y	NY	NY			
Pump	NY	N Y	N Y	NY	NY			
Solvent Tanks + containers	N Y	N Y	N Y	NY	ΝΥ			
Water Separators	N Y	N Y	N Y	NY	ΝΥ			
Muck Cooker	NY	N Y	N Y	NY	NY			
Still	N Y	N Y	N Y	NY	ΝΥ			
Exhaust Dampers	N Y	N Y	N Y	NY	ΝΥ			
Diverter Valves	ΝΥ	NY	N Y	ΝΥ	NY			
Filter Gaskets + Seating	N Y	N Y	N Y	NY	ΝΥ			
All Filter Housings	ΝΥ	ΝΥ	N Y	NY	NY			
Waste Containers	ΝΥ	NY	N Y	ΝΥ	NY	LABELED Y N DAT	ED Y N	

MARCH 2022

Su	M	Tu	W	Th	F	Sa
		1 Temp logged Inspect logged	2	3	4	5
6	7	8 Temp logged Inspect logged	9	10	11	12
13	14	15 Temp logged Inspect logged	16	17	18	19
20	21	22 Temp logged Inspect logged	23	24	25	26
27	28	29 Temp logged Inspect logged	30	31		

APRIL 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

DATE	PRES	SURE	TEMP (°F or °C)		sure within ecs? Or is	[PCE] in CA	[PCE] in Drum
DAIL	High	Low	(1010)	temp 45	5º F (7.2º C)	Exhaust	(ppm)
				or	less?	(ppm)	
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM						
PURCHASE	SUBTRACT PCE PURCHASED LAST YEAR during APRIL 2021					
SUB	TOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKING?							
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	NY	N Y	NY	NY	NY			
Door Gaskets + Seating	NY	N Y	N Y	NY	NY			
Pump	NY	NY	N Y	NY	NY			
Solvent Tanks + containers	NY	N Y	N Y	NY	NY			
Water Separators	N Y	N Y	N Y	NY	NY			
Muck Cooker	N Y	NY	N Y	NY	NY			
Still	N Y	N Y	N Y	NY	NY			
Exhaust Dampers	N Y	N Y	N Y	NY	NY			
Diverter Valves	N Y	NY	N Y	NY	NY			
Filter Gaskets + Seating	ΝΥ	NY	N Y	N Y	NY			
All Filter Housings	ΝΥ	NY	N Y	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

APRIL 2022

Su	M	Tu	W	Th	F	Sa
					1	2
3	4	5 Temp logged Inspect logged	6	7	8	9
10	11	12 Temp logged Inspect logged	13	14	15	16
17	18	19 Temp logged Inspect logged	20	21	22	23
24	25	26 Temp logged Inspect logged	27	28	29	30

MAY 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

	PRES	SURE	TEMP		sure within	[PCE] in	[PCE] in Drum (ppm)
DATE	High	Low	(° F or ° C)		ecs? Or is	CA	
	i iigii	LOW			5º F (7.2º C)	Exhaust	(ppm)
				or	less?	(ppm)	
				V	N.I.		
				T	N		
				Y	N		
				Y	N		
				•	1 1		
				V	N.I		
				T	N		
				Y	N		
				•	• •		

TOTAL FROM						
PURCHASE	SUBTRACT PCE PURCHASED LAST YEAR during MAY 2021					
SUB	TOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKING?							
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	NY	N Y	NY	NY	NY			
Door Gaskets + Seating	NY	N Y	N Y	NY	NY			
Pump	NY	NY	N Y	NY	NY			
Solvent Tanks + containers	NY	N Y	N Y	NY	NY			
Water Separators	N Y	N Y	N Y	NY	NY			
Muck Cooker	N Y	NY	N Y	NY	NY			
Still	N Y	N Y	N Y	NY	NY			
Exhaust Dampers	N Y	N Y	N Y	NY	NY			
Diverter Valves	NY	NY	N Y	NY	NY			
Filter Gaskets + Seating	ΝΥ	NY	N Y	N Y	NY			
All Filter Housings	ΝΥ	NY	N Y	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

MAY 2022

Su	M	Tu	W	Th	F	Sa
1	2	Temp logged Inspect logged	4	5	6	7
8	9	10 Temp logged Inspect logged	11	12	13	14
15	16	17 Temp logged Inspect logged	18	19	20	21
22	23	24 Temp logged Inspect logged	25	26	27	28
29	30	31 Temp logged Inspect logged				

JUNE 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber[PCE] (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit **PCE PURCHASES 12-MONTH TOTAL**

	DATE PRESSURE		TEMP (°F or °C)	Is press	sure within	[PCE] in CA	[PCE] in Drum
DAIL	High	gh Low (° F or ° C) mfr specs? Or temp 45° F (7.2° or less?		5º F (7.2º C)	Exhaust (ppm)	(ppm)	
				Y	N	(ρριιι)	
				Υ	N		
				· V			
				T	N		
				Y	N		
				Y	Z		

TOTAL FROM						
PURCHASE	SUBTRACT PCE PURCHASED LAST YEAR during JUNE 2021					
SUB	TOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKING?							
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	NY	N Y	NY	N Y			
Door Gaskets + Seating	N Y	N Y	N Y	NY	NY			
Pump	N Y	NY	N Y	NY	N Y			
Solvent Tanks + containers	N Y	N Y	N Y	NY	NY			
Water Separators	N Y	NY	N Y	NY	N Y			
Muck Cooker	N Y	NY	N Y	NY	N Y			
Still	N Y	N Y	N Y	NY	NY			
Exhaust Dampers	N Y	NY	N Y	NY	N Y			
Diverter Valves	N Y	ΝΥ	ΝΥ	NY	NY			
Filter Gaskets + Seating	N Y	N Y	N Y	NY	NY			
All Filter Housings	N Y	ΝΥ	ΝΥ	N Y	NY			
Waste Containers	N Y	ΝΥ	ΝΥ	ΝΥ	ΝΥ	LABELED Y N DAT	ED Y N	

JUNE 2022

Su	М	Tu	W	Th	F	Sa
			1	2	3	4
5	6	7 Temp logged Inspect logged	8	9	10	11
12	13	14 Temp logged Inspect logged	15	16	17	18
19	20	21 Temp logged Inspect logged	22	23	24	25
26	27	28 Temp logged Inspect logged	29	30		

JULY 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

High Low (° F or ° C) mfr specs? Or is temp 45° F (7.2° C) or less? Y N Y N Y N Y N Y N							rocont on rom,	
High Low temp 45° F (7.2° C) Exhaust (ppm) Y N Y N Y N Y N Y N	PRESSURE							[PCE] in
or less? (ppm) Y N Y N Y N Y N Y N Y N	ow	High	High Low (°F	or °C)				Drum (ppm)
Y N Y N Y N								(ррііі)
Y N Y N Y N					V	N.I.		
YN					Y	N		
YN					V	NI		
YN					ľ	IN		
YN					V	N		
						14		
					V	NI		
						14		
					V	N		
					ľ	IA		

TOTAL FROM		
SUBTR PURCHASE during	-	
SUB	TOTAL	
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL
	+	

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	-EAKING?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	N Y	N Y	NY	ΝΥ			
Door Gaskets + Seating	N Y	N Y	N Y	NY	ΝΥ			
Pump	NY	N Y	N Y	NY	ΝΥ			
Solvent Tanks + containers	N Y	N Y	N Y	NY	ΝΥ			
Water Separators	N Y	N Y	N Y	NY	ΝΥ			
Muck Cooker	NY	N Y	N Y	NY	ΝΥ			
Still	N Y	N Y	N Y	NY	ΝΥ			
Exhaust Dampers	N Y	N Y	N Y	NY	ΝΥ			
Diverter Valves	ΝΥ	NY	N Y	NY	ΝΥ			
Filter Gaskets + Seating	N Y	N Y	N Y	NY	ΝΥ			
All Filter Housings	ΝΥ	NY	N Y	NY	ΝΥ			
Waste Containers	ΝΥ	NY	NY	NY	ΝΥ	LABELED Y N DAT	ED Y N	

JULY 2022

Su	M	Tu	W	Τh	F	Sa
31					1	2
3	4	5 Temp logged Inspect logged	6	7	8	9
10	11	12 Temp logged Inspect logged	13	14	15	16
17	18	19 Temp logged Inspect logged	20	21	22	23
24	25	26 Temp logged Inspect logged	27	28	29	30

AUGUST 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) (Use pressure if pressure gauges are present on refrigeration unit

tow email and Earge / trea eleanere)		000 00000.00	P. 00000	rodont on ronigoration and			
DATE	PRESSURE		TEMP (°F or °C)	Is pressure within mfr specs? Or is		[PCE] in CA Exhaust	[PCE] in Drum
DAIL	High	Low	Low temp 45° F (7.2° C)		° F (7.2° C)	(ppm)	(ppm)
				or	less?		
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM		
SUBTR PURCHASE during Al	-	
SUB	TOTAL	
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL
	+	

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	LEAKING?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	NY	NY	NY	NY	NY			
Door Gaskets + Seating	NY	N Y	N Y	NY	NY			
Pump	NY	NY	N Y	NY	NY			
Solvent Tanks + containers	NY	N Y	N Y	NY	NY			
Water Separators	N Y	N Y	N Y	NY	NY			
Muck Cooker	NY	NY	N Y	NY	NY			
Still	N Y	N Y	N Y	NY	NY			
Exhaust Dampers	N Y	N Y	N Y	NY	NY			
Diverter Valves	NY	NY	N Y	NY	NY			
Filter Gaskets + Seating	ΝΥ	NY	N Y	N Y	NY			
All Filter Housings	ΝΥ	NY	N Y	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

AUGUST 2022

Su	М	Tu	W	Th	F	Sa
	1	Z Temp logged Inspect logged	3	4	5	6
7	8	9 Temp logged Inspect logged	10	11	12	13
14	15	16 Temp logged Inspect logged	17	18	19	20
21	22	23 Temp logged Inspect logged	24	25	26	27
28	29	30 Temp logged Inspect logged	31			

SEPTEMBER 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

DATE	PRESSURE		TEMP (°F or °C)	Is press	sure within ecs? Or is	[PCE] in CA	[PCE] in Drum
DAIL	High	High Low		temp 45	5º F (7.2º C) less?	Exhaust (ppm)	(ppm)
				V	N	(ррііі)	
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM						
SUBTR PURCHASE during SEP	-					
SUB	SUBTOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	NG?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	NY	N Y	NY	N Y			
Door Gaskets + Seating	N Y	NY	N Y	NY	NY			
Pump	N Y	NY	N Y	NY	N Y			
Solvent Tanks + containers	N Y	NY	N Y	NY	NY			
Water Separators	N Y	NY	N Y	NY	NY			
Muck Cooker	N Y	NY	NY	NY	NY			
Still	N Y	NY	N Y	NY	NY			
Exhaust Dampers	N Y	NY	N Y	NY	NY			
Diverter Valves	ΝΥ	ΝΥ	ΝΥ	NY	NY			
Filter Gaskets + Seating	N Y	NY	N Y	NY	NY			
All Filter Housings	N Y	ΝΥ	ΝΥ	N Y	NY			
Waste Containers	ΝΥ	NY	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

SEPTEMBER 2022

Su	M	Tu	W	Th	F	Sa
				1	2	3
4	5	6 Temp logged Inspect logged	7	8	9	10
11	12	13 Temp logged Inspect logged	14	15	16	17
18	19	20 Temp logged Inspect logged	21	22	23	24
25	26	27 Temp logged Inspect logged	28	29	30	

OCTOBER 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL

(New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

DATE		SURE	TEMP (°F or °C)	Is pres	sure within ecs? Or is	[PCE] in	[PCE] in Drum
DAIL	High	Low	(1 01 0)	temp 45	5º F (7.2º C) less?	Exhaust (ppm)	(ppm)
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM							
SUBTR PURCHASE during OC	-						
SUB	TOTAL						
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL					
	+						
	+						

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	LEAKING?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	NY	NY	NY	N Y			
Door Gaskets + Seating	N Y	N Y	N Y	NY	ΝΥ			
Pump	N Y	NY	N Y	NY	N Y			
Solvent Tanks + containers	N Y	N Y	N Y	NY	ΝΥ			
Water Separators	N Y	N Y	N Y	NY	ΝΥ			
Muck Cooker	N Y	NY	NY	NY	NY			
Still	N Y	NY	NY	NY	N Y			
Exhaust Dampers	N Y	N Y	N Y	NY	ΝΥ			
Diverter Valves	ΝΥ	ΝΥ	ΝΥ	NY	NY			
Filter Gaskets + Seating	N Y	N Y	N Y	NY	ΝΥ			
All Filter Housings	N Y	ΝΥ	ΝΥ	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

OCTOBER 2022

Su	M	Tu	W	Th	F	Sa
30	31					1
2	3	Temp logged Inspect logged	5	6	7	8
9	10	11 Temp logged Inspect logged	12	13	14	15
16	17	18 Temp logged Inspect logged	19	20	21	22
23	24	25 Temp logged Inspect logged	26	27	28	29

NOVEMBER 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) Use pressure if pressure gauges are present on refrigeration unit

	.a. =age	x 0.000,	000 00000.00	e gaagee are present on reingeration and			
DATE	PRES	SURE	TEMP (°F or °C)		sure within ecs? Or is	[PCE] in CA	[PCE] in Drum
DAIL	High	Low	(1010)	temp 45	5º F (7.2º C)	Exhaust	(ppm)
				or	less?	(ppm)	
				Y	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM						
SUBTR PURCHASE during NO	-					
SUB	TOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKII	NG?						
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	N Y	N Y	N Y	NY	ΝΥ			
Door Gaskets + Seating	NY	NY	N Y	NY	ΝΥ			
Pump	ΝΥ	NY	NY	NY	ΝΥ			
Solvent Tanks + containers	NY	NY	N Y	NY	ΝΥ			
Water Separators	ΝΥ	NY	NY	NY	ΝΥ			
Muck Cooker	ΝΥ	NY	NY	NY	ΝΥ			
Still	NY	NY	N Y	NY	ΝΥ			
Exhaust Dampers	NY	NY	N Y	NY	ΝΥ			
Diverter Valves	ΝΥ	NY	NY	NY	ΝΥ			
Filter Gaskets + Seating	ΝΥ	NY	NY	NY	ΝΥ			
All Filter Housings	ΝΥ	NY	NY	NY	ΝΥ			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	ΝΥ	ΝΥ	LABELED Y N DAT	ED Y N	

NOVEMBER 2022

Su	M	Tu	W	Th	F	Sa
		Temp logged Inspect logged	2	3	4	5
6	7	8 Temp logged Inspect logged	9	10	11	12
13	14	15 Temp logged Inspect logged	16	17	18	19
20	21	22 Temp logged Inspect logged	23	24	25	26
27	28	Temp logged Inspect logged	30			

DECEMBER 2022

Weekly RC PRESSURE/TEMPERATURE and Carbon Adsorber [PCE] PCE PURCHASES 12-MONTH TOTAL (New Small and Large Area Cleaners) (Use pressure if pressure gauges are present on refrigeration unit

		SURE	TEMP	Is press	sure within	[PCE] in	[PCE] in
DATE	High	Low	· (°F or °C)	or °C) mfr specs? Or is temp 45° F (7.2°C) or less?		CA Exhaust (ppm)	Drum (ppm)
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		
				Υ	N		

TOTAL FROM						
SUBTR PURCHASE during DEC	-					
SUB	TOTAL					
PURCHASE DATE	PURCHASE AMOUNT	12 MONTH RUNNING TOTAL				
	+					
	+					

LEAK INSPECTIONS (TEST METHOD: sight smell (ss) or with a leak detector (ld))

COMPONENT INSPECTED	LEAKING?							
Date						DATE PARTS	DATE PARTS	DATE
TEST METHOD						ORDERED	RECEIVED	REPAIRED
Hose + Pipe Connections	NY	NY	NY	NY	NY			
Door Gaskets + Seating	NY	N Y	N Y	NY	NY			
Pump	N Y	NY	N Y	NY	NY			
Solvent Tanks + containers	NY	N Y	N Y	NY	NY			
Water Separators	N Y	N Y	N Y	NY	NY			
Muck Cooker	N Y	NY	N Y	NY	NY			
Still	N Y	N Y	N Y	NY	NY			
Exhaust Dampers	N Y	N Y	N Y	NY	NY			
Diverter Valves	N Y	NY	N Y	NY	NY			
Filter Gaskets + Seating	ΝΥ	NY	N Y	N Y	NY			
All Filter Housings	ΝΥ	NY	N Y	N Y	NY			
Waste Containers	ΝΥ	ΝΥ	ΝΥ	NY	NY	LABELED Y N DAT	ED Y N	

DECEMBER 2022

Su	M	Tu	W	Th	F	Sa
				1	2	3
4	5	6 Temp logged Inspect logged	7	8	9	10
11	12	13 Temp logged Inspect logged	14	15	16	17
18	19	20 Temp logged Inspect logged	21	22	23	24
25	26	27 Temp logged Inspect logged	28	29	30	31

RECORDKEEPING INSTRUCTIONS

July 2022

PCE Purchases Running Total

Enter 12 month running total from last month (June 2021).

55 TOTAL FROM LAST MONTH- June 2022 SUBTRACT PCE **PURCHASED** June 2021 45 **SUBTOTAL** 12 MONTH **PURCHASE PURCHASE** RUNNING DATE AMOUNT TOTAL 60

Record the date you

purchased PCE this

month, if any.

Enter the amount of PCE you bought during this month <u>last</u> year (2020), from <u>last</u> year's records or calendar.

Subtract <u>last</u> years PCE purchases for this month, July 2020 the purchased PCE was 10 gallons, so 55 - 10 = 45. This is your 12 month running total if you do not buy any PCE this month.

This is your new 12 month running total if you bought PCE this month. Record the bottom number in this column on next month's form on the "TOTAL FROM LAST MONTH" line.

If you bought PCE this month, record the amount and add it to the subtotal. This amount will also go on next year's calendar for this same month on the "SUBTRACT PCE PURCHASED" line.

If you bought none write in "0".

You may use this calendar to keep records required for air quality compliance. Keep these records <u>at</u> your facility for **5 years**.

REFRIGERATED CONDENSER (RC) EVALUATION, Inspect the RC control device each week using the pressure method or if pressure gauges are not present use the temperature method. Record date, readings and findings in the space provided.

Refrigeration System Pressure Method: Evaluate the high and low pressure readings on the compressor unit during the drying phase. Compare readings to manufactures specifications.

RC Outlet Temperature Method: Check the outlet temperature of the refrigerated condenser. Is the temperature less than or equal to 45° F (7.2° C)?" Check "Y" for "yes" or "N" for "no". If you checked "N," the machine must be repaired.

LEAK INSPECTIONS-Once each month a handheld leak detector <u>must</u> be used at each facility

If you buy **less than 140 gallons** of PCE per year, you must conduct and record leak inspections at least <u>every other week</u>.

If you buy **140 gallons or more** of PCE per year, you must conduct and record inspections EVERY week.

Record the results of the inspections on the calendar. If leaks are found, they must be repaired within 24 hours. Indicate in the "DATE REPAIRED" block when repairs are completed.

If parts must be purchased, indicate the date(s) they are ordered and the date(s) installed. Parts must be ordered within 2 working days of leak detection and installed within 5 working days of receipt.

Dry Cleaner Perchloroethylene NESHAP Notification of Compliance

1.	Perchloroethylene (PCE) Dry Cleaning Facility Owner and Business Information: Print or type the following for each separately located dry cleaning facility. The owner of more than one facility must fill out a separate form for each facility.												
	Owner/Operator_												
	Company Name_												
	Mailing Address_												
	City		State		Zip								
	Phone Number		Fax		E-mail								
		acility Address (If different from the above mailing address)											
	Street Address												
			State										
	Phone Number _	Phone Number											
	Comments:												
2.													
	Gallo	ns	Highest expe	cted 12 m	onth total	Gallons							
3.	Facility's source	classificati	on based on the Po	CE used a	nt this facility (Dry	to Dry){Transfer}:							
	Small Area Source (use less than 140 {200} gallons of PCE per year)												
	Large Area Source (use 140 - 2,100 {200 – 1,800} gallons of PCE per year)												
	Major Source (use greater than 2,100 {1,800} gallons of PCE per year)												
4.	List all machines	List all machines located at this facility:											
	Manufacturer	Model	Serial Number	Installe	ed (mm-dd-yy)	Control Device							
	-												

Dry Cleaner Perchloroethylene NESHAP

Notification of Compliance

5.	Circle one:							
	Collocated residential (located in a building with residential units). Number of Residential Units							
	Collocated commercial (located in a building with commercial)							
	Standalone							
6.	Halogenated hydrocarbon detector or PCE gas analyzer available? Y N Type							
7.	Comments:							
8.	Compliance Certification							
	By checking this box you are certifying the above equipment is in compliance with all applicable requirements of 40 CFR Part 63 Subpart M NESHAP for Perchloroethylene Dry Cleaning Facilities, including performing all inspections and recordkeeping.							
Pri	int or type the name and title of the Responsible Official for the dry cleaning facility:							
	Name of Responsible Official Title							
	ERTIFY THE INFORMATION CONTAINED IN THIS REPORT TO BE ACCURATE AND TRUE TO THE ST OF MY KNOWLEDGE.							
	Signature of Responsible Official Date							
the	his notification is to be submitted to the Utah Division of Air Quality within 30 days of any of ese events (please check all that apply): start-up of a new location old machines are replaced or additional dry cleaning machines are added to a facility the amount of PCE purchased in a year exceeds the threshold previously reported in #3 change of location or ownership							

October 2019

Instructions for Completing the Notification of Compliance

This notice is required for dry cleaners subject to the 40 CFR 63 Subpart M NESHAP for Perchloroethylene Dry Cleaning Facilities. This notice is for existing and new machines using perchloroethylene (PCE). If you need to submit compliance information for a transfer machine or a system that is located in a building with a residence, please contact the Utah Division of Air Quality, Small Business Environmental Assistance Program 801-536-4000 or 800-270-4440.

This notification is to be submitted to the Division of Air Quality on or before 30 days after start-up of new or used dry cleaning machines, if PCE use increases or if additional dry cleaning machines are added to a facility which has previously filed.

Copies of regulations and guidance documents are available from the Utah Division of Air Quality, Small Business Environmental Assistance Program 801-536-4000 or 800-270-4440.

1. Dry Cleaning Facility Address and Location

Owner/Operator - The name of the corporation, agency or individual that has ownership or control of the dry cleaning facility for which this notification is submitted. Owner/Facility Address - Write in the mailing address of the owner and the facility.

2. Yearly PCE solvent consumption:

Write in the total amount, in gallons, of PCE consumed (purchased) at the facility during the previous twelve months. The total amount is for all machines, new and existing, at the facility. New owners of used machines should obtain solvent purchase records from the previous owner. If this is a new machine, don't include the initial PCE charge to fill the tank in the consumption calculation. Contact the manufacturer of the machine to estimate the PCE consumption based on future usage. Note: If this is a new facility or dry cleaning machine the consumption will be an estimate of future consumption.

3. Facility's source classification based on the PCE used at this facility: Using the amount of PCE written in No. 2 above, select the facility's classification:

Indicate with an "X" which classification applies to the facility.

4. List the machines located at this facility:

List **all** the machines for this location. For each machine located at the facility, list the make, model, serial number (if it can be found), installed date and the control device required for the machine. Use 'Control Device Requirements' table below for guidelines for control device requirements. Write the date of the machine's installation in the date-month-year (dd-mm-yy) format.

If a machine listed as an 'existing' machine is moved to another location, it becomes new installation and must meet all the applicable requirements. Note: A facility can have both new and old machines at the same location. Different machines can have different control and reporting requirements at the same location.

If a facility has machines initially <u>installed before December 9, 1991</u> the machine will be classified as "existing". If a facility has machines initially <u>installed on or after</u> December 9, 1991, the source will be classified as "new".

Control Device Requirements

ClassificationControl DeviceExisting Small Area SourceNone Required

Existing Large Area Source Refrigerated Condenser

(Carbon Adsorbers if machine installed before 11-22-93)

New Small and Large Area Source Refrigerated Condenser

Major and ALL New Area Sources after December 21, 2005. Refrigerated Condenser and pass the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened.

- **5. Collocated** means located in a building with residential or commercial.
- **6.** Halogenated hydrocarbon detector or PCE gas analyzer available? Indicate Yes or No and the type, make and model.
- **7. Comments:** If this notification is a change of owner, address or name change include a comment explaining this on the 'Comments' line.
- **8. Compliance certification:** Indicate with an "X" if you are in compliance. Compliance means using the required control devices, performing the required pollution prevention, recordkeeping and reporting as required by the Subpart M NESHAP for Perchloroethylene Dry Cleaning Facilities.

Responsible Official Certification

Print or type the name of the responsible official and his/her title. The responsible official must sign and date this form.

A Responsible Official can be:

- The president, vice president, secretary or treasurer of the company that owns the dry cleaning facility,
- An owner of the dry cleaning facility,
- The manager of the dry cleaning facility, or,
- A government official, if the dry cleaning facility is owned by the Federal, State, City or County government,
- A ranking military officer, if the dry cleaning facility is located at a military base.

Make a copy of the completed form for your records.

Mail the signed and completed Notification of Compliance status form to:

Utah Division of Air Quality
Minor Source Compliance Section
P.O. Box 144820
Salt Lake City, UT 84114-4820

Small Business Environmental Assistance Program Utah Division of Air Quality P.O. Box 144820 Salt Lake City, UT 84114-4820

Presorted Standard U.S. Postage PAID Salt Lake City, UT Permit No. 4621

Notes:

A hand-held hydrocarbon detector or PCE gas analyzer <u>is required</u> to be used ONCE EACH MONTH to conduct the required equipment leak inspections, regardless of the size of the facility (small, large, major) or the installation date(s) of the dry cleaning equipment.

Each dry cleaning system installed after December 21, 2005 at an area source shall route the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and pass the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened. The carbon adsorber must be desorbed in accordance with manufacturer's instructions.

References: Title 40 Code of Federal Regulations Part 63 Subpart M (National Perchloroethylene Air Emission Standards for Dry Cleaning Facilities) [last revised July 11, 2008]

Utah SBEAP Website: https://deq.utah.gov/air-quality/small-business-environmental-assistance-program-air-quality-research-program **EPA Website:** https://www.epa.gov/stationary-sources-air-pollution/clean-air-act-guidelines-and-

standards-solvent-use-and-surface

Need Help?

For additional information on Dry Cleaning operations, please contact Utah's Small Business Environmental Assistance Program at: 1-800-270-4440 or 1-801-536-4000