WASTELOAD ANALYSIS [WLA] Addendum: Statement of Basis SUMMARY Discharging Facility: Nephi Rubber UPDES No: UT-0025097 Design Flow Current Flow: 0.08 MGD Design Flow 0.08 MGD Nephi Irrigation Ditch Receiving Water: Stream Classification: 2B, 4 Stream Flows [cfs]: 0.0 Summer (July-Sept) Ephemeral wash Ephemeral wash 0.0 Fall (Oct-Dec) Ephemeral wash 0.0 Winter (Jan-Mar) Ephemeral wash 0.0 Spring (Apr-June) 0.0 Average Water Quality Data Stream TDS Values: 307.0 Summer (July-Sept) Water Quality Data 307.0 Fall (Oct-Dec) 307.0 Winter (Jan-Mar) Water Quality Data 307.0 Spring (Apr-June) Water Quality Data WQ Standard: **Effluent Limits:** 0.08 MGD Design Flow Flow, MGD: 5.0 Indicator BOD, mg/l: 25.0 Summer 5.0 30 Day Average Dissolved Oxygen, mg/l 5.0 Summer Varies Function of pH and Temperature TNH3, Chronic, mg/l: 5.9 Summer 1207.2 Summer TDS, mg/l: **Modeling Parameters:** Acute River Width: 50.0% Chronic River Width: 100.0%

Antidegradation Level II Review is not required. Basic Renewal, no increase in flow or concentration

Date: 11/26/2012

Permit Writer:		7 2		
WLA by:	7/oil	M	ulun	1-3-17/3
WQM Sec. Approval:	-			
TMDL Sec. Approval:	***************************************			

WASTELOAD ANALYSIS [WLA] Addendum: Statement of Basis

26-Nov-12 4:00 PM

UPDES No: UT-0025097

Facilities:

Nephi Rubber

Discharging to:

Nephi Irrigation Ditch

I. Introduction

Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses [R317-2-8, UAC]. Projected concentrations are compared to numeric water quality standards to determine acceptability. The anti-degradation policy and procedures are also considered. The primary in-stream parameters of concern may include metals (as a function of hardness), total dissolved solids (TDS), total residual chlorine (TRC), un-ionized ammonia (as a function of pH and temperature, measured and evaluated interms of total ammonia), and dissolved oxygen.

Mathematical water quality modeling is employed to determine stream quality response to point source discharges. Models aid in the effort of anticipating stream quality at future effluent flows at critical environmental conditions (e.g., low stream flow, high temperature, high pH, etc).

The numeric criteria in this wasteload analysis may always be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

II. Receiving Water and Stream Classification

Nephi Irrigation Ditch:

2B, 4

Antidegradation Review:

Antidegradation Level II Review is not required. Basic Renewa

III. Numeric Stream Standards for Protection of Aquatic Wildlife

Total Ammonia (TNH3)

Varies as a function of Temperature and pH Rebound. See Water Quality Standards

Chronic Total Residual Chlorine (TRC)

0.011 mg/l (4 Day Average) 0.019 mg/l (1 Hour Average)

Chronic Dissolved Oxygen (DO)

5.00 mg/l (30 Day Average) N/A mg/l (7Day Average) 3.00 mg/l (1 Day Average

Maximum Total Dissolved Solids

1200.0 mg/l

Acute and Chronic Heavy Metals (Dissolved)

	4 Day Average (Chror	nic) Standard	1 Hour Average (Acute) Standard		
Parameter	Concentration	Load*	Concentration		Load*
Aluminum	87.00 ug/l**	0.058 lbs/day	750.00	ug/l	0.500 lbs/day
Arsenic	190.00 ug/l	0.127 lbs/day	340.00	ug/l	0.227 lbs/day
Cadmium	0.61 ug/l	0.000 lbs/day	6.52	ug/l	0.004 lbs/day
Chromium III	211.92 ug/l	0.141 lbs/day	4433.71	ug/l	2.958 lbs/day
ChromiumVI	11.00 ug/l	0.007 lbs/day	16.00	ug/l	0.011 lbs/day
Copper	23.85 ug/l	0.016 lbs/day	39.41	ug/i	0.026 lbs/day
Iron			1000.00	ug/l	0.667 lbs/day
Lead	12.88 ug/l	0.009 lbs/day	330.60	ug/l	0.221 lbs/day
Mercury	0.0120 ug/l	0.000 lbs/day	2.40	ug/l	0.002 lbs/day
Nickel	132.13 ug/l	0.088 lbs/day	1188 .44	ug/l	0.793 lbs/day
Selenium	4.60 ug/l	0.003 lbs/day	20.00	ug/l	0.013 lbs/day
Silver	N/A ug/l	N/A lbs/day	25.04	ug/l	0.017 lbs/day
Zinc	303.93 ug/l	0.203 lbs/day	303.93	ug/l	0.203 lbs/day
* Allow	ed below discharge	•			

^{**}Chronic Aluminum standard applies only to waters with a pH < 7.0 and a Hardness < 50 mg/l as CaCO

Metals Standards Based upon a Hardness of 300 mg/l as CaCO3

Organics [Pesticides]						
	4 Day Average (Chron	ic) Standard	1 Hour Average (Acute) Standard			
Parameter	Concentration	Load*	Concentration		Load*	
Aldrin		75	1.500	ug/l	0.001 lbs/day	
Chlordane	0.004 ug/l	0.003 lbs/day	1.200	ug/l	0.001 lbs/day	
DDT, DDE	0.001 ug/l	0.001 lbs/day	0.550	ug/l	0.000 lbs/day	
Dieldrin	0.002 ug/l	0.001 lbs/day	1.250	ug/l	0.001 lbs/day	
Endosulfan	0.056 ug/l	0.038 lbs/day	0.110	ug/l	0.000 lbs/day	
Endrin	0.002 ug/l	0.002 lbs/day	0.090	ug/l	0.000 lbs/day	
Guthion			0.010	ug/l	0.000 lbs/day	
Heptachlor	0.004 ug/l	0.003 lbs/day	0.260	ug/l	0.000 lbs/day	
Lindane	0.080 ug/l	0.054 lbs/day	1.000	ug/l	0.001 lbs/day	
Methoxychlor			0.030	ug/l	0.000 lbs/day	
Mirex			0.010	ug/l	0.000 lbs/day	
Parathion			0.040	ug/l	0.000 lbs/day	
PCB's	0.014 ug/l	0.009 lbs/day	2.000	ug/l	0.001 lbs/day	
Pentachlorophenol	13.00 ug/l	8.742 lbs/day	20.000	ug/l	0.013 lbs/day	
Toxephene	0.0002 ug/l	0.000 lbs/day	0.7300	ug/l	0.000 lbs/day	

IV. Numerio		ndards for Protection of Day Average (Chronic		1 Hour Average (Ad	cute) Standard
72		Concentration	Load*	Concentration	Load*
	Arsenic			100.0 ug/l	lbs/day
	Boron			750.0 ug/l	lbs/day
	Cadmium			10.0 ug/l	lbs/day
	Chromium			. 100.0 ug/l	lbs/day
	Copper			200.0 ug/l	lbs/day

Lead	100.0 ug/i	lbs/day
Selenium	50.0 ug/l	lbs/day
TDS, Summer	1200.0 mg/l	0.40 tons/day

V. Numeric Stream Standards for Protection of Human Health (C	Class 1C Waters)
---	------------------

4	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
Metals	Concentration	Load*	Concentration	Load*	
Arsenic			ug/l	lbs/day	
Barium			ug/l	lbs/day	
Cadmium			ug/l	lbs/day	
Chromium			ug/l	lbs/day	
Lead			ug/l –	lbs/day	
Mercury			ug/l	lbs/day	
Selenium			ug/l	lbs/day	
Silver			ug/l	lbs/day	
Fluoride (3)			ug/l	lbs/day	
to			ug/i	lbs/day	
Nitrates as N			ug/l	lbs/day	
Chlorophenoxy Herbicid	les				
2,4-D			ug/l	lbs/day	
2,4,5-TP		¥	ug/i	lbs/day	
Endrin			ug/l	lbs/day	
ocyclohexane (Lindane)			ug/l	lbs/day	
Methoxychlor			ug/l	lbs/day	
Toxaphene			ug/l	lbs/day	

VI. Numeric Stream Standards the Protection of Human Health from Water & Fish Consumption [Toxics]

Maximum Conc., ug/l - Acute Standards

	Class 1C			Class 3A, 3B	
Toxic Organics	[2 Liters/Day for 7	70 Kg Perso	on over 70 Yr.]	[6.5 g for 70 Kg Perso	n over 70 Yr.]
Acenaphthene	ug/l		lbs/day	ug/l	lbs/day
Acrolein	ug/l		lbs/day	ug/l	lbs/day
Acrylonitrile	ug/l		lbs/day	ug/l	lbs/day
Benzene	ug/l		lbs/day	ug/l	lbs/day
Benzidine	ug/l		lbs/day	ug/l	lbs/day
Carbon tetrachloride	ug/l		lbs/day	ug/l	lbs/day
Chlorobenzene	ug/l		lbs/day	ug/l	lbs/day
1,2,4-Trichlorobenzene					
Hexachlorobenzene	ug/l		lbs/day	ug/l	lbs/day
1,2-Dichloroethane	ug/l		lbs/day	ug/l	lbs/day
1,1,1-Trichloroethane					
Hexachloroethane	ug/l		lbs/day	ug/l	lbs/day
1,1-Dichloroethane					
1,1,2-Trichloroethane	ug/l		lbs/day	ug/l	lbs/day
1,1,2,2-Tetrachloroethai	ug/l		lbs/day	ug/l	lbs/day
Chloroethane			•	ug/l	lbs/day
Bis(2-chloroethyl) ether	ug/l		lbs/day	ug/l	lbs/day
2-Chloroethyl vinyl ether	ug/l	*	lbs/day	ug/l	lbs/day

2-Chloronaphthalene	ug/l	lbs/day	ug/l	lbs/day
2,4,6-Trichlorophenol	ug/l	lbs/day	ug/l	lbs/day
p-Chloro-m-cresol	~3	,	ug/l	lbs/day
Chloroform (HM)	ug/l	lbs/day	ug/l	lbs/day
2-Chlorophenol	ug/l	lbs/day	ug/l	lbs/day
1,2-Dichlorobenzene	ug/l	lbs/day	ug/l	lbs/day
1,3-Dichlorobenzene	ug/l	lbs/day	ug/l	lbs/day
1,4-Dichlorobenzene	ug/l	lbs/day	ug/l	lbs/day
3,3'-Dichlorobenzidine	ug/l	lbs/day	ug/l	lbs/day
1,1-Dichloroethylene	ug/l	lbs/day	ug/l	lbs/day
1,2-trans-Dichloroethyle	ug/l	lbs/day	ug/l	lbs/day
2,4-Dichlorophenol	ug/l	lbs/day	ug/l	lbs/day
1,2-Dichloropropane	ug/l	lbs/day	ug/l	lbs/day
1,3-Dichloropropylene	ug/l	lbs/day	ug/l	lbs/day
2,4-Dimethylphenol	ug/l	lbs/day	ug/l	lbs/day
2,4-Dinitrotoluene	ug/l	lbs/day	ug/l	lbs/day
2,6-Dinitrotoluene	ug/l	lbs/day	ug/l	lbs/day
1,2-Diphenylhydrazine	ug/l	lbs/day	ug/l	lbs/day
Ethylbenzene	ug/l	lbs/day	ug/l	lbs/day
Fluoranthene	ug/l	lbs/day	ug/l	lbs/day
4-Chlorophenyl phenyl ethe	-	155,443	ugh	Dorday
4-Bromophenyl phenyl ethe				
Bis(2-chloroisopropyl) e	ug/l	lbs/day	ug/l	lbs/day
Bis(2-chloroethoxy) met	ug/l	lbs/day	ug/l	lbs/day
Methylene chloride (HM	·	lbs/day	ug/l	lbs/day
Methyl chloride (HM)	ug/l ug/l	lbs/day	ug/l	lbs/day
• •		lbs/day	ug/l	lbs/day
Methyl bromide (HM)	ug/l	lbs/day	ug/l	lbs/day
Bromoform (HM)	ug/l	lbs/day	ug/l	lbs/day
Dichlorobromomethanel Chlorodibromomethane	ug/l	lbs/day	ug/l	lbs/day
	ug/l	lbs/day	ug/l	lbs/day
Hexachlorobutadiene(c)	ug/l	lbs/day	ug/l	lbs/day
Hexachlorocyclopentadi	ug/l	lbs/day	ug/l	lbs/day
Isophorone	ug/l	ibs/day	ugn	1557 day
Naphthalene	uall	lbs/day	ug/l	lbs/day
Nitrobenzene	ug/l	lbs/day	ug/ł	lbs/day
2-Nitrophenol	ug/l	lbs/day	ug/l	lbs/day
4-Nitrophenol 2,4-Dinitrophenol	ug/l	lbs/day	ug/l	lbs/day
•	ug/l	lbs/day	ug/l	lbs/day
4,6-Dinitro-o-cresol N-Nitrosodimethylamine	ug/l ug/l	lbs/day	ug/l	lbs/day
N-Nitrosodiphenylamine	ug/l	lbs/day	ug/l	lbs/day
N-Nitrosodi-n-propylami	ug/l	lbs/day	ug/l	lbs/day
Pentachlorophenol	ug/l	lbs/day	ug/l	lbs/day
Phenol	ug/l	lbs/day	ug/l	lbs/day
Bis(2-ethylhexyl)phthala	ug/l	lbs/day	ug/l	lbs/day
· · · · · · · · · · · · · · · · · · ·	_	lbs/day	ug/l	lbs/day
Butyl benzyl phthalate	ug/l	lbs/day	ug/l	lbs/day
Di-n-butyl phthalate	ug/l	ibs/uay	mAu.	ibo/day
Di-n-octyl phthlate	um fl	lbs/day	ug/l	lbs/day
Diethyl phthalate	ug/l	lbs/day	ug/l	lbs/day
Dimethyl phthlate	ug/l	lbs/day	ug/i	lbs/day
Benzo(a)anthracene (P/	ug/l	ib5/uay	ug/i	ibarday

Benzo(a)pyrene (PAH)	ug/l	lbs/day	ug/l	lbs/day
Benzo(b)fluoranthene (F	ug/l	lbs/day	ug/l	lbs/day
Benzo(k)fluoranthene (F	ug/l	lbs/day	ug/l	lbs/day
Chrysene (PAH)	ug/l	lbs/day	ug/l	lbs/day
Acenaphthylene (PAH)	-5	150,000	agn	iborday
Anthracene (PAH)	ug/l	lbs/day	ug/l	lbs/day
Dibenzo(a,h)anthracene	ug/l	lbs/day	ug/l	lbs/day
Indeno(1,2,3-cd)pyrene	ug/l	lbs/day	ug/l	lbs/day
Pyrene (PAH)	ug/l	lbs/day	ug/i	lbs/day
Tetrachloroethylene	ug/l	lbs/day	ug/l	lbs/day
Toluene	ug/l	lbs/day	ug/l	lbs/day
Trichloroethylene	ug/l	lbs/day	ug/l	lbs/day
Vinyl chloride	ug/l	lbs/day	ug/l	lbs/day
viny, omende	49/1	ibs/day	ugn	lbs/day
Pesticides				lbs/day
Aldrin	ug/l	lbs/day	ug/l	lbs/day
Dieldrin	ug/l	ibs/day	ug/l	lbs/day
Chlordane	ug/l	lbs/day	ug/l	lbs/day
4,4'-DDT	ug/l	lbs/day	ug/l	lbs/day
4,4'-DDE	ug/l	lbs/day		lbs/day
4,4'-DDD	ug/l	lbs/day	ug/l	lbs/day
alpha-Endosulfan	ug/l	lbs/day	ug/l	-
beta-Endosulfan	ug/l	lbs/day	ug/l	lbs/day
Endosulfan sulfate	ug/i	lbs/day	ug/l	lbs/day
Endrin		•	ug/l	lbs/day
Endrin aldehyde	ug/l	lbs/day	ug/l	lbs/day
Heptachlor	ug/l	lbs/day	ug/l	lbs/day
Heptachlor epoxide	ug/l	lbs/day	ug/i	lbs/day
rieptaciiloi epoxide				
PCB's				
PCB 1242 (Arochlor 124	ug/l	lbs/day	ua/l	lha/day
PCB-1254 (Arochlor 125	-	lbs/day	ug/l	lbs/day
PCB-1221 (Arochlor 122	ug/l	lbs/day	ug/l	lbs/day
PCB-1232 (Arochlor 12)	ug/l	lbs/day	ug/l	lbs/day
PCB-1248 (Arochlor 124	ug/l	•	ug/l	lbs/day
PCB-1240 (Arochlor 124	ug/l	lbs/day	ug/l	lbs/day
PCB-1016 (Arochlor 10'	ug/l	lbs/day	ug/i	lbs/day
1 OB-1010 (A10011101 10	ug/l	lbs/day	ug/l	lbs/day
Pesticide				
Toxaphene	ug/i		ug/i	lbs/day
Toxaphone	ugn		ug/i	ibsruay
Dioxin				
Dioxin (2,3,7,8-TCDD)	ug/i	lbs/day		
510,011 (2,0,1,011000)	ug/.	ib3/day		
Metals				
Antimony	ug/l	lbs/day		
Arsenic	ug/l	lbs/day	ug/l	lbs/day
Asbestos	ug/l	lbs/day	ug/I	ibarday
Beryllium	ugn	issiday		
Cadmium				
Cadifilati				

Chromium (III) Chromium (VI)				
Copper				
Cyanide	ug/l	lbs/day	ug/l	lbs/day
Lead	ug/l	lbs/day		
Mercury			ug/I	lbs/day
Nickel			ug/l	lbs/day
Selenium	ug/l	lbs/day		
Silver	ug/l	lbs/day		
Thallium			ug/l	lbs/day
Zinc				

There are additional standards that apply to this receiving water, but were not considered in this modeling/waste load allocation analysis.

VII. Mathematical Modeling of Stream Quality

Model configuration was accomplished utilizing standard modeling procedures. Data points were plotted and coefficients adjusted as required to match observed data as closely as possible.

The modeling approach used in this analysis included one or a combination of the following models.

- (1) The Utah River Model, Utah Division of Water Quality, 1992. Based upon STREAMDO IV (Region VIII) and Supplemental Ammonia Toxicity Models; EPA Region VIII, Sept. 1990 and QUAL2E (EPA, Athens, GA).
- (2) Utah Ammonia/Chlorine Model, Utah Division of Water Quality, 1992.
- (3) AMMTOX Model, University of Colorado, Center of Limnology, and EPA Region 8
- (4) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

Coefficients used in the model were based, in part, upon the following references:

- (1) Rates, Constants, and Kinetics Formulations in Surface Water Quality Modeling. Environmental Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency, Athens Georgia. EPA/600/3-85/040 June 1985.
- (2) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al. Harper Collins Publisher, Inc. 1987, pp. 644.

VIII. Modeling Information

The required information for the model may include the following information for both the upstream conditions at low flow and the effluent conditions:

Flow, Q, (cfs or MGD) D.O. mg/l

Temperature, Deg. C. Total Residual Chlorine (TRC), mg/l

pH Total NH3-N, mg/l

BOD5, mg/l
Metals, ug/l
Toxic Organics of Concern, ug/l

Other Conditions

In addition to the upstream and effluent conditions, the models require a variety of physical and biological coefficients and other technical information. In the process of actually establishing the permit limits for an effluent, values are used based upon the available data, model calibration, literature values, site visits and best professional judgement.

Model Inputs

The following is upstream and discharge information that was utilized as inputs for the analysis. Dry washes are considered to have an upstream flow equal to the flow of the discharge.

Current Upstream Information Stream

Critical	Tomn	-U	T NH2	PODE	DO	TDC	TDS
	-	=					
cfs	Deg. C		mg/l as N	mg/l	mg/l	mg/l	mg/l
0.0	20.0	7.6	0.10	0.50	10.74	0.00	307.0
0.0	12.0	7.6	0.10	0.50	****	0.00	307.0
0.0	4.0	7.6	0.10	0.50	***	0.00	307.0
0.0	12.0	7.6	0.10	0.50		0.00	307.0
Al	As	Cd	Crlll	CrVI	Copper	Fe	Pb
ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l
1.59*	0.53*	0.053*	0.53*	2.65*	0.53*	0.83*	0.53*
Hg	Ni	Se	Ag	Zn	Boron		
ug/l	ug/l	ug/l	ug/l	ug/l	ug/l		
0.0000	0.53*	1.06*	0.1*	0.053*	10.0	*	1/2 MDL
	Cfs 0.0 0.0 0.0 0.0 Al ug/l 1.59* Hg ug/l	Critical Low Flow Temp. cfs Deg. C 0.0 20.0 0.0 12.0 0.0 4.0 0.0 12.0 Al As ug/l ug/l 1.59* 0.53* Hg Ni ug/l ug/l	Critical Low Flow Temp. pH cfs Deg. C Deg. C 0.0 20.0 7.6 0.0 12.0 7.6 0.0 4.0 7.6 0.0 12.0 7.6 Al As Cd ug/l ug/l ug/l 1.59* 0.53* 0.053* Hg Ni Se ug/l ug/l ug/l	Critical Low Flow Temp. pH T-NH3 cfs Deg. C mg/l as N 0.0 20.0 7.6 0.10 0.0 12.0 7.6 0.10 0.0 4.0 7.6 0.10 0.0 12.0 7.6 0.10 Al As Cd CrIII ug/l ug/l ug/l ug/l 1.59* 0.53* 0.053* 0.53* Hg Ni Se Ag ug/l ug/l ug/l	Critical Low Flow Temp. pH T-NH3 BOD5 cfs Deg. C mg/l as N mg/l 0.0 20.0 7.6 0.10 0.50 0.0 12.0 7.6 0.10 0.50 0.0 4.0 7.6 0.10 0.50 0.0 12.0 7.6 0.10 0.50 Al As Cd CrIII CrVI ug/l ug/l ug/l ug/l ug/l 1.59* 0.53* 0.053* 0.53* 2.65* Hg Ni Se Ag Zn ug/l ug/l ug/l ug/l	Critical Low Flow Temp. pH T-NH3 BOD5 DO cfs Deg. C mg/l as N mg/l mg/l mg/l 0.0 20.0 7.6 0.10 0.50 10.74 0.0 12.0 7.6 0.10 0.50 0.0 4.0 7.6 0.10 0.50 0.0 12.0 7.6 0.10 0.50 Al As Cd Crlll CrVI Copper ug/l ug/l ug/l ug/l ug/l ug/l 1.59* 0.53* 0.053* 0.53* 2.65* 0.53* Hg Ni Se Ag Zn Boron ug/l ug/l ug/l ug/l ug/l	Critical Low Flow Temp. pH T-NH3 BOD5 DO TRC cfs Deg. C mg/l as N mg/l mg/l mg/l 0.0 20.0 7.6 0.10 0.50 10.74 0.00 0.0 12.0 7.6 0.10 0.50 0.00 0.0 4.0 7.6 0.10 0.50 0.00 0.0 12.0 7.6 0.10 0.50 0.00 Al As Cd Crlll CrVI Copper Fe ug/l ug/l ug/l ug/l ug/l ug/l 1.59* 0.53* 0.053* 0.53* 2.65* 0.53* 0.83* Hg Ni Se Ag Zn Boron ug/l ug/l ug/l ug/l ug/l

Projected Discharge Information

Season	Flow, M GD	Temp.	TDS mg/l	TDS tons/day
Summer	0.08000	15.6	307.00	0.10239
Fall	0.08000	15.6		
Winter	0.08000	15.6		
Spring	0.08000	15.6		

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

IX. Effluent Limitations

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort coincide with the environmental conditions expected at low stream flows.

Effluent Limitation for Flow based upon Water Quality Standards

In-stream criteria of downstream segments will be met with an effluent flow maximum value as follows:

Season	Daily Average	
Summer	0.080 MGD	0.124 cfs
Fall	0.080 MGD	0.124 cfs
Winter	0.080 MGD	0.124 cfs
Spring	0.080 MGD	0.124 cfs

Flow Requirement or Loading Requirement

The calculations in this wasteload analysis utilize the maximum effluent discharge flow of 0.08 MGD. If the discharger is allowed to have a flow greater than 0.08 MGD during 7Q10 conditions, and effluent limit concentrations as indicated, then water quality standards will be violated. In order to prevent this from occuring, the permit writers must include the discharge flow limitiation as indicated above; or, include loading effluent limits in the permit.

Effluent Limitation for Whole Effluent Toxicity (WET) based upon WET Policy

Effluent Toxicity will not occur in downstream segements if the values below are met.

WET Requirements	LC50 >	EOP Effluent	[Acute]
	IC25 >	99.2% Effluent	[Chronic]

Effluent Limitation for Biological Oxygen Demand (BOD) based upon Water Quality Standards or Regulations

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent BOD limitation as follows:

Season	Concentration	
Summer	25.0 mg/l as BOD5	16.7 lbs/day
Fall	25.0 mg/l as BOD5	16.7 lbs/day
Winter	25.0 mg/l as BOD5	16.7 lbs/day
Spring	25.0 mg/l as BOD5	16.7 lbs/day

Effluent Limitation for Dissolved Oxygen (DO) based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent D.O. limitation as follows:

Season	Concentration		
Summer	5.00		
Fall	5.00		
Winter	5.00		
Spring	5.00		

Effluent Limitation for Total Ammonia based upon Water Quality Standards

In-stream criteria of downstream segments for Total Ammonia will be met with an effluent limitation (expressed as Total Ammonia as N) as follows:

Sea	son				
	Concentration				
Summer	4 Day Avg Chronic	5.9	mg/l as N	3.9	lbs/day
	1 Hour Avg Acute	13.2	mg/l as N	8.8	lbs/day
Fall	4 Day Avg Chronic	5.9	mg/l as N	3.9	lbs/day
	1 Hour Avg Acute	13.2	mg/l as N	8.8	lbs/day
Winter	4 Day Avg Chronic	5.9	mg/l as N	3.9	lbs/day
	1 Hour Avg Acute	13.2	mg/l as N	8.8	lbs/day
Spring	4 Day Avg Chronic	5.9	mg/l as N	3.9	lbs/day
	1 Hour Avg Acute	13.2	mg/l as N	8.8	lbs/day

Acute limit calculated with an Acute Zone of Initial Dilution (ZID) to be equal to 100.%.

Effluent Limitation for Total Residual Chlorine based upon Water Quality Standards

In-stream criteria of downstream segments for Total Residual Chlorine will be met with an effluent limitation as follows:

Season		Concentr	ation	Load	d
Summer	4 Day Avg Chronic	0.011	mg/l	0.01	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.01	lbs/day
Fall	4 Day Avg Chronic	0.011	mg/l	0.01	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.01	lbs/day
Winter	4 Day Avg Chronic	0.011	mg/l	0.01	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.01	lbs/day
Spring	4 Day Avg Chronic	0.011	mg/l	0.01	lbs/day
	1 Hour Avg Acute	0.019	mg/l	0.01	lbs/day

Effluent Limitations for Total Dissolved Solids based upon Water Quality Standards

Sea	son	Concentra	ation	Loa	d
Summer	Maximum, Acute	1207.2	mg/l	0.40	tons/day
Fall	Maximum, Acute	1207.2	mg/l	0.40	tons/day
Winter	Maximum, Acute	1207.2	mg/l	0.40	tons/day
Spring	4 Day Avg Chronic	1207.2	mg/l	0.40	tons/day
Colorado	Salinity Form Limits	Determine	d by Permit	ting Section	

Effluent Limitations for Total Recoverable Metals based upon Water Quality Standards

In-stream criteria of downstream segments for Dissolved Metals will be met with an effluent limitation as follows (based upon a hardness of 300 mg/l):

		4 Day Average		1 Hour	Average	
	Conce	ntration	Load	Concentration		Load
Aluminum	N/A		N/A	⁼ 756.0	ug/l	0.5 lbs/day
Arsenic	191.53	ug/l	0.1 lbs/day	342.7	ug/l	0.2 lbs/day
Cadmium	0.62	ug/l	0.0 lbs/day	6.6	ug/l	0.0 lbs/day
Chromium III	213.62	ug/l	0.1 lbs/day	4,469.5	ug/l	3.0 lbs/day
Chromium VI	11.06	ug/l	0.0 lbs/day	16.1	ug/l	0.0 lbs/day
Copper	24.04	ug/l	0.0 lbs/day	39.7	ug/l	0.0 lbs/day
Iron	N/A		N/A	1,008.1	ug/l	0.7 lbs/day
Lead	12.98	ug/l	0.0 lbs/day	333.3	ug/l	0.2 lbs/day
Mercury	0.01	ug/l	0.0 lbs/day	2.4	ug/l	0.0 lbs/day
Nickel	133.19	ug/l	0.1 lbs/day	1,198.0	ug/l	0.8 lbs/day
Selenium	4.62	ug/l	0.0 lbs/day	20.1	ug/l	0.0 lbs/day
Silver	N/A	ug/l	N/A lbs/day	25.2	ug/l	0.0 lbs/day
Zinc	306.39	•	0.1 lbs/day	306.4	ug/l	0.2 lbs/day
Cyanide	5.24	ug/l	0.0 lbs/day	22.2	ug/l	0.0 lbs/day

Effluent Limitations for Heat/Temperature based upon Water Quality Standards

Summer	22.0 Deg. C.	71.6 Deg. F
Fall	14.0 Deg. C.	57.2 Deg. F
Winter	6.0 Deg. C.	42.8 Deg. F
Spring	14.0 Deg. C.	57.2 Deg. F

Effluent Limitations for Organics [Pesticides] Based upon Water Quality Standards

In-stream criteria of downstream segments for Organics [Pesticides] will be met with an effluent limit as follows:

	4 Day Average		1 Hour Average			
	Concentration	Load	Concentration		Load	
Aldrin			1.5E+00	ug/l	1.55E-03 lbs/day	
Chlordane	4.30E-03 ug/l	2.87E-03 lbs/day	1.2E+00	ug/l	1.24E-03 lbs/day	
DDT, DDE	1.00E-03 ug/l	6.67E-04 lbs/day	5.5E-01	ug/l	5.68E-04 lbs/day	
Dieldrin	1.90E-03 ug/l	1.27E-03 lbs/day	1.3E+00	ug/l	1.29E-03 lbs/day	
Endosulfan	5.60E-02 ug/l	3.74E-02 lbs/day	1.1E-01	ug/l	1.14E-04 lbs/day	
Endrin	2.30E-03 ug/l	1.53E-03 lbs/day	9.0E-02	ug/l	9.29E-05 lbs/day	
Guthion	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.03E-05 lbs/day	
Heptachlor	3.80E-03 ug/l	2.53E-03 lbs/day	2.6E-01	ug/l	2.68E-04 lbs/day	
Lindane	8.00E-02 ug/l	5.34E-02 lbs/day	1.0E+00	ug/l	1.03E-03 lbs/day	
Methoxychlor	0.00E+00 ug/l	0.00E+00 lbs/day	3.0E-02	ug/ľ	3.10E-05 lbs/day	
Mirex	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02	ug/l	1.03E-05 lbs/day	
Parathion	0.00E+00 ug/l	0.00E+00 lbs/day	4.0E-02	ug/l	4.13E-05 lbs/day	
PCB's	1.40E-02 ug/l	9.34E-03 lbs/day	2.0E+00	ug/l	2.06E-03 lbs/day	
Pentachlorophenol	1.30E+01 ug/l	8.67E+00 lbs/day	2.0E+01	ug/l	2.06E-02 lbs/day	
Toxephene	2.00E-04 ug/l	1.33E-04 lbs/day	7.3E-01	ug/l	7.53E-04 lbs/day	

Effluent Targets for Pollution Indicators Based upon Water Quality Standards

In-stream criteria of downstream segments for Pollution Indicators would be met by achieving the following effluent targets

1 Hour Average		
Concentration	Loading	
50.0 pCi/L		
5.0 mg/l	3.3 lbs/day	
4.0 mg/l	2.7 lbs/day	
0.05 mg/l	0.0 lbs/day	
90.0 mg/l	60.0 lbs/day	
	Concentration 50.0 pCi/L 5.0 mg/l 4.0 mg/l 0.05 mg/l	

Note: Pollution indicator targets are for information purposes only.

Effluent Limitations for Protection of Human Health [Toxics Rule] Based upon Water Quality Standards (Most stringent of 1C or 3A & 3B as appropriate.)

In-stream criteria of downstream segments for Protection of Human Health [Toxics] will be met with an effluent limit as follows:

	Maximum Concentration		
	Concentration	Load	
Toxic Organics			
Acenaphthene	ug/l	lbs/day	
Acrolein	ug/l	lbs/day	
Acrylonitrile	ug/l	lbs/day	
Benzene	ug/l	lbs/day	
Benzidine	ug/l	lbs/day	

Carbon tetrachloride	ug/l	lbs/day
Chlorobenzene	ug/Ì	lbs/day
1,2,4-Trichlorobenzene		
Hexachlorobenzene	ug/l	lbs/day
1,2-Dichloroethane	ug/l	lbs/day
1,1,1-Trichloroethane		•
Hexachloroethane	ug/l	lbs/day
1,1-Dichloroethane	ŭ	•
1,1,2-Trichloroethane	ug/l	lbs/day
1,1,2,2-Tetrachloroethane	ug/l	lbs/day
Chloroethane	3	,
Bis(2-chloroethyl) ether	ug/l	lbs/day
2-Chloroethyl vinyl ether	- 9	,
2-Chloronaphthalene	ug/l	lbs/day
2,4,6-Trichlorophenol	ug/l	lbs/day
p-Chloro-m-cresol	ug/i	iborday
Chloroform (HM)	ug/l	ibs/day
2-Chlorophenol	ug/l	lbs/day
•	_	lbs/day
1,2-Dichlorobenzene	ug/l	lbs/day
1,3-Dichlorobenzene	ug/l	-
1,4-Dichlorobenzene	ug/l	lbs/day
3,3'-Dichlorobenzidine	ug/l	lbs/day
1,1-Dichloroethylene	ug/l	lbs/day
1,2-trans-Dichloroethylene1		
2,4-Dichlorophenol	ug/l	lbs/day
1,2-Dichloropropane	ug/l	lbs/day
1,3-Dichloropropylene	ug/l	lbs/day
2,4-Dimethylphenol	ug/l	lbs/day
2,4-Dinitrotoluene	ug/l	lbs/day
2,6-Dinitrotoluene		
1,2-Diphenylhydrazine	ug/l	lbs/day
Ethylbenzene	ug/i	lbs/day
Fluoranthene	ug/i	lbs/day
4-Chlorophenyl phenyl ether		
4-Bromophenyl phenyl ether		
Bis(2-chloroisopropyl) ether	ug/l	lbs/day
Bis(2-chloroethoxy) methane		
Methylene chloride (HM)	ug/I	lbs/day
Methyl chloride (HM)	<u> </u>	·
Methyl bromide (HM)		
Bromoform (HM)	ug/l	lbs/day
Dichlorobromomethane(HM)	ug/l	lbs/day
Chlorodibromomethane (HM)	ug/l	lbs/day
Hexachlorocyclopentadiene	ug/i	lbs/day
Isophorone	ug/l	lbs/day
Naphthalene	~5··	,
Nitrobenzene	ug/l	lbs/day
2-Nitrophenol	29/1	isorday
4-Nitrophenol	us/l	lbe/day
2,4-Dinitrophenol	ug/l	lbs/day
4,6-Dinitro-o-cresol	ug/l	lbs/day

N-Nitrosodimethylamine	ua/l	lbs/day
•	ug/l	•
N-Nitrosodiphenylamine	ug/l	lbs/day
N-Nitrosodi-n-propylamine	ug/l	lbs/day
Pentachlorophenol	ug/l	lbs/day
Phenol	ug/l	lbs/day
Bis(2-ethylhexyl)phthalate	ug/l	lbs/day
Butyl benzyl phthalate	ug/l	lbs/day
Di-n-butyl phthalate	ug/l	lbs/day
Di-n-octyl phthlate	43	,
Diethyl phthalate	ug/l	lbs/day
Dimethyl phthlate	ug/l	lbs/day
Benzo(a)anthracene (PAH)	_	-
• • • • • • • • • • • • • • • • • • • •	ug/l	lbs/day
Benzo(a)pyrene (PAH)	ug/l	lbs/day
Benzo(b)fluoranthene (PAH)	ug/l	lbs/day
Benzo(k)fluoranthene (PAH)	ug/l	lbs/day
Chrysene (PAH)	ug/I	lbs/day
Acenaphthylene (PAH)		
Anthracene (PAH)		
Dibenzo(a,h)anthracene (PAH)	ug/l	lbs/day
Indeno(1,2,3-cd)pyrene (PAH)	ug/l	lbs/day
Pyrene (PAH)	ug/l	lbs/day
Tetrachloroethylene	ug/l	lbs/day
Toluene	ug/l	lbs/day
Trichloroethylene	_	
-	ug/l	lbs/day
Vinyl chloride	ug/l	lbs/day
Paradist to		
Pesticides		· · · · · · · · · · · · · · · · · · ·
Aldrin	ug/l	lbs/day
Dieldrin	ug/l	lbs/day
Chlordane	ug/l	lbs/day
4,4'-DDT	ug/l	lbs/day
4,4'-DDE	ug/l	lbs/day
4,4'-DDD	ug/l	lbs/day
alpha-Endosulfan	ug/l	lbs/day
beta-Endosulfan	ug/l	lbs/day
Endosulfan sulfate	ug/l	lbs/day
Endrin	ug/I	lbs/day
Endrin aldehyde	-	lbs/day
Heptachlor	ug/l	•
•	ug/l	lbs/day
Heptachlor epoxide		
PCB's		
		N= - 1-1 =
PCB 1242 (Arochlor 1242)	ug/l	lbs/day
PCB-1254 (Arochlor 1254)	ug/l	lbs/day
PCB-1221 (Arochlor 1221)	ug/l	lbs/day
PCB-1232 (Arochlor 1232)	ug/l	lbs/day
PCB-1248 (Arochlor 1248)	ug/l	lbs/day
PCB-1260 (Arochlor 1260)	ug/l	lbs/day
PCB-1016 (Arochlor 1016)	ug/l	lbs/day
· •	-	•

Pesticide

Toxaphene	ug/t	lbs/day
Metals		
Antimony	ug/l	lbs/day
Arsenic	ug/l	lbs/day
Asbestos	ug/l	lbs/day
Beryllium		
Cadmium		
Chromium (III)		
Chromium (VI)		
Copper	ug/l	lbs/day
Cyanide	ug/l	lbs/day
Lead		
Mercury	ug/l	lbs/day
Nickel	ug/l	lbs/day
Selenium		
Silver		
Thallium	ug/l	lbs/day
Zinc		3
Dioxin		40.514.41.43
Dioxin (2,3,7,8-TCDD)	#N/A ug/I	#N/A lbs/day

Metals Effluent Limitations for Protection of All Beneficial Uses Based upon Water Quality Standards and Toxics Rule

	Class 4 Acute Agricultur al ug/l	Class 3 Acute Aquatic Wildlife ug/l	Acute Toxics Drinking Water Source ug/l	Acute Toxics Wildlife ug/l	1C Acute Health Criteria ug/l	Acute Most Stringent ug/l	Class 3 Chronic Aquatic Wildlife ug/l
Aluminum						0.0	N/A
Antimony				4334.7		4334.7	
Arsenic	100.8				0.0	100.8	
Barium						0.0	
Beryllium	0.0					0.0	
Cadmium	10.1				0.0	10.1	
Chromium (III)					0.0	0.0	
Chromium (VI)	100.8				0.0	100.80	
Copper	201.6					201.6	
Cyanide		22.2	221777.6			221777.6	5.2
Iron						0.0	
Lead	100.8				0.0	100.8	
Mercury				0.15	0.0	0.15	
Nickel				4637.2		4637.2	
Selenium	50.4				0.0	50.4	
Silver					0.0	0.0	

Thallium		6.4	6.4
Zinc			0.0
Boron	756.1		756.1

Summary Effluent Limitations for Metals [Wasteload Allocation, TMDL]

[If Acute is more stringent than Chronic, then the Chronic takes on the Acute value.]

	WLA Acute ug/l	WLA Chronic ug/l	;
Aluminum	0.0	N/A	
Antimony	4334.74		
Arsenic	100.8		Acute Controls
Asbestos	0.00E+00		
Barium			
Beryllium	#.2		
Cadmium	10.1		Acute Controls
Chromium (III)	0.0		Acute Controls
Chromium (VI)	100.8		Acute Controls
Copper	201.6		Acute Controls
Cyanide	221777.6	5.2	
Iron	0.0		
Lead	100.8		Acute Controls
Mercury	0.151		Acute Controls
Nickel	4637.2		Acute Controls
Selenium	50.4		 Acute Controls
Silver	0.0	N/A	
Thallium	6.4		
Zinc	0.0		Acute Controls
Boron	756.06		

Other Effluent Limitations are based upon R317-1.

E. coli

126.0 organisms per 100 ml

X. Antidegradation Considerations

The Utah Antidegradation Policy allows for degradation of existing quality where it is determined that such lowering of water quality is necessary to accommodate important economic or social development in the area in which the waters are protected [R317-2-3]. It has been determined that certain chemical parameters introduced by this discharge will cause an increase of the concentration of said parameters in the receiving waters. Under no conditions will the increase in concentration be allowed to interfere with existing instream water uses.

The antidegradation rules and procedures allow for modification of effluent limits less than those based strictly upon mass balance equations utilizing 100% of the assimilative capacity of the receiving water. Additional factors include considerations for "Blue-ribbon" fisheries, special recreational areas, threatened and endangered species, and drinking water sources.

An Antidegradation Level I Review was conducted on this discharge and its effect on the

receiving water. Based upon that review, it has been determined that an Antidegradation Level II Review is not required. Basic Renewal, no increase in flow or concentration

XI. Colorado River Salinity Forum Considerations

Discharges in the Colorado River Basin are required to have their discharge at a TDS loading of less than 1.00 tons/day unless certain exemptions apply. Refer to the Forum's Guidelines for additional information allowing for an exceedence of this value.

XII. Summary Comments

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important downstream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.

XIII. Notice of UPDES Requirement

This Addendum to the Statement of Basis does not authorize any entity or party to discharge to the waters of the State of Utah. That authority is granted through a UPDES permit issued by the Utah Division of Water Quality. The numbers presented here may be changed as a function of other factors. Dischargers are strongly urged to contact the Permits Section for further information. Permit writers may utilize other information to adjust these limits and/or to determine other limits based upon best available technology and other considerations provided that the values in this wasteload analysis [TMDL] are not compromised.

David Wham Utah Division of Water Quality 801-538-6052

File Name: NephiRubber_WLA_11-30-12.xls

APPENDIX - Coefficients and Other Model Information

CBOD	CBOD	CBOD	REAER.	REAER.	REAER.	NBOD	NBOD
Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.	Coeff.
(Kd)20	FORCED	(Ka)T	(Ka)20	FORCED	(Ka)T	(Kn)20	(Kn)T
1/day	(Kd)/day	1/day	(Ka)/day	1/day	1/day	1/day	1/day
2.000	0.000	0.806	4340.249	0.000	2713.785	0.600	0.131
Open Coeff. (K4)20 1/day 0.000	Open Coeff. (K4)T 1/day 0.000	NH3 LOSS (K5)20 1/day 4.000	NH3 (K5)T 1/day 1.611	NO2+NO3 LOSS (K6)20 1/day 0.000	NO2+NO3 (K6)T 1/day 0.000	TRC Decay K(Cl)20 1/day 32.000	TRC K(Cl)(T) 1/day 10.095

BENTHIC BENTHIC DEMAND

(SOD)20 gm/m2/day gn 1.000	(SOD)T n/m2/day 0.287						
K1	K2	K3	K4	K5	K6	K(CI)	S
CBOD	Reaer.	NH3	Open	NH3 Loss	NO2+3	TRC	Benthic
{theta}	{theta}	{theta}	{theta}	{theta}	{theta}	{theta}	{theta}
1.0	1.0	1.1	1.0	1.0	1.0	1.1	1.1