



SIGIE	LOCAT	ON: Highy	vav 276 Marke	r 30, Lake Powell		533 435-78 hunty	8-2142	
ISSUE D		10/29/201			ON DATE:	10/29/	/2019	
ISSUED			\mathcal{L}	Walter	L. Baker, P.E.,	Director, I	Division of Water Quali	ty
wastewate	r disposal sy	stem in conform		revoked, the permitee requirements, limitat	e is authorized t	o operate a		
				SCHEDULE A				
waste D	isposal Lir							
1.	constructed following c	l in accordance conditions:	with plans and sp	ecifications approved			al system that has been Quality and with the	
	a. Syst		onventional Gravi onventional with F essure Distributio ternative (describ	Pump-to-Gravity;				
	b. Max	imum Daily De		>5,000				
				RV's;#2-Store & sho	op#3- 6RV; #4-	2 RVs; #5-	- 4 Rv's; #6- 3 RV's;	
DWQ-2014-01304	☐ Red ☐ Gra ☐ Puu ☐ Co ☐ Tre ✔ Ded ☐ Bed	circulatingTank caseTrap npTankWithFloa ntrol Panel nches cpTrench	ts		Septic Tank Distribution H Distribution H Drip Irrigatio Enhanced Trt Ratcheting Vi Mound	Box ribution n : Unit	parate Systems): #1- 2,500g # 1,500; #4-1,500; #5- 1,500	; #6- 1 560ga
	d Drai	nfield media	Gravel:	Gravelless Chambers	-			
	e. Effl Discharge	uent parameters of untreated or	will meet R317-4 partially treated s	4 for domestic wastew sewage or septic tank	vater or addition effluent directly	nal treatme y or indirec d. This pe	ctly onto the ground sur ermit does not relieve th	face or
2		from responsibi	lity for compliant	ce with any other appl		state, or lo	cal law(s), rule(s) or	
2 3	permittee standard(s No coolin	from responsibi). g water, air cone	ditioner water, gro	e with any other applound water, oil, hazar	licable federal, and dous materials,	roof drain	cal law(s), rule(s) or age, storm water runoff ental to the performance	
	permittee standard(s No coolin other aq u the	from responsibi). g water, air con- eous or non-aqu ies shall be cond	ditioner water, gro leous substance w	e with any other applound water, oil, hazar	licable federal, dous materials, ent of the Divisi	roof drain: on, detrime	age, storm water runoff ental to the performance	

2. All servicing and inspections must be conducted by a certified maintenance person per R317-11. Level 2 is required for conventional systems and level 3 for all other LUWDS.

Name of person performing maintenance on thsi system:/

- Level 2
- Level 3 Note: if this person is replaced with another maintenance person, the owner must notify the Division within 30 day of change.

Page 2 **OFFSHORE MARINA OPERATING PERMIT** 810

If Sample results exceed Operating Parameters (other than Flow of wastewater) in table titled "Minimum 3. Monitoring and Reporting Requirements", report to the Division within 5 days and follow rules in R317-5-1.4 (F).

Inspection Components

ł

TYPE OF SYSTEM	Measure sludge/ scum levels, pump when necessary: * Septic Tank * Pump Tank * Grease Trap	Inspect and clean when necessary * Pump/Floats * Control Panel * Pump Filter	Flush/clean pressure laterals; inspect for ponding or surfacing in dispersal area; reset squirt height for equal pressure	Manufacturers Recommendations: * Recirc Tank * Pre-Treatment Unit * Misc
Conventional Gravity or Pump-to-Gravity				
Presure System (Drip)				
Mound, At-Grade				
Packed Bed				

* Or more per manufacturer requirements

Minimum Frequency of Periodic Inspections

TYPE OF SYSTEM	Every 12 months	Every 6 months
Conventional Gravity or Pump-to-Gravity 5,000 - 15,000 gal/day 15,000 + gal/day		
At-Grade Alternative System (first 5 years only)	[]	
Mound (drip. pressure)		
Packed Bed		
Treatment System (to lower waste strength levels)		

Monitoring and Reporting Requirements

Item or Parameter	Minimum Frequency	Type of Sample	Operating Parameters
Flow of wastewater (gpd)	Monthly	Measurement based on meter readings	Approved design flow (gpd)
COD, TSS			
Total Inorganic Nitrogen (TIN)			

Reporting

Monitoring, maintenance practices, solids handling and results shall be reported on Division approved forms and must be submitted by August 1, following the "reporting year" period of July 1 to June 30.

Mail or email Reports to (permitting agency): Division of Water Quality, c/o LUWDS, PO Box 144870, Salt Lake City, UT 84114-4870 Fax: 801-536-4301

Office: 801-536-4329

email: LUWDS@utah.gov

SCHEDULE C

Special and General Conditions

- 1. All septage/sludge shall be managed by a licensed sewage scavenger (pumper) as defined in R317-550.
- 2. Any observations of excessive kitchen wastes, surfacing sewage, etc., must be report to the Division within 5 working days
- 3. The permittee must maintain all treatment and control facilities in good working order and in conformance with permit requirements.