

# LARGE UNDERGROUND WASTEWATER OPERATING PERMIT Division of Water Quality

- Shares							
NAME C	<b>DF SYSTEM: RICH COUNTY SCHOOL DISTRICT - RICH MIDDLE SCHOOL AND NORTH</b>						
CONTACT PERSON/MAILING ADDRESS/PHONE NO: Rick Limb 25 South 100 West Randolph UT 84064 4357573248							
SYSTEM	I LOCATION: 50E 100S, Laketown, Rich County						
ISSUE D	DATE: 01/18/2015 //// / EXPIRATION DATE: 01/18/2020						
ISSUED	BY: Walter L. Baker, P.E., Director, Division of Water Quality						
wastewate	time as this permit expires or is modified or revoked, the permitee is authorized to operate a large underground r disposal system in conformance with all the requirements, limitations, and conditions set forth in <i>Utah Administrative</i> 17-5, with the attached schedules as follows:						
Waste Di	isposal Limitations:						
1.	The permittee is authorized to operate and maintain a large underground wastewater disposal system that has been constructed in accordance with plans and specifications approved by the Division of Water Quality and with the following conditions:						
	a. System type 🗹 Conventional Gravity;						
	<ul> <li>Conventional with Pump-to-Gravity;</li> <li>Pressure Distribution;</li> </ul>						
	Alternative (describe)						
	b. Maximum Daily Design Flow of <u>5,875 gpd</u>						
	235 students						
	c. Components of wastewater disposal system (check)						
	C RecirculatingTank Septic Tanks; 2-1,000 gal						
	✓ GreaseTrap						
	PumpTankWithFloats   Pressure Distribution						
	Control Panel Drip Irrigation						
	✓ Trenches Enhanced Trt Unit						
	DeepTrench Ratcheting Valve Box						
	Bed     Mound       Other (describe) No     Other (describe) No						
	d. Drainfield media 🗹 Gravel; 🗌 Gravelless Chambers						
	e. Effluent parameters will meet R317-4 for domestic wastewater or additional treatment may be required.						
2	Discharge of untreated or partially treated sewage or septic tank effluent directly or indirectly onto the ground surface or the surface waters of the state constitutes a public health hazard and is prohibited. This permit does not relieve the permittee from responsibility for compliance with any other applicable federal, state, or local law(s), rule(s) or standard(s).						
3							
4	No activities shall be conducted that could cause an adverse impact on existing or potential beneficial use of groundwater.						
	SCHEDULE B Required Servicing and Inspections						
1.	✓ Annually □ Semi-Annually (every 6 months) □ Other (specify)						
2.	All servicing and inspections must be conducted by a certified maintenance person per R317-11. Level 2 is required for conventional systems and level 3 for all other LUWDS.						
	Name of person performing maintenance on thsi system:/						
	Level 2 Level 3 Note: if this person is replaced with another maintenance person, the owner must notify the Division						
	- LEVEL 2 - LEVEL 3 TORE, If this person is replaced with another maintenance person, the owner must notify the Division						

within 30 day of change.

## Page 2 RICH COUNTY SCHOOL DISTRICT - RICH MIDDLE SCHOOL AND NORTH RICH

If Sample results exceed Operating Parameters (other than Flow of wastewater) in table titled "Minimum 3. Monitoring and Reporting Requirements", report to the Division within 5 days and follow rules in R317-5-1.4 (F).

#### **Inspection Components**

TYPE OF SYSTEM	Measure sludge/ scum levels, pump when necessary: * Septic Tank * Pump Tank * Grease Trap	when necessary	Flush/clean pressure laterals; inspect for ponding or surfacing in dispersal area; reset squirt height for equal pressure	Manufacturers Recommendations: * Recirc Tank * Pre-Treatment Unit * Misc
Conventional Gravity or Pump-to-Gravity	✓	✓	✓	
Presure System (Drip)				
Mound, At-Grade				
Packed Bed				

\* Or more per manufacturer requirements

#### **Minimum Frequency of Periodic Inspections**

TYPE OF SYSTEM	Every 12 months	Every 6 months
Conventional Gravity or Pump-to-Gravity 5,000 - 15,000 gal/day 15,000 + gal/day		
At-Grade Alternative System (first 5 years only)		
Mound (drip, pressure)		
Packed Bed		
Treatment System (to lower waste strength levels)		

#### **Monitoring and Reporting Requirements**

Item or Parameter	Minimum Frequency	Type of Sample	Operating Parameters
Flow of wastewater (gpd)	2	Measurement based on meter readings	Approved design flow (gpd)
COD, TSS			
Total Inorganic Nitrogen (TIN)			

#### Reporting

Monitoring, maintenance practices, solids handling and results shall be reported on Division approved forms and must be submitted by August 1, following the "reporting year" period of July 1 to June 30.

Mail or email Reports to (permitting agency): Division of Water Quality, c/o LUWDS, PO Box 144870, Salt Lake City, UT 84114-4870 Office: 801-536-4329 Fax: 801-536-4301

email: LUWDS@utah.gov

### SCHEDULE C

#### **Special and General Conditions**

- 1. All septage/sludge shall be managed by a licensed sewage scavenger (pumper) as defined in R317-550.
- 2. Any observations of excessive kitchen wastes, surfacing sewage, etc., must be report to the Division within 5 working days
- 3. The permittee must maintain all treatment and control facilities in good working order and in conformance with permit requirements.