

# LARGE UNDERGROUND WASTEWATER OPERATING PERMIT Division of Water Ouality

NAME OF SYSTEM: MOAB VALLEY RV RESORT				
CONTACT PERSON/MAILING ADDRESS/PHONE NO:	Bill Gannom 1773 North Highway 191 Moab UT 84532 435-259-4469			
SYSTEM LOCATION: 1773 North Highway 191, Moab,	Grand County			
ISSUE DATE: 01/06/2015 // / / EXPIRATION DATE: 01/06/2020				
ISSUED BY: W	Valter L. Baker, P.E., Director, Division of Water Quality			
Until such time as this permit expires or is modified or revoked, the per wastewater disposal system in conformance with all the requirements, 1: <i>Code R317-5</i> , with the attached schedules as follows:				
SCHEDULI	EA			

# Waste Disposal Limitations:

1. The permittee is authorized to operate and maintain a large underground wastewater disposal system that has been constructed in accordance with plans and specifications approved by the Division of Water Quality and with the following conditions:

a.	Conventional Gravity;	
	Conventional with Pump-to-Gravi	ity;
	Pressure Distribution;	
	Alternative (describe)	

 b. Maximum Daily Design Flow of <a href="https://www.systems">>5,000 gpd</a> Two systems; System #1-bath house and 62 RV sites. System #2- 2 offices, residence and bath house

RecirculatingTank		Septic Tanks;	
GreaseTrap		Distribution Box	
] PumpTankWithFloa	ats	Pressure Distribution	
Control Panel		Drip Irrigation	
<ul> <li>Trenches</li> </ul>	system #1	Enhanced Trt Unit	
DeepTrench		Ratcheting Valve Box	
✓ Bed	System #2	Mound	

- d. Drainfield media Gravel; Gravelless Chambers
- e. Effluent parameters will meet R317-4 for domestic wastewater or additional treatment may be required.
- 2.. Discharge of untreated or partially treated sewage or septic tank effluent directly or indirectly onto the ground surface or the surface waters of the state constitutes a public health hazard and is prohibited. This permit does not relieve the permittee from responsibility for compliance with any other applicable federal, state, or local law(s), rule(s) or standard(s).
- 3.. No cooling water, air conditioner water, ground water, oil, hazardous materials, roof drainage, storm water runoff, or other aq ueous or non-aqueous substance which is, in the judgment of the Division, detrimental to the performance of the
- 4.. No activities shall be conducted that could cause an adverse impact on existing or potential beneficial use of groundwater.

## SCHEDULE B Required Servicing and Inspections

 1.
 ✓ Annually
 □ Semi-Annually (every 6 months)

2. All servicing and inspections must be conducted by a certified maintenance person per R317-11. Level 2 is required for conventional systems and level 3 for all other LUWDS.

Name of person performing maintenance on thsi system:/

✓ Level 2

Level 3 Note: if this person is replaced with another maintenance person, the owner must notify the Division within 30 day of change.

# Page 2 MOAB VALLEY RV RESORT OPERATING PERMIT

If Sample results exceed Operating Parameters (other than Flow of wastewater) in table titled "Minimum 3. Monitoring and Reporting Requirements", report to the Division within 5 days and follow rules in R317-5-1.4 (F).

#### **Inspection Components**

Measure sludge/ scum levels, pump when necessary: * Septic Tank * Pump Tank * Grease Trap		Inspect and clean when necessary * Pump/Floats * Control Panel * Pump Filter	Flush/clean pressure laterals; inspect for ponding or surfacing in dispersal area; reset squirt height for equal pressure	Manufacturers Recommendations: * Recirc Tank * Pre-Treatment Unit * Misc
Conventional Gravity or Pump-to-Gravity	✓	✓	✓	
Presure System (Drip)				
Mound, At-Grade				
Packed Bed				

\* Or more per manufacturer requirements

#### **Minimum Frequency of Periodic Inspections**

TYPE OF SYSTEM	Every 12 months	Every 6 months
Conventional Gravity or Pump-to-Gravity 5,000 - 15,000 gal/day 15,000 + gal/day		
At-Grade Alternative System (first 5 years only)		
Mound (drip, pressure)		
Packed Bed		
Treatment System (to lower waste strength levels)		

## **Monitoring and Reporting Requirements**

Item or Parameter	Minimum Frequency	Type of Sample	Operating Parameters
Flow of wastewater (gpd)	2	Measurement based on meter readings	Approved design flow (gpd)
COD, TSS			
Total Inorganic Nitrogen (TIN)			

#### Reporting

Monitoring, maintenance practices, solids handling and results shall be reported on Division approved forms and must be submitted by August 1, following the "reporting year" period of July 1 to June 30.

Mail or email Reports to (permitting agency): Division of Water Quality, c/o LUWDS, PO Box 144870, Salt Lake City, UT 84114-4870 Office: 801-536-4329 Fax: 801-536-4301

email: LUWDS@utah.gov

## SCHEDULE C

#### **Special and General Conditions**

- 1. All septage/sludge shall be managed by a licensed sewage scavenger (pumper) as defined in R317-550.
- 2. Any observations of excessive kitchen wastes, surfacing sewage, etc., must be report to the Division within 5 working days
- 3. The permittee must maintain all treatment and control facilities in good working order and in conformance with permit requirements.