

ATTACHMENT 3

SECURITY PLAN

Contents

1.0 Introduction 3-1

2.0 24-Hour Surveillance System 3-1

3.0 Barrier 3-1

4.0 Means to Control Entry 3-1

5.0 Warning Signs..... 3-1

1.0 Introduction

- 1.1** The Hazardous Waste Storage Facility (HWSF) shall be designed, constructed, maintained, and operated to minimize the possibility of unauthorized entry. The security procedures described below are currently in place to prevent unauthorized entry.

2.0 24-Hour Surveillance System [UAC R315-264-14(b)(2)]

- 2.1** The HWSF is located within the fenced and secured area of Hill AFB with access controlled at guarded gates on a 24-hour basis. In addition, the HWSF is fully enclosed by a fence. This fence is gated with access controls that are only accessible to facility staff.

3.0 Barrier [UAC R315-264-14(b)(2)(i)]

- 3.1** The HWSF shall be completely enclosed with a 6-foot-high, chain link, barbed wire fence with a 24-foot sliding gate on the west side of the HWSF for daily use, and a 14-foot double swing gate at the south of the HWSF to allow emergency and fire department access.

4.0 Means to Control Entry [UAC R315-264-14(b)(2)(ii)]

- 4.1** Unauthorized entry is minimized through the following procedures:
- 4.1.2** The fence surrounding the HWSF has a primary 24-foot, sliding, lockable gate through which normal entrance is gained and a secondary 14-foot access gate.
- 4.1.3** The gates shall be locked except when access is needed to transport waste into or out of the HWSF. Prior to entering, all contractors are required to check in at the HWSF Administration Building, which is shown in Figure 1-2 in Attachment 1.
- 4.1.4** The doors of the HWSF buildings and gates in the fence surrounding the HWSF are locked at all times when the HWSF staff is not present.

5.0 Warning Signs [UAC R315-264-14(c)]

- 5.1** Warning signs which read, “Danger - Unauthorized Personnel Keep Out” are posted at the entrances to the HWSF and on the perimeter fence. These signs shall be visible from 25 feet and shall be spaced no more than 100 feet apart. The signs shall be printed in English. In addition, placards shall be posted within the HWSF that describe the types of hazards presented by the waste stored in the area.