



State of Utah

GARY R. HERBERT  
*Governor*

SPENCER J. COX  
*Lieutenant Governor*

Department of  
Environmental Quality

Alan Matheson  
*Executive Director*

DIVISION OF WASTE MANAGEMENT  
AND RADIATION CONTROL  
Scott T. Anderson  
*Director*

November 30, 2015

Jerald Pezely  
Renegade Oil Inc.  
1141 South 3200 West  
Salt Lake City, UT 84104

RE: Used Oil Transporter Permit Approval (UOP-0158)  
UTR000011445

Dear Mr. Pezely:

The Division of Waste Management and Radiation Control has completed its review of Renegade Oil's application to operate as a used oil transporter in Utah submitted on September 17, 2015.

A draft permit was prepared and subjected to a fifteen-day public comment period which began on October 13, 2015 and ended on October 27, 2015. No public comments were received.

Enclosed is a hard copy of the Transporter Permit (UOP-0158), Renegade's Used Oil Handler Certificate (M-46) for 2015 and a compact disc with an electronic version of the permit. Please refer to Permit UOP-0158 on all future correspondence sent to the Division concerning the permit.

If you have any questions, please call Michelle Weis at (801) 536-0256.

Sincerely,

Scott T. Anderson, Director  
Division of Waste Management and Radiation Control

STA/MAW/kl

Enclosures: Used Oil Transporter Permit # UOP-0158 (DSHW-2015-0010271)  
Used Oil Handler Certificate # M-46 (DSHW-2015-011534)

c: Gary Edwards, MS, Health Officer, Salt Lake County Health Dept.  
Royal DeLegge, MPA, EHS, Environmental Health Director, Salt Lake County Health Dept.

DSHW-2015-011528

195 North 1950 West • Salt Lake City, UT  
Mailing Address: P.O. Box 144880 • Salt Lake City, UT 84114-4880  
Telephone (801) 536-0200 • Fax (801) 536-0222 • T.D.D. (801) 903-3978  
[www.deq.utah.gov](http://www.deq.utah.gov)  
Printed on 100% recycled paper



WASTE MANAGEMENT  
& RADIATION CONTROL

## Division of Waste Management and Radiation Control

### USED OIL TRANSPORTER PERMIT



**Permittee Name:** Renegade Oil, Inc.

**Permittee Mailing Address:** 1141 South 3200 West  
Salt Lake City, Utah 84104

**Permittee Phone Number:** (801) 973-7912

**Permittee Contact:** Jerald Pezely – Owner  
(801) 973-7912 (office)  
Email: renegadeoil@hotmail.com


**Facility Address:** 1141 South 3200 West  
Salt Lake City, Utah 84104

**Facility Contact:** Gary Clark – Facility Engineer  
(801) 725-0087 (cell)  
Email: gary@renegadeoil.net

**Type of Permit:** Used Oil Transporter Permit

**Permit #:** UOP-0158

**EPA ID #:** UTR000011445

Signature: 

Scott T. Anderson, Director  
Division of Waste Management and Radiation Control

Effective Date: 30 November 2015

**I.A. Effect of Permit**

- I.A.1. Renegade Oil, Inc. (hereafter referred to as "Permittee") is hereby authorized to operate as a used oil transporter in accordance with all applicable requirements of R315-15 of the Utah Administrative Code and of the Used Oil Management Act (the Act) 19-6-701 et. seq., Utah Code Annotated and this Permit.
- I.A.2. This Permit shall be effective for a term not to exceed ten years in accordance with the requirements of R315-15-15 of the Utah Administrative Code. This Permit shall be reviewed by the Director five years after the Permit's effective date of issuance or when the Director determines that the Permit requires review.
- I.A.3. Attachments incorporated by reference are enforceable conditions of this Permit, as are documents incorporated by reference into the attachments. Language in Conditions I and II supersedes any conflicting language in the attachments or documents incorporated into the attachments.

**I.B. Permit Revocation**

- I.B.1. Violation of any permit condition or failure to comply with any provision of the applicable statutes and rules shall be grounds for enforcement actions, including revocation of this Permit. The Director shall notify the Permittee in writing of his intent to revoke this Permit.

**I.C. Permit Modification**

- I.C.1. The Permittee may request modifications to any item or activity covered by this Permit by submitting a written permit modification request to the Director. If the Director determines the modification request is substantive, a public hearing, a 15-day public comment period or both may be required before the modification request may be determined. Implementing a substantive modification prior to the Director's written approval constitutes a violation of the Permit and may be grounds for enforcement action or permit revocation.
- I.C.2. The Permittee shall notify the Director in writing of any non-substantive changes, such as changes to the contact person, within 20 days of the change.
- I.C.3. The Director may modify this Permit as necessary to protect human health and the environment, because of statutory or regulatory changes or because of operational changes affecting this Permit.

**I.D. Spill Prevention**

- I.D.1. The Permittee shall maintain and operate all used oil transportation vehicles and associated equipment to minimize the possibility of fire, explosion or sudden or non-sudden release of used oil to the air, ground, soil, surface and groundwater and sewer systems.

**I.E. Record Retention**

- I.E.1. The Permittee shall maintain all applicable used oil records required by R315-15 of the Utah Administrative Code and this Permit at the Permittee's facility located at 1141 South 3200 West in Salt Lake City, Utah.
- I.E.2. All records shall be readily accessible for inspection by representatives of the Director. Records may be in a hard copy or electronic format. Records shall be maintained for a minimum of three years.

**I.F. Tracking**

- I.F.1. The Permittee shall keep written transportation records for both the collection and delivery of used oil. Collection and delivery records may be a log, invoice, manifest, bill of lading or other shipping document.
- I.F.2. For collections, the records shall include the Permittee's name, address, EPA identification number, the facility's vehicle number, driver name, date of collection, the volume of used oil collected and the type of collection (i.e., bulk oil in tankers or containerized, specifying container types and numbers). Additionally, the used oil records shall include the generator's, transporter's, transfer facility's, burner's, or processor's name and signature (dated upon receipt), address and EPA identification number.
- I.F.3. The halogen content from screening tests or analytical laboratory testing shall be documented on the used oil record/bill of lading at each used oil collection location prior to loading for transportation
- I.F.4. The Permittee shall record the PCB concentration based on analytical results of used transformer oil prior to collection/transport in accordance with Condition II.D.6.
- I.F.5. For deliveries, the delivery records shall include the Permittee's name, address, EPA identification number, vehicle identification number, driver name, date of delivery, the volume of used oil delivered and the type of delivery (i.e., bulk oil in tankers or containerized, specifying container types and numbers). Additionally, the used oil records shall include the receiving transfer facility's, burner's, processor's or other transporter's name and signature (dated upon receipt), address and EPA identification number.
- I.F.6. The Permittee shall create a new delivery record for internal transfers between the Permittee's transportation vehicles.

**I.G. Sampling and Analyses**

- I.G.1. The Permittee shall follow all sampling and analytical procedures in Condition II.D., Used Oil Sampling and Analytical Procedures, when conducting used oil sampling and analytical testing to meet the requirements of R315-15 of the Utah Administrative Code and this Permit.

**I.H. Prohibited Waste**

- I.H.1. Used oil that has been mixed with hazardous waste as defined by R315-1 and R315-2 of the Utah Administrative Code or PCBs as defined by R315-301-2(53) of the Utah Administrative Code shall no longer be managed as used oil and shall be subject to applicable hazardous waste and PCB-contaminated waste rules.
- I.H.2. Used oil shall not be stored in tanks, containers or storage units that previously stored hazardous waste unless these tanks, containers and storage units have been cleaned in accordance with R315-2-7 of the Utah Administrative Code.
- I.H.3. The Permittee shall not place, manage, discard or otherwise dispose of used oil in any manner other than specified in R315-15-1.3 of the Utah Administrative Code.

**I.I. Waste Disposal**

- I.I.1. The Permittee shall document and maintain records showing proper characterization, handling and disposal for used oil related wastes, including oily wastewater.
- I.I.2. The Permittee shall properly characterize used oil related wastes to determine if the wastes are hazardous or non-hazardous in accordance with R315-15-8 of the Utah Administrative Code. All wastes generated during used oil operations shall be handled in accordance with this Permit and R315-15 of the Utah Administrative Code. The wastes shall be taken to an appropriate facility permitted to handle the type of waste generated.

**I.J. Used Oil Storage**

- I.J.1. The Permittee shall not store used oil longer than 24 hours without first obtaining a transfer facility or processor permit for that storage location. This includes storing used oil in vehicles at loading and unloading docks and parking areas.
- I.J.2. The Permittee shall notify the Director if the 24-hour storage is exceeded due to mechanical failure of the Permittee's transportation vehicle prior to exceeding the 24-hour storage requirement.

**I.K. Liability and Financial Requirements**

- I.K.1. The Permittee shall procure and maintain general liability and sudden used oil third-party environmental pollution liability coverage for the Permittee's operations as required by R315-15-10 of the Utah Administrative Code.
- I.K.2. The Permittee shall provide documentation of financial responsibility, environmental pollution legal liability and general liability coverage annually to the Director for review and approval by March 1 of each reporting year or upon request by the Director.
- I.K.3. The Permittee shall notify the Director immediately of any changes to the extent and type of liability coverage in accordance with R315-15-10 of the Utah Administrative Code.

**I.L. Used Oil Handler Certificate**

- I.L.1. In accordance with R315-15-4.1 of the Utah Administrative Code, the Permittee shall not operate as a used oil transporter without obtaining annually a Used Oil Handler Certificate from the Director. The Permittee shall pay a used oil handler fee, pursuant to Utah Code 63J-1-504, by December 31 of each calendar year to receive certification for the upcoming calendar year.

**I.M. Inspection and Inspection Access**

- I.M.1. Any duly authorized employee of the Director may, at any reasonable time and upon presentation of credentials, have access to and the right to copy any records relating to used oil and to inspect, audit or sample. The employee may also make record of the inspection by photographic, electronic, audio, video or any other reasonable means to determine compliance.
- I.M.2. In addition, the authorized employees may collect soil, groundwater or surface water samples to evaluate the facility's compliance.
- I.M.3. Failure to allow reasonable access to the property by an authorized employee may constitute "denial of access" and may be grounds for enforcement action or permit revocation.

**I.N. Annual Report**

- I.N.1. As required by R315-15-13.4 of the Utah Administrative Code, the Permittee shall prepare and submit an Annual Report of its used oil activities for the calendar year to the Director by March 1 of the year following the reported activity (Form UO 004 (Annual Report for Used Oil Transporter Facilities)). The Annual Report shall also include all financial assurance documentation required by Form UO 004.

**I.O. Other Laws**

- I.O.1. Nothing in this Permit shall be construed to relieve the Permittee of his obligation to comply with any Federal, State or local law.

**I.P. Enforceability**

- I.P.1. Violations documented through the enforcement process pursuant to Utah Code Annotated 19-6-112 may result in penalties in accordance with R315-102 of the Utah Administrative Code.

**I.Q. Effective Date**

- I.Q.1. The permit is effective on the date of signature by the Director.

## **II.A. Transportation Operations**

- II.A.1. The Permittee is authorized to transport used oil and deliver the used oil to another permitted transporter, transfer facility, processor and re-refiners or used oil burners in accordance with R315-15-4.4 of the Utah Administrative Code.
- II.A.2. Used oil recovered from oily water shall be managed as used oil in accordance with R315-15 of the Utah Administrative Code and this Permit.
- II.A.3. The Permittee shall comply with TSCA regulations when transporting used oil with PCB concentrations greater than or equal to 50 ppm (mg/kg).

## **II.B. Transport Vehicle Requirements**

- II.B.1. The Permittee shall only transport used oil in the types of vehicles listed in Table II.B.

**Table II.B: Vehicle Description**

<b>Type of Vehicle</b>	<b>Used Oil Capacity (gallons)</b>
Tanker Trucks	9,000
Pumper Trucks	3,100

- II.B.2. All Permittee's used oil transport vehicles shall have the words "USED OIL" on both sides of the transport vehicle in a contrasting color that is distinguishable from the background color and at least three inches tall. These designations shall be in place at all times the transport vehicle is transporting or storing used oil.
- II.B.3. All Permittee's vehicles which transport used oil shall have a copy of the Permittee's Used Oil Emergency Spill Plan maintained in the vehicle at all times.
- II.B.4. The Permittee shall maintain Emergency Spill Cleanup materials in all vehicles used to transport used oil as specified in Condition II.G of this Permit.

## **II.C. Used Oil Loading and Unloading Requirements**

- II.C.1. The Permittee shall secure the vehicle by positioning wheel chocks and applying the emergency brakes before loading or unloading used oil.
- II.C.2. The Permittee shall inspect all used oil collection equipment (e.g., vehicles and associated pumping equipment) for any damage prior to use.
- II.C.3. The Permittee shall place buckets or other containers under piping connections to collect drips of used oil during loading and unloading operations.
- II.C.4. The Permittee shall ensure the amount of used oil to be loaded into the transport vehicle will not exceed the carrying capacity. The Permittee shall utilize a calibrated gauging instrument to measure used oil volume in each collection vehicle.
- II.C.6. The Permittee is allowed to transfer to rail cars in accordance with the rail car loading procedure in Attachment 1 (Rail Car Loading Procedures).

- II.C.6.a. During loading and unloading operations, two trained operators shall remain at the transfer location and maintain control of the operations throughout the entire used oil transfer.

**II.D. Used Oil Sampling and Analytical Procedures**

- II.D.1. Prior to loading the used oil for transport, the Permittee shall collect a representative sample using sampling procedures in Attachment 2 (Sample Collection Procedures) and screen the used oil for halogens using either Method 9077 specified in Condition II.D.4.d or a Utah-certified laboratory or documentation to support generator knowledge.

- II.D.2. Used oil determined to be on-specification by a Utah-registered marketer can be collected and transported without further testing. Bills of Lading or used oil transportation records shall include copies of the analytical results for reference.

**II.D.3. Sample Collection Requirements for Used Oil Containers**

- II.D.3.a. The Permittee shall ensure a representative sample is collected from tanks, totes, drums or other containers from which used oil is collected. Sampling personnel shall be trained on appropriate sampling methods for each type of container and matrix.
- II.D.3.b. Drums or containers of used oil from different sources or processes shall be sampled individually at each generator's facility.
- II.D.3.c. Composite sampling is only allowed for a maximum of 500 gallons from containers of used oil that are generated from the same source or process at each generator's facility.

**II.D.4. Halogen Field Screening Methods**

- II.D.4.a. The Permittee shall screen for halogens in the field, prior to the acceptance or delivery of used oil or oily water subject to R315-15 of the Utah Administrative Code as specified in Conditions II.D.4.b through II.D.4.d.
- II.D.4.b. Used oil that contains less than 20% water shall be screened for halogens with a CLOR-D-TECT® halogen test kit (EPA Method 9077).
- II.D.4.c. Used oil that contains between 20% and 70% water shall be screened for halogens with a HYDROCLOR-Q® test kit. The resulting halogen concentration must be corrected using the following conversion formula to calculate true halogen concentration.

*True Halogen Concentration = Reading Syringe + [(10 + ml oil in sample)/10]*

**Example:** sample contains 6 ml water and 4 ml oil (60% water) and the syringe reading is 2,000 ppm, then the true concentration is:

$$2,000 \text{ ppm } [(10 + 4)/10] = 2,800 \text{ ppm}$$



- II.D.4.d. Used oil that contains greater than 70% water shall be screened for halogens with a HYDROCLOR-Q<sup>®</sup> test kit. Correction of the halogen screening results is not required.
- II.D.4.e. The Permittee shall document on acceptance records the screening results to determine if the total halogens concentration of the incoming used oil is less than 1,000 ppm.
- II.D.4.f. Results of all halogen field screening results shall be recorded on the shipping document such as a bill of lading and results initialed by the sampler.
- II.D.4.g. The requirement for a quality control sample (duplicate) may be satisfied by testing prior to off-loading from permitted vehicles in accordance with the CLOR-D-TECT<sup>®</sup> kits (Method 9077 of SW846) and is not required for each load collected.
- II.D.5. **Halogen Laboratory Analytical Methods**
- II.D.5.a. When relying on laboratory testing, the Permittee shall submit a representative used oil sample to a Utah-certified laboratory to analyze for total halogen concentrations using Method 9076 or other equivalent method approved by the Director.
- II.D.6. **PCB Contaminated Used Oil**
- II.D.6.a. The Permittee shall not accept for transport used oil with PCB concentrations greater than or equal to 50 ppm. Used oils containing PCB concentrations greater than or equal to 50 mg/kg (ppm) are subject to TSCA regulations 40 CFR 761. Used oils containing PCB concentrations greater than or equal to 2 ppm but less than 50 ppm are subject to both R315-15 of the Utah Administrative Code and 40 CFR 761.
- II.D.6.b. The Permittee shall obtain analytical results of dielectric oil used in transformers and other high voltage devices, verifying the PCB concentrations are less than 50 mg/kg (ppm) prior to loading the used oil into the transportation vehicle.
- II.D.6.c. The Permittee shall determine the PCB concentration of other used oils not specified in Condition II.D.6.b through written certification from the generator or laboratory testing.
- II.D.6.d. Used oil may not be diluted to avoid any provision of any federal or state environmental rules.
- II.D.6.e. If PCB concentrations greater than 2 ppm have been transported, the Permittee shall assume that all subsequent loads of used oil are contaminated with PCBs and has a quantifiable PCB concentrations of 2 ppm or greater unless the equipment has been decontaminated as described in 40 CFR 761 Subpart S.
- II.D.6.f. Table II.D lists required laboratory PCB sample preparation and analytical methods.

**Table II.D: PCB Sample Preparation and Analytical Methods**

Methods	Analytical Methods:	Analytes	
		<i>PCB CAS RN</i>	<i>PCB Aroclor</i>
<b>Sample Preparation Methods:</b> 3580A and 3665A (Cleanup)	<ul style="list-style-type: none"> <li>8082A</li> <li>PCB Analytical Method</li> <li>Analyses of the Aroclors bolded in the last column are mandatory.</li> <li>Choose an additional two Aroclors from the last column for analysis which could be contained in the oil, which will make a total of seven Aroclors.</li> </ul>	<b>12674-11-2</b>	<b>1016*</b>
		147601-87-4	1210
		151820-27-8	1216
		<b>11104-28-2</b>	<b>1221*</b>
		37234-40-5	1231
		<b>11141-16-5</b>	<b>1232*</b>
		71328-89-7	1240
		<b>53469-21-9</b>	<b>1242*</b>
		<b>12672-29-6</b>	<b>1248*</b>
		165245-51-2	1250
		89577-78-6	1252
		<b>11097-69-1</b>	<b>1254*</b>
		<b>11096-82-5</b>	<b>1260*</b>
		37324-23-5	1262
		11100-14-4	1268

## II.E. Rebuttable Presumption

- II.E.1. Used oil with total halogen concentrations greater than 1,000 parts per million (ppm) is presumed to have been mixed with a hazardous waste and shall be managed as a hazardous waste unless the Permittee successfully rebuts the presumption.
- II.E.2. The Permittee may rebut the hazardous waste presumption in accordance with R315-15-4.5 of the Utah Administrative Code if the Permittee can demonstrate that the used oil does not contain significant concentrations of any of the halogenated hazardous constituents listed in Appendix VIII of EPA CFR 40, Part 261 which includes volatiles, semi-volatiles, PCBs, pesticides, herbicides and dioxin/furans.
- II.E.3. If the additional testing shows that used oil has been mixed with a listed hazardous waste listed in R315-2-10 of the Utah Administrative Code the mixture is subject to regulation as a hazardous waste regardless of the level of halogenated constituents.
- II.E.4. The rebuttable presumption does not apply to metalworking oils/fluids containing chlorinated paraffins if they are processed through a tolling arrangement as described in R315-15-2.5(c) of the Utah Administrative Code to reclaim metalworking oils/fluids. The rebuttable presumption does apply to metalworking oils/fluids if such oils/fluids are recycled in any other manner or disposed.

- II.E.5. The rebuttable presumption does not apply to used oils contaminated with chlorofluorocarbons (CFCs) removed from refrigeration units if the CFCs are destined for reclamation. The rebuttable presumption does apply to used oils contaminated with CFCs that have been mixed with used oil from sources other than refrigeration units.

**II.F. Used Oil Training**

- II.F.1. The Permittee shall train used oil handlers of used oil activities in accordance with R315-15-4 of the Utah Administrative Code and the requirements of this Permit. New employees may not manage or process used oil without a trained employee present until used oil training is completed.
- II.F.2. The Permittee shall follow a written training program (Attachment 3 – Training Plan). Employee training shall include documentation that the following topics were covered; identification of used oil, recordkeeping requirements and facility used oil procedures for handling, transporting, sampling and analysis, emergency response, spill reporting and personal safety.
- II.F.3. Employees collecting and performing field halogen testing shall be trained and demonstrate competence in collecting a representative used oil sample and testing for halogens using a CLOR-D-TECT<sup>®</sup> kit prior to fieldwork if Utah certified laboratory data is not available.
- II.F.4. The Permittee shall provide, at a minimum, an annual used oil training refresher course for employees handling used oil. Additional training is required if the Permittee changes used oil handling procedures or this Permit is modified.
- II.F.5. The Permittee shall keep training records for each employee for a minimum of three years. Employees and supervisors shall sign and date training attendance sheets to document class attendance.

**II.G. Spill Response, Remediation, and Reporting**

- II.G.1. In accordance with R315-15-9.1(a) of the Utah Administrative Code, the person responsible for the spill shall immediately take appropriate action to minimize the threat to human health and the environment and notify the DEQ Hotline at (801) 536-4123 if the spill is greater than 25 gallons or for smaller spills that pose threat to human health or the environment.
- II.G.2. Responders shall take action to prevent spill from spreading by utilizing absorbent, booms, pads, rags, etc. (Attachment 4 – Emergency Controls- Spill Plan).
- II.G.3. Once the material is containerized, a waste determination shall be made to determine the material's disposition.
- II.G.4. The Director may require additional cleanup action to protect human health or the environment.

- II.G.5. All costs associated with the cleanup shall be at the expense of the Permittee.
- II.G.6. Vehicle spill kits shall contain, at a minimum, the equipment listed in Table II.G of this Permit and shall be checked daily prior to collection activities.
- II.G.7. The Permittee shall report all relevant information, including the amount of waste generated from cleanup efforts, the characterization of the waste (i.e. hazardous or non-hazardous), final waste determination and disposal records. The report shall also include actions taken by the Permittee to prevent future spills.
- II.G.8. An air, rail, highway or water transporter who has discharged used oil shall give notice, if required by 49 CFR 171.15, to the National Response Center at <http://nrc.uscg.mil/nrchp.html>, (800) 424-8802. In addition to the notification above, a written report, as required in 49 CFR 171.16, shall be presented to the Director, Office of Hazardous Materials Regulations, Materials Transportation Bureau located in Washington, D.C., 20590.
- II.G.9. In accordance with R315-15-9.4 of the Utah Administrative Code, the Permittee shall submit to the Director a written report within 15 days of any reportable release of used oil.

**Table II.G: Spill Kit Equipment Requirements**

Equipment Description	Quantity
Shovel	1
Broom	1
Buckets	2
Spill Pads	10
Granulated Absorbent	2 ft <sup>3</sup>
Boom/oil Socks	1
Spill Plan with Emergency Contact Numbers	1
Blank Spill Report Sheets	5

**ATTACHMENT 1**  
**Renegade Oil Inc.**  
**Rail Car Loading Procedures**

The following procedure is designed to ensure that all railcars containing used oil and non-regulated waste are loaded safely and in compliance with all applicable regulations in order to minimize the potential for spills.

Two people with knowledge of loading and offloading procedures must be present during loading or off-loading of any rail car. If, at any time, one of the people must leave the operation, the operation must be stopped until a second qualified person is available.

**Rail Car Loading and Unloading Procedure**

1. Lock-out track with derailleurs at both ends of the rail spur so train operators know not to move any railcars on the spur during offloading.
2. Place railcar chocks on both sides of the wheels of the railcar while offloading.
3. Lay out black containment mat and position truck over the mat.
4. Set truck parking brake and chock both sides of one wheel of the truck to prevent accidental movement.
5. Ensure adequate spill response equipment is readily accessible. Including but not limited to:
  - a. 1 box of absorbent pads
  - b. 1 bag of Granulated Absorbent
  - c. 2 oil boom socks
  - d. 1 shovel
  - e. 1 empty 55 gallon drum.
  - f. 1 broom
6. Prior to railcar loading, fill out the Railcar Used Oil Transfer Log.
7. Take a beginning reading on truck to determine volume to be transferred.
8. Unsecure railcar manway/top hatch by removing I-bolts using a pipe wrench.
9. Open manway/top hatch and take a beginning reading on the rail car by using a tape measure and verifying the current railcar measurements with the railcar strapping chart to ensure there is enough space available for transfer.
10. One person must remain on top of the railcar and one person must remain at the tank truck connection at all times during transfer.
11. Hoist opposite end of hose up to railcar hatch, uncap hose end, and insert into railcar. The top man must hold the hose in place while transferring or a fill lid must be used.
12. Secure hose with bungee to the side of the railcar.
13. Check the cam lock gaskets for integrity and secure the cam lock ears down with a bungee.
14. Proceed with transfer operation.

15. Top man shall notify second operator immediately if the railcar appears to be filling to a level higher than expected so the operation can be stopped.
16. After transfer is complete, clear the hose of any material.
17. Cap and plug all hoses to prevent drips.
18. Close and secure the railcar hatch.
19. Complete all necessary paperwork and checklists including:
  - a. Load transfer BOLs;
  - b. Railcar inspections;
  - c. Railcar loading log.
20. Insure all tank files are updated after each transfer is completed.
21. Clear area of all safety equipment and clean area of any spills or drips prior to departing transfer area.
22. Remove locks from rail switches at both ends.
23. Remove derailleurs and railcar chocks.

**ATTACHMENT 2**  
**Renegade Oil Inc.**  
**Sample Collection Procedures**

Renegade Oil Inc. employees shall use the sampling procedures below to collect representative sample from customers' tanks and containers when screening used oil for halogen content prior to collection.

**Procedure 1: Containers - 375 gallons or less**

**Sampling Equipment:** Oil thief sampler 175 ml, 39 inch, sample jar.

**Step 1**

Take oil thief sampler and dip into drum or tote make sure the tube fills up a good cross section before covering top hole with finger

**Step 2**

Open sample jar and dispose contents from drum thief into sample jar

**Step 3**

Screen sample using CLOR-D-TECT halogen test kit.

**Step 4**

Empty the sample in the bucket back into the used oil container/tank.

**Procedure 2: Tankers/Pumper Trucks and Tanks/Containers  $\geq$  375 gallons**

**Sampling Equipment:** Dip tube sampler (Polypropylene/ plastic type tube) sampler.

**Step 1**

Lower the sampling tube slowly into the liquid waste at a rate that allows the liquid level inside and outside the tube to equalize. Manways located at the top of the Tanker/Pump trucks will be used to collect samples.

**Step 2**

Slowly withdraw Dip tube from the liquid. Either wipe the exterior of the sampler tube with a disposable cloth or allow excess liquid to drain back into the used oil container/tank.

**Step 3**

Discharge the sample by placing the lower end of the Dip tube into a sampling bucket.

**Step 4**

Screen sample using CLOR-D-TECT halogen test kit.

**Step 5**

Empty the sample in the bucket back into the used oil container/tank.

**ATTACHMENT 3**

**Renegade Oil Inc.  
Training Plan**

**GENERAL TRAINING**

All drivers transporting used oil will receive used oil training before participating in used oil processing and handling operations.

Utah-specific used oil training will be conducted on an annual basis to all employees involved in used oil handling in Utah. The training will be provided during scheduled company safety/training meetings, or as appropriate. Refresher training will cover general used oil management procedures, identification of used oil and rebuttable presumption/analysis requirements for used oil transportation in Utah, the “Emergency Controls/Spill Plan,” spill reporting, and personal safety and protection.

Records of this training (date, employee name & signature, items covered) will be kept and made available for inspection for three years, and a master copy will be kept in the company training file (Table 1).

**Table 1: Example of Used Oil Training Record**

<b>Date</b>	<b>Name</b>	<b>Signature</b>	<b>Comments</b>



**ATTACHMENT 4**  
**Renegade Oil Inc.**  
**Emergency Controls- Spill Plan**

**General Procedures**

1. Renegade Oil drivers shall immediately clean up any spills which occur during the transportation and loading/unloading of used oil.
2. Drivers shall maintain the integrity of the scene while ensuring the safety of bystanders and themselves. If bystanders or the driver is at risk then call 911 when warranted to summon emergency personnel to the scene.
3. The driver shall take action to prevent the spilled material from spreading by utilizing absorbent, dirt, booms, pads, rags, etc. The driver should prevent used oil from entering any adjacent storm water drain or sewer drain system.
4. In the event that more resources are required, contact your supervisor to dispatch a spill response team to help facilitate the mitigation and/or remediation of the spill.
5. Used Oil spills exceeding 25 gallons, or that pose a risk to human health and the environment, shall be reported to Renegade Oil management, and to the Utah Department of Environmental Quality and any other applicable regulatory agency immediately after containment of the spill (Table 1).

**Table 1: Regulatory Agency Notification Numbers**

<b>Regulatory Agency</b>	<b>Contact Phone Number</b>
National Response Center (when applicable)	(800) 424-8802
Utah Department of Environmental Quality (within 24 hrs.)	(801) 536-4123
Utah State Highway Patrol	(801) 538-3400

6. Renegade drivers shall submit a completed spill report to a supervisor at or before the end of the driver's shift. The report must follow the reporting requirements of R315-15 of the Utah Administrative Code and Renegade's Transporter Permit and include:
  - a. Name, phone number, and address of person responsible for the release
  - b. Name, title, and phone number of person reporting
  - c. Time and date of release
  - d. Location of the release (specific as possible)
  - e. Description contained on the manifest and the amount of material released
  - f. Cause of release
  - g. Possible hazards to human health or the environment and emergency action taken to minimize the threat (including the extent of injuries, if any).
7. Complete Spill Report and Incident Report and give to management.
8. Renegade Oil employees shall report any spills to management, regardless of the volume. Employees are exempted from reporting de minimis drips to management that are immediately cleaned up responsible employee.

9. Used oil transport vehicles shall maintain absorbents and equipment to contain a leaking containers and spills. The Permittee's used oil transport vehicles shall be equipped, at a minimum, with in the equipment listed in Table 2.

**Table 2: Spill Equipment List for Vehicles**

Equipment Description	Quantity
Shovel	1
Broom	1
Buckets	2
Spill Pads	10
Granulated Absorbent	2 ft <sup>3</sup>
Boom/oil Socks	1
Spill Plan with Emergency Contact Numbers	1
Blank Spill Report Sheets	5

10. A spill report of used Oil spills exceeding 25 gallons, or that pose a risk to human health and the environment, shall be submitted to the Division of Waste Management and Radiation Control within 15 days of the spill in accordance with R315-15-9.1.

11. Reporting Highway and Railcar Spills

If a spill occurs on a highway or railway, employees should immediately stop the release if possible, secure the scene and contain the spill. Immediately notify the Renegade Oil Management emergency contacts in Table 3 below. If there are, injuries to personnel/public or the spill will require additional emergency responders to contain then all 911 to request help. The discharge notification form is included in this spill plan shall be completed immediately by the operator after containment of the used oil, notification to emergency responders (if applicable) and Renegade Oil management.

**Table 3: Emergency Contacts List**

Contact Person	Title	Contact Information
Jorge Medina	Facility Manager	Mobile: 801-589-1246 Office: 801-973-7912 <a href="mailto:jorge@renegadeoil.com">jorge@renegadeoil.com</a>
Ryan Pezely	Company VP	Mobile: 801-631-7594 Office: 801-973-7912 <a href="mailto:ryan@renegadeoil.net">ryan@renegadeoil.net</a>
Fire Response (In case of fire or injury)	NA	911
Jerald Pezely	Company President	Mobile: 801-520-3567 Office: 801-973-7912 <a href="mailto:Renegadeoil@hotmail.com">Renegadeoil@hotmail.com</a>



# Utah Used Oil Handler Certificate

The following is permitted as a Used Oil Transporter with the Utah Division of  
Waste Management and Radiation Control pursuant to Utah Code Annotated  
Section 63J-1-504

Renegade Oil Inc.  
UOP-0158

**Effective Date:** November 30, 2015

**Expiration Date:** December 31, 2016

**Certificate No. T-46**

**Approved by:**

  
Director, Utah Division of Waste Management and Radiation Control