

Used Oil Transfer Facility Application

Application General Information								
Company Name (As registered with Utah Department of Commerce) Facility EPA ID # (Not for UOCCs)							NAICS (C ode (If e)
Com	pany Street Address	City			State	Zip Code	le Telephone # (10	
Mail	ing Address (If different than street address)	Iress (If different than street address) City State Zip Code				Telepho	one #	
Facil	ity's Street Address (If different than company)	City	City State Zip Code			Telephone #		
Company Owner						Telephone #		
Cont	tact Name & Title (If different than company ow	rner) Contact (e-mail A	ddress			Telephone #	
Lanc	Owner (If different than company/business owne	er)					Telephone #	
	Current a	and/or Previo	us Perr	nits with Ut	ah DEC	1		
Has your company ever held or currently holds any permits with Utah DEQ? If yes, please list them below (e.g. UO Transporter Permit, Water Quality Discharge Permit, Permit by Rule)								
#	Туре	Permit #	Permit # Type				Permit #	
1			3					

Regular Mail

2

Director of Utah Division of Waste Management & Radiation Control P.O. Box 144880 Salt Lake City, Utah 84114-4880

Phone: (801) 536-0200 **Fax:** (801) 536-0222

Fed Ex & UPS... Or in Person

Director of Utah Division of Waste Management & Radiation Control 195 North 1950 West Multi-Agency State Office Building, 2nd Floor Salt Lake City, Utah 84116

4

^{**} Please keep a copy of your Registration Application for your records **



Used Oil Transfer Facility Application

					Payment						
	Che	ck:\$200.00 payable to DEQ/D	WMRC - or	-	Online Payı	ment	<u>Portal</u>				
	-	licate the permit applicant's nat pose(s).	te the permit applicant's name and the e(s). Permit Application Fee (\$100.00) Used Oil Handler Fee (\$100.00)				ee				
			Busin	ess/Co	ompany Inf	orm	ation				
rar	sfer F	acility Operations Contact & Ti	tle					Tel	ephone	# (Area code	+ 7 digits
)pe	ration	s Contact e-mail						-			
rar	nsfer F	acility Environmental Contact	& Title					Tel	ephone	:#	
nvi	ronm	ental Contact e-mail									
					ty Informat						
					questions related	to you	ır facility)				
		Type of l (Tanks, tanker trucks, rail)	Jsed Oil Sto cars – Add ad	_		ry)			Capacity In Gallons	•	uantity Units)
	ks? (In	e maximum capacity of used oi Gallons) ride a detailed map of the facilit								ts and fire	
		nguishers	y, include di	etaneu	storage locati	10113,	secondary contain	mem,	, эрш кі	ts and me	
	_	u have stationary tanks, please ugh 200?	provide Uta	h Profe	essional Engin	eer ta	ank certification in	accor	dance v	with R315- 2	64-190
es	No	Answer all questions related	to your facil	ity (Pro	vide documents	as nee	ded)				
		Do you have secondary contai	nment for y	our use	ed oil storage i	inclu	ding truck parking	areas	?		
		Are your tanks and other stora	age units lab	eled "L	Jsed Oil" inclu	ıding	fill pipes for under	grour	nd tanks	s?	
		Will you be storing used oil filt	ters?								
		Will you be storing used oil wi	th PCBs? If y	es, pleas	se select the appl	icable	concentration from the	e follov	ving optic	ons	
		Less than 2 mg/kg (ppm per million)	= parts		ireater than ong/kg but less	-			eater th g/kg	nan or equal	to 50
low	do yo	ou plan to receive used oil?									
		Tanker Truck	Rail C	Car			Box Car			Drums/Cont	tainers
Vha	at type	e of storage units do you plan to	store used	oil?							
		Tanks	Tanke	er Truck			Rail car			Drums / Cor	
		Idiks	Tank	- Huck	`		Naii Cai			Drums / Cor	ntainers

How do you plan to ship us	sed oil from the fac	cility?				
Tanker Tr	uck	Rail Car		Box Car	Dr	ums/Containers
		Required Do	cument	s		
Business License From local city/county and any other applicable license(s) or registration(s)						
Certificate of Existence Or Letter of Good Standing From the state of incorporation (For Utah)						
Property Owner nformation (Utah Only) Documentation showing who owns the property (For Utah)						
	letter from the	NOT the property owner property owner to the roves of the proposed	Director	of the DWM&RC ackno	wledging tha	
Rail Car Loading and Unloading Plan	please subr	rant to utilize the Rail C nit a Rail Loading and Unload	ing procedu	re.		he Division? If NOT
Contingency/Emergency Controls and Spill Plan	Utah Emergen	cy Coordinator Contac	& Title	To	elephone #	
	Do you w Division?	ant to utilize the Conti	ngency/Er	nergency Controls and	Spill Plan pr	epared by the
	Spill Plan with	rish to use the plan dev this application in acco to operations in Utah.	-	•		
Financial Assurance (Please read carefully)		er facility, processor/re neral liability, 2) Enviro tion.				-
	General Liabili	ty				
		an "ACORD" certificate owing must be listed in Division Director Division of Waste N P.O. Box 144880 Salt Lake City, UT 84	the "Certi lanageme	ficate Holder" box of the nt and Radiation Cont		
	Environmenta	Pollution Liability				
Establish a financial assurance mechanism to protect against environmental pollution lia from either sudden, or sudden and non-sudden releases. Use one of the following (R31 a. Insurance b. Letter of Credit c. Surety Bond d. Trust Agreement Contact Brent Gaschler, the Division's Financial Assurance Administrator, at brgaschler@utah.gov and/or (801) 536-0034 or obtain specific requirements and requir					(R315-15-12.3):	
	Cleanup and Closure Default Protection					
Default protection in case the State of Utah must conduct clean up and closure. a. Prepare a cleanup and closure cost estimate in accordance with R315-15-11. b. Establish a financial assurance mechanism to cover the total amount of the clocure cost estimate, using one of the following (R315-15-12.3): i. Insurance ii. Letter of Credit iii. Surety Bond iv. Trust Agreement Contact Brent Gaschler (see contact info above)						

The application process can proceed without the financial assurance in place. However, prior to final approval of the permit, all financial assurance documents shall be submitted and approved by the Director. Applicants are advised to begin this process as soon as possible.

Certification

I certify under penalty of law that this application and all associated documents were prepared by me or under my direction or supervision. The information submitted is to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of a fine and imprisonment for knowing violations.

I hereby certify the forgoing is true and correct. Company owner must sign this form. (Keep a copy of this form for your records)

Name of Owner or Authorized Designee	Title
Signature	Date

Emergency Spill Plan For Transfer Facilities

[Default Plan]

1. Company Information

Company Name	Telephone Number (Area code + 7 digits)	
Company Physical Address	City	State and Zip Code

2. General Procedures

In the event of a release of used oil, the employee will immediately take the following appropriate actions to contain and minimize the spill and the threat to life, health, environment and property.

- Attempt to control or stop the leak if it can be done safely.
- Use absorbent material, brooms, spill pads and dirt dams and dikes if necessary to control the material. If possible, keep spilled material out of storm drains and open waterways.
- Contact 9-1-1 emergency responders if needed.
- Contact supervisor.
- If necessary, the supervisor will contact an authorized waste remediation company for assistance with the clean-up.
- Report used oil spills exceeding 25 gallons, or that pose risk to human health and the environment to management and to the Utah Department of Environmental Quality and any other applicable regulatory agency immediately after containment of the spill (Table 1).

Table 1: Regulatory Agency Notification Numbers

Regulatory Agency	Contact Phone Number
National Response Center	(800) 424-8802 or (202) 426-2675
Utah Department of Environmental Quality (within 24 hours)	(801) 536-4123
Utah State Highway Patrol	(801) 538-3400

The following information shall be provided by telephone to the Utah State Department of Environmental Quality's 24-hour answering service at (801) 538-3400.

- The names, telephone numbers and the addresses of the parties responsible for the release.
- The name, title and telephone number of the individual that is reporting the spill.
- Time and date of the release of used oil.
- Location of the release. Please be as specific as possible including nearest town, city, highway or waterway.
- Description of released material found in the manifest or shipping document, along with the amount of material released.
- Cause of the release.
- Possible hazards to human health or the environment and any emergency action taken to minimize these hazards.
- The extent of injury, if any.

If a spill occurs on a highway or railway, employees should immediately stop the release if possible, secure the scene and contain the spill. Facility shall give notice, if required by 49 CFR 171.15 to the National Response Center (Table 1). The Utah State Highway Patrol (table 1) shall be contacted if the spill restricts a public road.

A Spill report of used oil spills exceeding 25 gallons, or that pose risk to human health and the environment, shall be submitted to the Division of Waste Management and Radiation Control within 15 days of the spill in accordance with R315-15-9.4.

The driver/employee shall immediately notify their supervisor of reportable spills. If after hours, initial notification is to be made to the 24-hour emergency contacts in Table 2 below. If there are injuries to personnel/public or the spill will require additional emergency responders to contain it, then, call 9-1-1 to request help. The discharge notification form included in this spill plan shall be completed by the operator after containment of the used oil, notification to emergency responders (if applicable) and facility's management.

Table 2: Emergency Contact List

Contact Person	Title	e-mail	Phone Number
[Primary]			
[Secondary]			
Fire Response			9-1-1

The transporter shall maintain absorbents and equipment to contain a leaking containers and spills. At minimum each vehicle spill kit shall contain the items listed in Table 3.

Table 3: Spill Equipment Inventory for Facility

Equipment Description	Location	Quantity
Shovel / Broom / Vacuum		
Buckets		
Spill Absorbent Pads		
Granulated Absorbents		
Absorbent Boom / Oil Sock		
Emergency Controls Spill Plan (with contact numbers)		
First Aid Kit		
Fire Extinguisher		
Eye washer / Safety Shower		

Employees are exempted from reporting to management "de minimis" drips that are immediately cleaned up by the responsible employee.

The supervisor shall be responsible to initiate and complete any reporting and notification to the required Federal, State, and Local agencies.

3. Certification

Business owner or designee must sign this form.

Name of Owner or Designee	Title
Signature	Date

^{**} Keep a copy of this Used Oil Spill Containment Plan at the actual location **

Spill Report Form

[Template – For All UOCC's & Permitted Sites. Use ONLY for spills (Do NOT send with application]

Company Name:			Date of spill:
Company Address:			Time of Spill:
Location of spill (Name of business, street address, and	specific location of spil	I):	
Driver or responsible party:			
Others at the scene (List contact info):			
Approximate quantity of spill (Gallons):		Quantity of spi	lled product recovered (Gallons):
Type of absorbent used:		Quantity of ab	sorbent used to be disposed (Pounds):
How long did the spill continue?			
Any other pertinent information:			
Describe actions taken to minimize spill and the	en clean it up:		
Who was contacted? (Agencies – fire, police, health de	partment, EPA)		
Agency:	Date:	Time:	Contact:
Agency:	Date:	Time:	Contact:
Agency:	Date:	Time:	Contact:
Agency:	Date:	Time:	Contact:
* Notify the Utah Department of Environmental Quality, 24-that pose a potential threat to human health or the environmental Within 15 days after any release of used oil that is report written report to the Director of the Department.	hour Answering Servinent.	ce, (801) 536-4123 for us	ed oil releases exceeding 25 gallons, or smaller releases
Name of Responsible Party Signature of Responsible Party		Name of Manager Signature of Manag	er
Signature of Responsible Falty		Jignature of Warldy	
Date of Signature		Date of Signature	

^{**} This form should be filed in the company files after form is completed and signed. **

Procedures for Recording Halogen Content

[Default Plan]

1. Company Information

Company Name	Telephone Number (Area code + 7 digits)	
Company Physical Address	City	State and Zip Code

2. General Procedures

The Permittee's drivers shall document the halogen content of the used oil, the determination method and date of entry, if applicable, on the shipping record as follows:

3. Bill of Lading (Record for single transporter)

When the Permittee determines the halogen content using halogen field screening methods or laboratory analytical methods in accordance with the Analysis Plan the driver shall record the following halogen information:

```
Halogen ≤ 1,000 ppm/test, OR
Halogen > 1,000 ppm/test
```

When the Permittee determines the halogen content using Generator Knowledge provided by the generator, the driver shall record the following information:

```
Halogen ≤ 1,000 ppm/GenKno, OR
Halogen > 1,000 ppm/GenKno
```

Note: The Bill of Lading must be dated.

4. Manifest (Record for single or multiple transporters)

When the Permittee determines the halogen content using halogen field screening methods or laboratory analytical methods in accordance with the Analysis Plan the driver shall record the following halogen information and date the entry in the special handling box of the manifest.

```
Halogen ≤ 1,000 ppm/test, OR
Halogen > 1,000 ppm/test
```

When the Permittee determines the halogen content using Generator Knowledge provided by the generator, the driver shall record the following information:

```
Halogen ≤ 1,000 ppm/GenKno (Date), OR
Halogen > 1,000 ppm/GenKno (Date)
```

Analysis Plan

[Default Plan]

1. Company Information

Company Name	Telephone Number (Area code + 7 digits)		
Company Physical Address	City	State and Zip Code	

2. General Requirements

The Permittee shall verify that the halogen content of the used oil collected prior to transport in accordance with at least one of the following halogen verification methods in accordance with 3 through 5 of this plan:

3. Halogen Field Screening Methods

If the Permittee screens the generator's used oil to verify halogen concentrations, the Permittee shall use a halogen field screening method in accordance with the following requirements:

- a. Used oil that contains less than 20% water shall be screened for halogens with a CLOR-D-TECT[®] halogen test kit (EPA Method 9077).
- b. Used oil that contains between 20% and 70% water shall be screened for halogens with a HYDROCLOR-Q[®] test kit. The resulting halogen concentration must be corrected using the following conversion formula to calculate true halogen concentration.

True Halogen Concentration = Reading Syringe + [(10 + mL oil in sample)/10]

<u>Example:</u> Sample contains 6 mL water and 4 mL oil (60% water) and the syringe readings is 2,000 ppm, then the true concentration is:

$$2,000 ppm [(10 + 4)/10] = 2,800 ppm$$

- c. Used oil that contains greater than 70% water shall be screened for halogens with a HYDROCLOR-Q[®] test kit. Correction of the halogen screening results is not required.
- d. The Permittee shall document on acceptance records of bill of lading the screening results.
- e. The requirement for quality control sample (duplicate) may be satisfied by testing prior to off-loading from permitted vehicles in accordance with the CLOR-D-TECT[®] kits (EPA Method 9077) and is not required for each load collected at individual generators.

4. Halogen Laboratory Analytical Methods

If the Permittee submits a representative used oil sample to a Utah-certified laboratory to analyze for total halogen concentration, the Permittee shall use Method 9076 or other equivalent method approved by the Director.

The Permittee shall document the analytical results on the transportation document such as a bill of lading or manifest.

5. Halogen Generator Knowledge Method

The Permittee shall have information on file, (e.g., analytical testing, industry process knowledge) from the generator which is sufficient, as determined by the Director, to support any use of generator knowledge.

The Permitee may not rely solely on safety data sheet (SDS) in making a halogen concentration determination.

If relying on generator knowledge, the Permittee shall document on the shipping record the use of generator knowledge in accordance with the Permittee's Procedures for Recording Halogen Content.

Used oil determined to be on-specification by Utah-registered marketer can be collected and transported without further testing. Bills of lading, manifests or other used oil transportation records shall include copies of the analytical results for reference.

6. PCB Contaminated Used Oil

Used oils containing PCB concentrations greater than or equal to 50 mg/kg are subject to TSCA regulations 40 CFR 761. Used oils containing PCB concentrations greater than or equal to 2 mg/kg but less than 50 mg/kg are subject to both R315-15 f the Utah Administrative Code and 40 CFR 761.

Table 1 lists required laboratory PCB sample preparation and analytical methods.

Table 1: PCB Sample Preparation and analytical Methods

Sample Preparation Methods	Analytical Methods	Analytes*	
3500C (General) 3580A (Preparation) 3665A (Cleanup)	8082A	PCB CAS RN	PCB Aroclor [®]
		12674-11-2	1016*
		147601-87-4	1210
		151820-27-8	1216
		11104-28-2	1221*
		37234-40-5	1231
		11141-16-5	1232*
		71328-89-7	1240
		53469-21-9	1242*
		12672-29-6	1248*
		165245-51-2	1250
		89577-78-6	1252
		11097-69-1	1254*
		11096-82-5	1260*
		37324-23-5	1262
		11100-14-4	1268

^{*} Note: Analyses of the seven Aroclors® bolded/* in the last column are mandatory to analyze. Additional Aroclors® may be selected from the last column for analysis if contained in the oil.

The Permittee shall obtain analytical results of dielectric oil used in transformers and other high voltage devices, verifying the PCB concentrations are less than 50 mg/kg prior to loading the used oil into the transportation vehicle.

PCB used oil may not be diluted to avoid any provision of 40 CFR 761.

If PCB concentrations greater than or equal to 2 mg/kg have been transported, the Permittee shall assume that all subsequent loads of used oil are contaminated with PCBs and has a quantifiable PCB concentrations of 2 mg/kg or greater unless the equipment has been decontaminated as described in 40 CFR 761 Subpart S.

Sample Collection Procedures

[Default Plan]

1. Company Information

Company Name		Telephone Number (Area code + 7 digits)
Company Physical Address	City	State and Zip Code

2. General Requirements

Employees shall use the sampling procedures described below to collect representative samples from customers' tanks and containers when screening used oil for halogen content prior to collection.

3. **Procedure 1 – Containers < 375 gallons** [Add specific sampling procedure]

a. Sampling Equipment

Composite Liquid Waste Sampler (COLIWASA) nominally 175 mL, 39 inch sampler jar.

i. Step 1

Take COLIWASA and dip into drum or tote, make sure the tube fills up completely before closing.

ii. Step 2

Open sample jar and dispense the entire contents from COLIWASA into sample jar.

iii. Step 3

Screen sample using CLOR-D-TECT halogen test kit in accordance with facility's Analysis Plan.

iv. Step 4

Empty the sample in the bucket back into the used oil container/tank.

4. Procedure 2 – Tanks ≥ 375 gallons [Add specific sampling procedure]

a. Sampling Equipment

Dip tube sampler (Polypropylene/plastic type tube) sampler.

i. Step 1

Lower the sampling tube slowly into the liquid waste at a rate that allows the liquid level inside and outside the tube to equalize. Man-ways openings located at the top of the Tanker/pump trucks will be used to collect samples.

ii. Step 2

Slowly withdraw dip tube from the liquid. Either wipe the exterior of the sampler tube with a disposable cloth or allow excess liquid to drain back into the used oil container/tank.

iii. Step 3

Discharge the sample by placing the lower end of the dip tube into a sampling bucket.

iv. Step 4

Screen sample using CLOR-D-TECT® halogen test kit.

v. Step 5

Empty the sample in the bucket back into the used oil container/tank.

Railcar Loading Procedures

[Default Plan]

1. Company Information

Company Name		Telephone Number (Area code + 7 digits)
Company Physical Address	City	State and Zip Code

2. General Procedure

The following procedure is designated to ensure that all railcars containing used oil (may use for non-regulated waste) are loaded safely and in compliance with all applicable regulations in order to minimize the potential for spills.

Two people with knowledge of loading and offloading procedures must be present during loading or offloading of any railcar. One person must remain on top of the railcar and one person must remain at the tank truck connection at all times during transfer. If at any time, one of the people must leave the operation, the operation must be stopped until a second qualified person is available. A single operator may be used is a secure dome lid connector is used to attach the upper hose to the railcar, the operator remains in sight of all connections, and the pump controls are readily accessible.

3. Rail Car Loading and Unloading Procedure

- a. Lock-out track with derailers at both ends of the rail spur so train operators know not to move any railcars on the spur during offloading.
- b. Place railcar chocks on both sides of the wheels of the railcar while offloading.
- c. Securely park used oil transportation trucks on an asphalt or concrete loading pad. Black containment mat or other containment structure during the loading and unloading of used oil between the trucks and rail tanker car.
- d. Set truck parking brake and chock both sides of one wheel of the truck to prevent accidental movement. Ensure adequate spill response equipment is readily accessible per procedures in Emergency Spill Plan.
- e. Prior to railcar loading, fill out Railcar Used Oil Transfer Log.
- f. Take an initial reading on truck to determine volume to be transferred.
- g. Unsecure railcar man-way/top hatch by removing I-bolts using a pipe wrench.
- h. Open man-way/top hatch and take an initial reading on the rail car by using a tape measure and verifying the current railcar measurements with the railcar strapping chart to ensure there is enough space available for transfer.
- i. Hoist opposite end of hose up to railcar hatch, uncap hose end, and insert into railcar. The person at the top must hold the hose in place while transferring or a fill lid must be used.
- j. Secure the hose to the side of the railcar, or candy-cane shaped stick, or other transfer equipment.
- k. Check the cam lock gaskets for integrity and secure the cam lock ears down.
- I. Proceed with transfer operation.
- m. If dome lid is not in use, the person at the top shall notify the second operator immediately if the railcar appears to be filling to a level higher than expected so the operation can be stopped.
- n. After transfer is complete, clear the hose of any material.
- o. Cap and plug all hoses to prevent drips.
- p. Close and secure the railcar hatch unless dome lid is in use.
- q. Complete all necessary shipping documentation and checklists.
- r. Ensure all tank files are updated after each transfer is completed.
- s. Clear are of all safety equipment and clean area of any spills or drips prior to departing transfer area.
- t. Remove derailers and railcar chocks when car is full and transfer operation has finished.

Useful Information

- Permittees must abide by the "Standards for the Management of Used Oil" R315-15. These rules may be more stringent than Federal EPA regulations. Visit https://adminrules.utah.gov/public/search//Current%20Rules under the Environmental Quality Agency tab, Waste Management and Radiation Control (315) Title tab, Standard for the Management of Used Oil (15) for the Used Oil Rules. Visit https://le.utah.gov/xcode/Title19/Chapter6/19-6-P7.html?v=C19-6-P7 1800010118000101 for the Used Oil Management Act.
- Failure to comply with Permit requirements or the Rules may lead to enforcement actions and/or revocation of a permit.
- Permittees are required to submit an annual report by March 1, of each year, for the prior calendar year. To view or download the form: <a href="https://deq.utah.gov/waste-management-and-radiation-control/forms-division-of-waste-management-and-radiation-control/forms-division-control/forms-division-control/forms-division-
- Permittees are subject to periodic used oil program inspections.
- All records associated with used oil transportation must be kept for a minimum of 3 years.
- Permittees must comply with all applicable Dept. of Transportation regulations (49 CFR 171 180). Contact UDOT (801-965-4000) for more information.
- Transporting used oil prior to receiving a final permit shall lead to enforcement actions including monetary penalties.

General Information

What is used oil?

Used oil is any oil, refined from crude oil (mineral oil) or synthetic oil, that has been used and as a result of that use is contaminated by physical or chemical impurities. Some common examples include used lubricating oils, hydraulic oils, transmission fluids, compressor oils, transformer oils, metalworking oils, or any mixtures of any of these items with other materials.

Used oil is not virgin oil, vegetable oil, or bio-diesel (unless mixed with used oil).

What are the Rules for Used Oil?

"Standards for the Management of Used Oil" (R315-15) may located at https://adminrules.utah.gov/public/search//Current%20Rules

Who Needs a Transporter Permit?

Anyone who plans to transport used oil (see definition above) in amounts of more than 55 gallons at one time. This will usually be a business that collects used oil from one or more generator locations, and then transports the used oil to another location to be processed/re-refined, burned for energy recovery or transferred to another permitted facility. A used oil transporter must first obtain a permit prior to transporting used oil in Utah even if you are currently a hazardous waste transporter.

Who does not need a Used Oil Transporter Permit?

- 1. Farmers who transport one 55-gallon drum of used oil (at one time) to a used oil collection center.
- 2. Do-It-Yourselfer (DIYer) households who transports less than 5 gallons to a used oil collection center.
- 3. Businesses that transport less than 55 gallons per visit to a Type C or D used oil collection center (collection center that can accept business oil).

Who Needs a Transfer Facility Permit?

A transfer Facility Permit will also be required if used oil will be held at transportation-related facilities including loading docks, parking areas, storage areas or other areas more than 24 hours and not longer than 35 days.

Who Needs a Processor Permit?

A Processor Permit is required if the used oil collected by a transporter will be held 35 days or more. If you are uncertain if you need a permit, please check with the Division at (801) 536-0200.

A complete and detailed application will greatly minimize time and charges. We recommend contacting the Division if you would like to discuss the application prior to submission.

Fees

- A one-time filing fee of \$100 is required and must be attached with each permit application.
- A registration fee of \$100 is also required to obtain a Used Oil Handler Certificate that is necessary to operate as a Used Oil Transfer Facility in Utah. This is an annual registration fee that will need to be renewed by December 31 of each calendar year. This fee must also be attached.
- The Permittee will be billed for actual costs associated with the review of the registration application and registration preparation.

Definitions

USED OIL – Means any oil, refined from crude oil or synthetic oil, that has been used and as a result of that use is contaminated by physical or chemical impurities. Used oil includes engine oil, transmission fluid, compressor oils, metalworking oils, hydraulic oil, brake fluid, oils used as buoyants, lubricating greases, electrical insulating, and dialectic oils. (R315-015.1.7.d)

USED OIL COLLECTION CENTER (UOCC) – There are four types of UOCC, type A, B, C, and D.

- Type A and B is any site or facility that accepts/aggregates and stores used oil collected only from household doit-yourselfers (DIYers) in quantities not exceeding five gallons per visit.
- Type B used oil collection center is any site or facility that accepts/aggregates and stores used oil collected from farmers as required by R315-15-2.1(a)(4) in quantities not exceeding 55 gallons per visit from farmers and not exceeding five gallons per visit from household do-it-yourselfers.
- Type C used oil collection center is any site or facility that accepts/aggregates and stores used oil collected from used oil generators regulated under R315-15-2 who bring used oil to the collection center in shipments of no more than 55 gallons under the provisions of R315-15-2.5(a). Type C used oil collection centers may also accept used oil from household do-it-yourselfers and farmers described in R315-15-2.1(a)(4).
- Type D used oil collection center is any site or facility that only accepts/aggregates and stores used oil collected from used oil generators regulated under R315-15-2 who bring used oil to the collection center in shipments of no more than 55 gallons under the provisions of R315-15-2.5(a). Type D used oil collection centers do not qualify for reimbursement.

USED OIL FUEL MARKETER – Means any person who conducts either of the following activities: (a) directs a shipment of off-specification used oil from its facility to a used oil burner; or (b) first claims the used oil to be burned for energy recovery meets the used oil fuel specifications set forth in R315-15-1.2. A person may not act as a used oil marketer without receiving a registration number issued by the Director of the Division of Waste Management & Radiation Control pursuant to R315-15-13.7.

USED OIL OFF-SPECIFICATION BURNER – An off-specification used oil burner is a person who burns used oil not meeting the specifications found in R315-15-1.2 for energy recovery. (R315-015-6.1.a)

USED OIL PROCESSOR/RE-REFINER FACILITY – Used oil Processor/re-refiner facilities are facilities designed for processing used oil. Processing means chemical or physical operations designed to produce from used oil, or to make used oil more amenable for production of, fuel oils, lubricants, or other used oil-derived products. Processing includes: blending used oil with virgin petroleum products, blending used oils to meet the fuel specification, filtration, simple distillation, chemical or physical separation and re-refining. (R315-015-5.1.a)

USED OIL TRANSFER FACILITY – Used oil transfer facilities are transportation-related facilities including loading docks, parking areas, storage areas, and other areas where shipments of used oil are held for more than 24 hours during the normal course of transportation and not longer than 35 days. Transfer facilities that store used oil for more than 35 days are subject to the processor/re-refiner requirements found in R315-15-4.6.

USED OIL TRANSPORTER – Persons who transport used oil, persons who collect used oil from more than one generator and transport the collected used oil, and owners and operators of used oil transfer facilities are used oil transporters. (R315-015-4.1a)

The owner or operator shall notify the Utah Division of Waste Management & Radiation Control in writing of any changes in the information submitted on the registration within 20 days of the change.

A registered used oil facility (when applicable) shall maintain a complete record of all analyses and transactions, documented by reproducible receipts for three years; and, upon request, make available to the Division for inspection or photocopying, all applicable analysis, records, and receipts for purposes of review and audit.