

ATTACHMENT 3

**GROUNDWATER FLOW AND SOLUTE TRANSPORT MODEL
FOR TOOELE ARMY DEPOT**

Groundwater Flow and Solute Transport Model for Tooele Army Depot, Tooele, Utah

1. Background

A. From 1968 to 1988, various hazardous wastes produced by TEAD activities were disposed in wastewater which flowed through four unlined ditches to an unlined Industrial Waste Lagoon (IWL). These disposal practices led to groundwater contamination which the U.S. Army Corps of Engineers (USACE) began investigation in 1979. The IWL was closed in 1988. A RCRA post-closure permit was subsequently issued for the site on January 7, 1991. After several assessments and investigations, a pump and treat system to isolate and remediate TCE contamination in the groundwater was designed and constructed. The system was placed in operation in the fall of 1993. The groundwater treatment system consists of 16 extraction wells and 13 injection wells, along with two stripping towers designed to treat up to 8,000 gpm.

2. Purpose of Modeling Efforts

A. From January 1993 to the present, the U.S. Army Corps of Engineers, Hydrologic Engineering Center (HEC), with the assistance of GeoTrans Inc beginning in 2003, have developed a series of computer models for simulating groundwater flow contaminant transport conditions at the Tooele Army Depot (as specified in Volume I, Table V-3).

B. The primary objective of these modeling efforts was originally to provide a tool for determining optimum pumping rates and locations for the hydrodynamic isolation of the TCE plume below and to the north of the closed Industrial Waste Lagoon (IWL). Following the shut-down of the pump-and-treat system in 2004, the models primary use was to understand the hydrologic controls on contaminant plume migration, to analyze the relative impact of specific source areas, and to evaluate corrective measure alternatives.

3. Abstract of Modeling Efforts

A. 1998 Flow and Transport Model (HEC, 1998)

(1) In 1994, a three dimensional finite difference flow model was used to simulate groundwater flow at a TCE contaminated site within the Tooele Army Depot. The modeled area of 15,600 feet by 24,000 feet was overlain by a 51 x 80 grid of square cells 300 ft on each side. The model was constructed in 3 layers simulating confined and unconfined flow conditions. Relative to the 1994 model, in the 1998 model represents an extension of 4,200 ft to the northeast, 3,000 ft to the northwest, and 6,000 ft to the southeast. The model was extended to the northeast to reduce model boundary effects. The model was extended to the northwest to allow for the simulation of the natural attenuation of groundwater contaminants. The model was extended to the southeast to incorporate key data points in the Industrial Area. The 1998 model covers a total of 19,800 feet by 33,000 feet. The model area was overlain by a grid of 99 columns and 165 rows of square cells, 200 ft on each side. The total number of model cells

increased from 12,480 cells in the 1994 model, to 49,005 cells in the 1998 model. The flow model utilized head-dependent flux, recharge, and specified flow boundaries to represent the hydrogeologic setting.

(2) Two model calibrations were performed; a pre-pumping calibration to water levels which were averaged over 4 seasonal measurements taken between June of 1992, and September of 1993; and a calibration to water levels which were measured in March of 1997., approximately 3 years following the commencement of operation of the pump-and-treat system. A total of 58 water elevations were selected as calibration targets for the pre-pumping calibration study, and a total of 61 water level measurements were used as calibration targets for the post-pumping calibration study. Values of hydrogeologic parameters were derived from field measurements and past regional studies. Transmissivity values from model calibration showed good correlation to transmissivity values estimated from aquifer tests, bedrock pressure tests, and regional flow estimates.

(3) The particle tracking model MODPATH was applied to both pre-pumping and post-pumping scenarios. Results from particle tracking analysis illustrated the controlling influence the uplifted bedrock block has on groundwater flow paths. An initial contaminant transport model was developed using the code MT3D. Results from the transport model indicate that significant reduction in total pumping rates can be incurred by optimizing the extraction system to focus on contaminant concentrations exceeding 50 ppb. Additionally, by adjusting clean-up levels to 50 ppb, model results indicated that minimal environmental impact from the migration of the lower concentration plume downgradient due to natural attenuation. Future investigations will concentrate on identifying contaminant sources and delineation the northeast boundary of the uplifted bedrock block.

B. 1999 Flow and Transport Model (HEC, 2000)

(1) The primary purpose of this calibration effort was to construct an additional model layer to better delineate the location of the bedrock block in the alluvium to the southeast of the uplifted bedrock block.

(2) Previous models of the site consisted of an upper layer (layer 1) located from the water table to a depth of 150 ft. Layer 2 was specified to have a thickness of 150 ft and was located beneath layer 1. Layer 3 was specified to have a thickness of 300 ft and was located beneath layer 2. Thus, past models simulated this area as having a thickness of 150 ft of alluvium overlying the bedrock. Since the construction of the original 1994 model, additional field evidence has indicated that the southern alluvium was significantly thinner than 150 ft. The purpose of this study was to better simulate this zone.

(3) Additionally, this study incorporated the most recent field data available. Water level data as recent as October 1999 was used in "post-pumping" calibration runs. Average extraction and injection rates were derived from the total volume of pumping from the commencement of the system operation to October 1999.

C. 2000 Flow Model (HEC, 2000a)

(1) The 2000 model consists of 4 layers, 165 rows, and 99 columns. Model cells are 200 ft square. Model layer thickness is specified relative to water table elevation. Layer 1 is 50 ft thick, layer 2 is 100 ft thick, layer 3 is 150 ft thick, and layer 4 is 400 ft thick.

(2) As the uplifted bedrock is a controlling hydrogeologic feature at the Tooele study site, the slightest conceptual alternation of the location or permeability of the bedrock block results in significant changes in flow and water levels throughout the study area. In 2000, a geophysical survey was conducted along the northeast boundary of the Tooele Army Depot. This resulted in a new conceptualization of the bedrock location. The primary purpose of the 2000 calibration effort was to incorporate this new information on the location of the bedrock block.

(3) The work performed for this recalibration included the following:

(a) Reconceptualization of the northeast bedrock block based on interpretation of geophysical data.

(b) Incorporation of the conceptual location southeast bedrock block according to boring log interpretations.

(c) The zone of low hydraulic conductivity (K) fault gouge encasing the uplifted bedrock block in the central area of the site was reconstructed.

(d) A new zone of a slightly higher K was incorporated in layer 1, northeast and up gradient of the bedrock block. This allows for more flow into the bedrock block in the northeast area as indicated by increasing contaminant levels in the area.

(e) The addition of a head dependant flux boundary condition along the northeast model boundary. This allows water to flow off-site to the northeast.

(f) The southwestern displaced sediments zone was realigned to trend in a more geologically realistic direction

(g) The northeastern displaced sediments zone was realigned to trend in a more geologically realistic direction.

D. 2001/2002 Recalibration Study (HEC 2001/2002)

(1) The 2001/2002 ground water flow model consisted of a reconstructed 9 layer model, consisting of 165 rows and 99 columns with 200 ft square model cells.

(2) The 9 layer structure of the model resulted in a more precise delineation of the hydrologic system. Additionally, the new layer structure included thinner layers in the upper 300 feet of the model domain, allowing for a more accurate simulation of contaminant transport in the future.

(3) A revised conceptual model of the study area was integrated into the model. This resulted in the adjustment of the bedrock location, the relocation of the southwestern displaced sediments zone, and the creation of two new fault zones.

(4) The model was calibrated to two sets of water level data: 157 water levels representing Spring of 2001 conditions, and the average of 7 semi-annual measurements at 54 wells between Spring 1997 to Spring 2001. Model conceptualization was initially based on the larger Spring 2001 data set. The model was then calibrated to the averaged data set. A final calibration was performed with the goal of achieving the best fit between the two data sets. By attaining a good calibration with both data sets, the 2001/2002 modeling study provided validation for the use of the new, larger data set in future calibration studies.

(5) The following tasks were completed as part of the 2001/2002 modeling study:

(a) The model was reconstructed as 9 layers. Layer bottom elevation were specified as constant through the entire model domain. Layer thickness in the southern alluvium was reduced to 25 feet in the upper two model layers. Layer thickness in the northern alluvium was reduced to 25 feet in the upper layer.

(b) Data quality analysis was performed on Spring 2001 and Fall 2001 water level measurements. Significant discrepancies between the two data sets were discovered. This was the result of varying extraction well rates in the bedrock area. Thus, it was determined that the Fall 2001 data should not be used in this calibration study.

(c) Data quality analysis was performed on 174 Spring 2001 water level measurements. This resulted in the removal of 17 water level measurements from the calibration study.

(d) Extraction and injection pumping well data through Spring 2001 was incorporated into the model.

(e) the coordinates of observation wells used in the calibration study were adjusted to the most recent survey data.

(f) The screened elevations of pumping wells and observation wells were incorporated into the model.

(g) The location of the uplifted bedrock block was reconceptualized based on potentiometric and geophysical data interpretations.

(h) The location of the southwestern displaced sediments zone was reconceptualized based on Spring 2001 water level data.

(i) Water level measurements from the recently constructed D-wells at the eastern end of the study area were integrated into the calibration process. A low permeability fault zone was created to allow for the simulation of a sharp drop in water levels measured in the proximity of the D-wells.

(j) Specified heads of boundary conditions at the southeast, northeast and northwest model boundaries were adjusted to reflect ground water table elevations according to revised ground water contour maps.

(k) The model was calibrated to two sets of water level data: 157 water levels representing Spring 2001 conditions and the average of 7 semi-annual measurements taken at 54 wells between Spring 1997 to Spring 2001.

E. 2003 Groundwater Flow and Transport Model (HEC, 2003)

(1) This model calibration study included several changes and additions to the prior models. Changes and additions consisted of:

(a) The model grid was extended 2,000 feet to the northeast to allow for a more accurate representation of flow at the northeast boundary.

(b) An algorithm was developed for the simulation of more representative well extraction rates.

(c) A revised conceptualization of bedrock, based upon geophysical studies, was integrated into the model.

(d) A much larger calibration data set was incorporated allowing for a more complex and accurate numerical representation of the site.

(e) The analysis also included the calibration of the transport model.

(2).. The model was calibrated to 184 water levels measured in the spring and fall of 2002. Additionally the model was calibrated to regional estimates of subsurface inflow, measured drawdown in the uplifted bedrock block and the migration of the TCE plume.

(3) The final model head calibration produced an absolute mean error of 1.76 ft. The absolute mean error of the prior (2001/2002) calibration study was 1.94 ft. The prior study used 157 calibration targets. The final model also reproduces the approximately 40 ft observed drawdown in the bedrock block due to groundwater pumping, and it matches prior estimates of groundwater inflow along the southeast boundary.

(4) The TCE plume produced by the model is a reasonable match to the observed plume, with a few noted exceptions.

(a) The model under predicts some concentration in the northern alluvium, but may over predict concentrations in other areas of the model.

(b) The simulated northeast plume is significantly different from the measured northeast plume.

(c) Approximately 992 kg of TCE have been removed by the groundwater extraction and treatment system. The model simulates a high TCE removal of 1430 kg. These facts suggest that either the modeled mass from source areas is too high or that the treatment system is less effective than modeled (or both). However, reduction in the source strength would lead to a poorer match to observed TCE concentrations, and reductions in extraction rates would not be realistic.

F. 2004 Groundwater Flow and Transport Model (HEC/Geotrans, 2004)

(1) This model calibration study includes several changes and additions to the prior models of TEAD. Changes consisted of:

(a) The model grid was extended 10,200 ft to the northeast and 1,200 ft to the southeast to allow for a more accurate representation of the regional flow regime.

(b) A revised conceptualization of the bedrock, based upon recent geophysical studies and analysis of bore logs, was integrated into the model.

(c) Three new Tooele City production wells were input into the model. The incorporation of a larger calibration data set allowed for a more complex and accurate numerical representation of the site.

(d) A transport model calibration was also included in this analysis.

(2) The model was calibrated to 195 water levels. Additionally the model was calibrated to regional estimates of subsurface inflow, measured drawdown in the uplifted bedrock block, and the migration of the TCE plume.

(3) The TCE plume produced by the model is a reasonable match to the observed plume, both under current conditions and development of the plume. The modeled results compare better with observed results than the prior model (HEC, 2003) particularly for the northeastern boundary plume area. There are a few noted exceptions where the model does not match observed conditions as well as other areas. In particular, the model under predicts some concentrations in the northern alluvium, but may over predict concentration in other areas of the model.

(4) Approximately 992 kg of TCE have been removed by the groundwater extraction and treatment system since June 2002. The model simulates removal of 1135 kg, which is within ten percent of measured.

G. Addendum, 2004 Groundwater Flow & Transport Model (HEC/Geotrans, 2004a)

(1) Due to time constraints for submittal of the 2004 model, the planned transport sensitivity analysis for 2004 was not completed in time for inclusion in the document. This addendum documented the TCE transport sensitivity analysis conducted subsequent to the model submittal.

(2) Prior to conducting the TCE transport sensitivity analysis, a sensitivity analysis on the groundwater flow model was performed by varying hydraulic conductivity of specific structural features of the site, hydraulic conductivity of subsurface material of the entire site, and areal recharge.

(3) The sensitivity analysis for the TCE transport model involved changes to parameters that directly affect TCE movement, but do not alter the groundwater flow field. These parameters were:

- (a) Effective porosity
- (b) Distribution coefficient (K_d)
- (c) Dispersivity
- (d) Source area loading

(4) In addition to the above parameters, the model was run with two additional numerical techniques for solving the solute transport equation.

(5) The sensitivity analysis conducted will be used to guide the scope of the 2005 model calibration and uncertainty analysis. Recommendations are provided in this document for future analysis.

H. 2005 Groundwater Flow and Transport Model (HEC/Geotrans, 2005)

(1) Recovery data following the summer 2004 shutdown of the groundwater treatment system facilitated a more accurate delineation of the bedrock encasing zone and faults, providing a significantly more accurate representation of the flow system. This resulted in an improved conceptualization of a controlling hydrologic feature of the site. The encased bedrock zone was expanded to the south and northwest relative to the 2004 model.

(2) The flow model was calibrated to four data sets consisting of:

- (a) Water levels measured in June 2004;
- (b) Water levels measured in September 2004;
- (c) A long-term average data set; and
- (d) Transient data from recovery following shutdown

(3) The model generally reproduces recovery curves in the bedrock block and alluvium due to shutdown of groundwater pumping. The model also matched prior estimates of groundwater inflow into the model domain, and simulated the general regional flow domain.

(4) The TCE plume produced by the model is a reasonable match to the observed plume, both under current conditions and during the development of the plume. The model results compare favorably with observed results and the prior model (HEC/Geotrans, 2004).

(5) Calibration to the recovery data and subsequent sensitivity analyses were used to analyze the relative influence of parameters on transient water levels. Changes in horizontal hydraulic conductivity primarily affected the total simulated head change over a time interval. Changes in vertical hydraulic conductivity and specific storage primarily affected the initial rebound following shutdown. Changes in specific yield/porosity primarily affected the slope of the recovery curve.

(6) The steady-state and transient calibrations demonstrated the model's ability to replicate changes in water levels resulting from changes in stress on the system. The good match with several independent data sets provides additional validation and reduces the uncertainty of the model. Porosity is important for simulating plume migration. In the past porosity was estimated from tables. Calibration to measured recovery provided a physical basis for porosity values in bedrock and alluvium.

I. 2006 Groundwater Flow and Transport Model (HEC/Geotrans, 2006)

(1) Groundwater level recovery data following the summer 2004 shutdown of the groundwater extraction/injection system facilitated a more precise and accurate delineation of the bedrock encasing zone and faults. The incorporation of the Horizontal Flow Barrier (HFB) Package in the current model provided a greater accuracy in both the location and conductance of faults. The HFB Package also allows for much faster computer runs, and a more stable numerical model. Additionally, recovery data allowed for a more precise determination of bedrock storage properties through model calibration.

(2) The flow model was calibrated to three data sets consisting of:

- (a) Water levels measured in June 2004;
- (b) A long-term average data set; and
- (c) Transient data from recovery following shutdown

(3) A good match was attained between measured and simulated values. A Mean Absolute Residual (MAR) of 2.41.ft. was attained during calibration to 212 long-term average target locations. The model also matched prior estimates of groundwater inflow into the model domain, and simulates the general regional flow domain.

(4) The TCE plume produced by the model is a reasonable match to the observed plume, both under current conditions and during development of the plume. The modeled results compare favorably with observed results and the prior model (HEC/Geotrans, 2005).

(5) Modeling Conclusions

(a) Groundwater flow across the site can be conceptualized as consisting of relatively flat gradients located in broad areas between fault zones, where dramatic drops in water levels occur over a very short distance. These fault zones are the controlling hydrologic structures in the model area. The more precise delineation of the bedrock encasing zone, from water level data and use of the HFB package, facilitated a significantly more accurate representation of the flow system.

(b) Calibration to the recovery data were used to analyze the relative influence of parameters on transient water levels. Changes in horizontal hydraulic conductivity primarily affected the total simulated head change over a time interval. Changes in vertical hydraulic conductivity and specific storage primarily affected the initial rebound following shutdown. Changes in specific yield/porosity primarily affected the slope of the recovery curve.

(c) The steady-state and transient calibrations demonstrated the model's ability to replicate changes in water levels resulting from changes in stress on the system. The good match with several independent data sets provides additional validation and reduces the uncertainty of the model. Porosity is important for simulating plume migration. In the past porosity was estimated from tables and calibration of the solute transport model. Calibration to measured recovery provided a physical basis for specific yield and hence porosity values in the bedrock.

(d) The solute transport model was run three years into the future to provide prediction of plume migration. Two methods of representing the current plume configuration (plume initialization) were used. The first method was simply to continue the model using the model calculated present day plume configuration. The second method was to reinitialize the plume based on contouring concentrations measured in monitoring wells in 2005. For both of these configurations the model was run with the source concentrations continued into the future and with the sources removed. The results of these simulations indicate that plume migration will be limited to 300 to 500 ft during the three year period. The results also show that the source area input does not affect the distal portion of the plume; only the area near the sources are affected.

(e) The expanded solute transport sensitivity analysis performed on individual source terms was useful for model calibration and for future plume management decisions. It appears that the Old Industrial Waste Lagoon and Spreading Area were the primary contributors to the main plume extent downgradient of the bedrock block. In addition, the Building 679 source appears to be the primary contributor to the Northeast Boundary Plume.

J. 2007 Groundwater Flow and Transport Model (HEC/Geotrans, 2007)

(1) Calibration of the groundwater flow and solute transport model over the past two years focused on matching groundwater level recovery following the summer 2004 shutdown of the groundwater extraction system. These efforts facilitate a more precise and accurate delineation of the bedrock encasing zone and faults. The incorporation of the Horizontal Flow Barrier Package in the 2006 model provided a greater accuracy in both the location and conductance of faults.

(2) The current flow model was calibrated to long-term water level data starting in 1942. Previous flow models used an assumption of steady-state water levels from 1942 to 1994. This assumption prevented accounting for changes in hydraulic gradients and flow trajectories caused by differential changes in water levels during the period when much of the plume migration took place. Modeling of water level changes during this period assigns the correct driving force to the plume; prior models may have used porosity of distribution coefficient as a calibration factor to adjust plume velocity to obtain a reasonable match to observed concentration data.

(3) The TCE plume produced by the model is a reasonable match to the observed plume, both under current conditions and during the development of the plume. The modeled results compare favorably with observed results and the prior year models.

(4) The accurate simulation of transient groundwater flow conditions from the beginning of plume formation in 1942 to the present provides more realistic simulation of the transient forces that drive plume formation. The transient groundwater flow model simulated the changes in heads and flows during long-term wet and dry periods. Additionally, the model simulated monthly extraction/injection wells for the full length of operation of the pump-and-treat system (1994-2004). The calibrated flow model produced a good match to selected, representative well hydrographs.

(5) As a result of the change to transient flow modeling, the simulated TCE plume initially moved further downgradient than measured. This required a change in effective porosity and sorption coefficient to bring the model back into reasonable calibration. Also, the calibration target of TCE influent concentration (flow weighted average of extraction well concentrations) proved very sensitive to the simulated mass flux applied at the ditches and lagoons. This sensitivity results because the wells located in the bedrock block extract much of the TCE mass and the ditches were a key contributor to contamination within the bedrock block. Identification of calibration targets that are sensitive to model input is important for defining reasonable ranges for the upcoming uncertainty analysis.

(6) The solute transport model was run through 2009 to provide prediction of plume migration in the near future. Two methods of representing the current plume configuration (plume initialization) were used. The first method was simply to continue the model using the model-calculated December 2006 plume configuration. The second method was to reinitialize the plume based on contouring concentrations measured in monitoring wells in October 2006. For both of these configurations the model was run with the source concentrations continued into the future and with the sources removed. The results of these simulations indicate that plume

migration will be limited to approximately 500 ft or less over a three year period. The results also show that the source area input does not affect the distal part of the plume; only the areas near the sources are affected. After completion of a planned model uncertainty analysis, longer-term predictive simulations will be conducted.

K. 2008 Groundwater Flow and Transport Model (HEC/Geotrans, 2008)

(1) The groundwater flow and transport model has evolved over the years with the addition of new data, results of new studies, and the use of more sophisticated modeling methods. This process has improved the understanding of the hydrogeologic system and increased confidence in the predictive capability of the model. For additions to the model in 2008 are particularly noteworthy. These additions are described below.

(a) The first major addition to the model, calibration to long-term transient water level data starting in 1942, assigns the correct driving force to the plume. Prior models, which used and assumption of steady state water levels from 1942 to 1994, may have used porosity or distribution coefficient as a calibration factor to adjust plume velocity to obtain a reasonable match to observed concentration data.

(b) The second addition to the model, the Monte-Carlo uncertainty analysis, providing insight into model sensitivity in addition to its intended purpose of providing guidance on management of site restoration.

(c) The third addition to the model, inclusion of the results of a recent USGS water budget analysis, constrained the limits of certain model parameters and boundary conditions. In addition, the water budget analysis provided a stronger technical basis for the value of model parameters that were previously either assumed or calibrated.

(d) The fourth addition to the model, the new conceptualization of the southern bedrock and alluvium, required adjustments to parameter zonation during model construction and adjustments to their values during calibration. The new conceptualization is believed to more accurately represent site conditions.

(2) Model Conclusions

(a) A key difference between the water budgets derived by the USGS and the 2007 Tooele groundwater model was in the total amount of water flowing through the system. The USGS showed approximately 50 percent less than the model. Using the USGS water budget calculations as a calibration target in the model resulted in decreasing the hydraulic conductivities of aquifer materials and faults. Additional adjustments to parameters that affect plume velocity were required to match historical plume movement and current distribution.

(b) The steady-state calibration produced a good statistical match to long-term average heads and flows. The transient groundwater flow model closely simulated the changes in head and flows during long-term wet and dry periods from 1942-2007. The model also accurately simulated mass extraction from operation of the pump-and-treat system (1994-

2004). In addition, the model simulated the historical evolution of the TCE plume to its current extent. The ability to match observed water levels in wells, mass extracted, and TCE concentrations in wells provides confidence that the model can predict future changes on concentration and plume movement.

(c) The solute transport model was run through 2010 to provide predictions of plume migration in the near future. Two methods of representing the current plume configuration (plume initialization) were used. The first method was simply to continue the model using the model calculated December 2007 plume configuration. The second method was to reinitialize the plume based on contouring concentrations measured in monitoring wells in November 2007. For both of these configurations the model was run with the source concentrations continued into the future and with the sources removed. The results of these simulations indicate that plume migration will be limited to approximately 500 ft or less over a three year period. In general, the 2008 model shows less plume migration over the three year period than prior models. The decrease in plume migration is the result of the decrease in hydraulic conductivity that was required to match the lower flow within the basing suggested by the USGS water budget analysis.

L. 2009 Groundwater Flow and Transport Model (HEC/Geotrans, 2009)

(1) The 2009 modeling study improves on prior analyses by including a revised configuration of the bedrock and associated faulting. Special emphasis was placed on calibration of the evolution and trajectory of the Northeast Boundary (NEB) plume. The simulation and calibration of a long-term (66 year) transient flow field that was introduced in the 2007 modeling study was also used in the present study. The long term transient simulation replicates regional flow patterns that may have affected TCE plume development from initial release to present. The model was also calibrated to steady state condition and water level recovery data from the Non-Operational Test (NOT) of the groundwater extraction/injection system. In addition, an uncertainty analysis that builds on knowledge gained from the study that was conducted in 2008.

(2) Model Conclusions

(a) The steady-state calibration produced a good statistical match to long term average heads and flows. The transient groundwater flow model acceptably simulated the changes in heads and flows during long term wet and dry periods from 1942-2008. The model also accurately simulated mass extraction from operation of the pump and treat system (1994-2004). In addition, the model simulated the historical evolution of the TCE plume to its current extent. The ability to match observed water levels in wells, mass extracted, and TCE concentrations in wells provides some level of confidence that the model can predict future changes in concentration and plume movement. However, all such predictions will be uncertain estimates, and predictive uncertainty will increase substantially after a few years into the future.

(b) The solute transport model was run through 2013 to provide prediction of plume migration in the near future. Two methods of representing the current plume configuration (plume initialization) were used. The first method was simply to continue the model using the model-calculated December 2008 plume configuration. The second method was

to reinitialize the plume based on contouring concentrations measured in monitoring wells in November 2008. For both of these configurations the model was run with the source concentrations continued into the future and with the sources removed. The results of these simulations (Figures 52 through 55) indicate that plume migration will be limited to approximately 500 ft or less over a five-year period. The results also show that the source area input does not affect the distal part of the plume; only the areas near the sources are affected.

(c) As part of the uncertainty analysis, many longer-duration predictive simulations were conducted. These simulations demonstrated the importance of proper representation of the initial (i.e. current-day) concentrations in the predictive model. The predictions made using the kriged plume indicate that the concentrations at the 1-mile buffer boundary are likely to remain below the MCL through 2028. However, these results may be influenced by numerical dispersion.

M. 2010 Groundwater Flow and Transport Model (HEC/Geotrans, 2010)

(1) The most significant revisions in the 2010 modeling study were: 1) a revised conceptualization of the Northern Alluvium and nearby boundary conditions based on additional water level and pumping data; 2) the definition of fault leakance that varies continuously along a fault; and 3) the assimilation of modeled and observed TCE data to produce a more informed initial plume for the prediction of TCE plume. The revised conceptualization of the Northern Alluvium required adjustments to parameter zonation in the northern and northwestern parts of the model. Additionally, the definition of the constant heads along the model boundary in that part of the domain were revised to more closely reflect the perceived vertical gradient observed. The definition of fault leakance along the faults throughout the model domain required the definition of estimates of leakance at various locations along the faults in each model layer and interpolating these point estimates to along the length of the entire fault system. Finally, a revised initial plume was defined for predictive simulations. This revised plume incorporated both TCE measurements and calibrated model estimates, weighting both according to the interpolation error associated with the interpolated TCE plume. In areas of the domain distant from TCE measurements, the aggregate plume would emphasize the model estimate of TCE; at and near locations of TCE concentration measurements, the aggregate plume would rely more heavily upon the actual measurement value.

(2) Model Conclusions

The steady-state calibration produced a good statistical match to 2002 average heads and flows. Moreover, it provided a suitable starting point for the transient flow and solute transport model calibration. The TCE plume created by the calibrated transient model matched well with the observed plume during the development of the plume and at the end of the calibration period. In general, the modeled water levels and TCE concentrations throughout time effectively match those observed in target wells and, at the very least, capture the temporal trends in observed conditions.

A Monte Carlo uncertainty analysis was implemented in running variations on the calibrated flow-transport model to the year 2032. The results of this uncertainty analysis suggest that, though there is some uncertainty in the long term future migration of the TCE plume, there is zero likelihood that the concentration of TCE will exceed the MCL by 2032.

N. 2011 Groundwater Flow and Transport Model (HEC/Geotrans, 2011)

(1) The most significant 2011 revision to the conceptual model was the introduction of two faults in the northern and northwestern alluvium. The purpose of these faults was to more accurately simulate abrupt drops in water levels in these areas of the model domain. The new faults also facilitated the simulation of more realistic flow gradients towards the northern (uppermost) edge of the model grid. The model was first calibrated to steady state conditions in order to provide the automated calibration of the transient model a meaningful and well-informed starting point. The automated calibration process resulted in a 12% reduction in overall model error in matches to transient water levels.

(2) Model Conclusions

As in prior years' model analyses, special emphasis was placed on calibration of the evolution and trajectory of the Northeast Boundary (NEB) plume. The long-term transient simulation replicated regional flow patterns that may have affected TCE plume development from initial release to present. In addition, the error associated with simulating TCE concentrations at wells improved model-wide and also at boundary wells.

An uncertainty analysis that builds on knowledge gained from the study that was conducted in 2009 and 2010 was also included. In this analysis, model parameters were permitted to vary within reasonable bounds of uncertainty; variability in resulting predictions of TCE plume migrations was assessed and reported in a probabilistic framework.

O. 2012 Groundwater Flow and Transport Model (HEC/Geotrans, 2012)

(1) The most significant 2012 revision to the model was the conceptualization of confinement in the northwestern alluvium in order to both accurately simulate downgradient drops in water levels that occur over short distances and effectively simulate pronounced vertical gradients in the northwestern and southern alluvium. The introduction of the confining bed (and corresponding elimination of downgradient faults from the

2011 TEAD model) marked a significant revision in the 2012 TEAD modeling study that accommodates both observed geologic and hydraulic conditions at the study area.

(2) Model Conclusions

The steady-state calibration produced a good statistical match to 2002 average heads and flows. In particular, the steady state flow model accurately simulated water levels and sharp hydraulic gradients in the northern alluvium; achieving accurate matches at these wells was a focus of the 2012 modeling analyses. The transient model calibration process resulted in a 60% reduction in overall model error. This is evident in very good model matches to water levels throughout the model throughout time. In addition, the error associated with simulating TCE concentrations at wells improved model-wide and also at boundary wells, where the greatest reduction improvement in model accuracy occurred through the calibration process.

P. 2013 Groundwater Flow and Transport Model (HEC/Geotrans, 2013)

(1) New data in the present study include 2012-2013 transducer data from wells D-20, D-21, D-22, D-23, D-25. Analysis of transducer data suggested a greater response to seasonal pumping in deeper wells relative to the shallow well D-22. Analysis of these data resulted in a relocation of the confining bed in the northern alluvium that allowed for wells D-20, D-23, D-25 to be located in the deeper aquifer hydraulically connected to the pumping wells, while well D-22 was located in the upper aquifer, above the confining bed. Another significant change to the 2013 model was the alteration of the vertical extent of layers 6-9 to provide an improved calibration to wells C-55, D-25, P-28D, and B-48. The new layer conceptualization provided a more physical basis for layer discretization than was used in previous models. In addition to changes made to the flow model, the characterizations of source location and timing were revised to reflect results of recent and historical remedial investigations at sources areas (i.e. sanitary landfill, Building 615, Building 679).

(2) Model Conclusions

As in prior analyses, the 2013 TEAD flow and transport model was calibrated using an optimization-based procedure. This automated calibration procedure iteratively adjusted model parameters in an effort to reduce the error between observed water level and TCE concentrations and their corresponding simulated values. In addition to these target types, two new categories of calibration targets were incorporated into the 2013 calibration effort: 1) observed head losses between nearby wells, and 2) recent rates of change of concentration observed in individual wells located throughout the main and NEB plumes. The incorporation of these targets was intended to foster a robust calibration and constrain the solution to the model. A robust calibration procedure should identify the flow and transport model parameters that provide the most accurate estimates of water levels and TCE concentrations. As such, the calibration of the 2013 flow and transport model maintained very low model error, as in prior years' analyses.

Q. 2014 Groundwater Flow and Transport Model

The 2014 study introduced improvements to the conceptual model of both groundwater flow. These improvements will be integrated into the 2015 numerical model.

An important recent discovery in understanding site hydrology is the impact of agricultural pumping at the northern part of the model domain on groundwater levels. Continuously recorded data gathered from wells D-20, D-23, and D-25 showed a consistent drawdown of 8-10 ft total that commences with the beginning of pumping in April and ends on September 1. Conversely, a recovery of 8-10 in measured water levels occurs between September 1 and the following April.

A field investigation of agricultural pumping rates was completed in March 2014. This also included a town hall meeting with local farmers and stakeholders. Property owners were identified and average water use was estimated both from irrigation measurements and by crop water requirement. A good correlation was obtained between the two. Additionally, the installation of transducers and continuous data loggers at nine additional locations was completed to provide information on the effect of agricultural pumping on groundwater flow in the northeast plume area.

An initial investigation of the potential recharge to groundwater from the City of Tooele wastewater treatment plant and adjacent golf course was performed. The impetus for this analysis was the April 2013 measured groundwater elevation at well D-21, located adjacent to the golf course, was 4.5 ft higher than the measured water level at well D-17, located up gradient and ½ mile from the golf course. The higher water levels measured at well D-21 relative to D-17 may be indicative of recharge from the wastewater treatment plant area and adjacent golf course. The City of Tooele Public Works treats an average of 2.1 MGD (million gallons per day) of wastewater. Water use estimates for irrigation and evaporation were then subtracted, and an initial estimate of potential recharge to the water table of 0.58 MGD was derived.

R. 2015 Groundwater Flow and Transport Model

The 2015 modeling study introduces improvements to the conceptual models of both groundwater flow and contaminant transport:

- An investigation of agricultural pumping located in the northern model domain was completed. Pumping estimates were based both on measured values in the field and crop type-based estimates of water use. A good correlation between the two was attained;
- The installation of transducers and continuous data loggers at nine additional locations was completed to provide information on the effect of agricultural pumping on groundwater flow in the northeast plume area;

- An initial investigation of the potential recharge from the City of Tooele wastewater treatment plant and adjacent golf course was performed;
- The total number of model layers was increased from 9 to 11. This allowed the upper 5 layers at the northwest boundary of the model to be discretized in a similar manner to the upper 5 layers at the southwest boundary of the model;
- A head-dependent flux boundary was specified along the northern boundary of the model to allow for the simulation of a regional response to localized stresses from agricultural pumping and recharge;
- Improved weighting of calibration targets to emphasize focus on effectively matching conditions along the current plume boundaries; and
- A more robust simulation of TCE source areas to reflect recent remedial impacts and removal of TCE mass.

The simulation and calibration of a long-term (73-year) transient flow field that was introduced in the 2007 modeling study was used in the present study. The long-term transient simulation replicates regional flow patterns that may have affected TCE plume development from initial release to present. As in prior years' model analyses, special emphasis was placed on calibration of the evolution and trajectory of the main and Northeast Boundary (NEB) plumes that emanated from on-site TCE sources. As mentioned above, weights associated with both observed water levels and observed concentration targets at the boundary of the plume were increased relative to prior modeling analyses. Moreover, greater emphasis was placed on observed water level differences between nearby wells and concentration rates of change throughout the plume, which were incorporated as calibration targets in 2013. The model was first calibrated to steady state conditions in order to confirm the validity of the conceptual model and provide the automated calibration of the transient numerical model a meaningful and well-informed starting point. Additionally, an uncertainty analysis that builds on knowledge gained from the study and was conducted in prior analyses (HEC and GeoTrans, 2009, 2010; HEC and Tetra Tech, 2011, 2012, 2013) is also included. In this analysis, model parameters are permitted to vary within reasonable bounds of uncertainty; variability in resulting predictions of TCE plume migrations is assessed and reported in a probabilistic framework

S. 2016 Groundwater Flow and Transport Model

The 2016 modeling study introduces improvements to the conceptual models of both groundwater flow and contaminant transport:

- Improvement to the accuracy of the representation of agricultural pumping located in the northern model domain. Pumping estimates are based both on measured values in the field and water use estimates for specific crops and anecdotal information provided by farmers. A good correlation of these data sources was attained;
- The continued use of transducers and continuous data loggers at nine various monitoring well locations to monitor groundwater levels and provide information on the effect of agricultural pumping on groundwater flow in the northeast plume area;
- An revised representation of the recharge from the City of Tooele wastewater treatment plant and adjacent golf course, predicated upon discussions with personnel from both organizations and a water budget analysis of the treatment plant and golf course;
- The calibration of both a steady state and transient groundwater flow model, upon which the transient groundwater flow and TCE transport model is based. The steady state flow model simulates the equilibrated pre-agricultural pumping conditions of March 2015, and the transient flow model simulates changes to groundwater levels as a result of agricultural pumping and seasonal fluctuations;
- A revised representation of specified head boundary conditions to reflect observed seasonal fluctuations in groundwater levels;
- A revision to the elevation of the bottom of model layer 5;
- Renewed emphasis on key transient flow and transport model targets such as within-well rates of change of concentration, water level changes between adjacent wells, as well as both water levels and TCE concentration at the plume's downgradient edge;
- Constraining of aquifer flow and transport parameters to attain homogeneity;
- A more robust simulation of TCE source areas to reflect recent remedial impacts and removal of TCE mass; and
- Pilot testing of alternative method for assimilating simulated and observed TCE concentration data to define initial conditions for predictive simulations.

The simulation and calibration of a long-term (74-year) transient flow field that was introduced in the 2007 modeling study, and refined annually since then, was used in the present study. The long-term transient simulation replicates regional flow patterns that may have affected TCE

plume development from initial release to present. As in prior years' model analyses, special emphasis was placed on calibration of the evolution and trajectory of the main and Northeast Boundary (NEB) plumes that emanated from on-site TCE sources. Weights associated with both observed water levels and observed concentration targets at the boundary of the plume were revised from prior modeling analyses. Moreover, greater emphasis was placed on observed water level differences between nearby wells and concentration rates of change throughout the plume, which were incorporated as calibration targets in 2013. Transport model calibration efforts focused on optimizing the weighting of calibration targets to produce a simulated TCE plume that both matches observed conditions and migrates in a manner consistent with the TCE transport conceptual model. Multiple calibration efforts were required due to difficulty in matching the downgradient edge of the TCE plume while accurately simulating groundwater flow conditions (discussed in Section 5). The results of these transport model calibration gives new insight into the likely role of biodegradation on the development of the TCE plume at the TEAD-N site.

The groundwater flow model was first calibrated to steady state conditions (March 2015) in order to confirm the validity of the conceptual model and provide the automated calibration of the transient numerical model a meaningful and well-informed starting point. Subsequently, a short-term (6-month) transient flow model of agricultural well pumping was calibrated to associated observed drawdown in nearby monitoring well. The results of these flow model calibrations informed the construction of a long-term transient groundwater flow and TCE transport model that was calibrated to effectively match over 70 years of hydrologic and water quality conditions at the site. Additionally, an uncertainty analysis that builds on knowledge gained from both the current calibration analysis and as well as prior modeling analyses (HEC and GeoTrans, 2009, 2010; HEC and Tetra Tech, 2011, 2012, 2013; HEC & Tetra Tech, 2015) was also conducted in this analysis. In this analysis, model parameters are permitted to vary within reasonable bounds of uncertainty; variability in resulting predictions of TCE plume migrations is assessed and reported in a probabilistic framework.

T. 2017 Groundwater Flow and Transport Model

The 2017 modeling study features improvements to the conceptual models of both groundwater flow and contaminant transport and introduces analyses focused on enhancing the accurate simulation of TCE plume migration at the TEAD-N site. This includes:

- An expanded calibration to agricultural well pumping-based groundwater drawdowns observed in monitoring wells with transducers and continuous data loggers;
- An increase in the number of flow and transport model calibration targets (i.e. groundwater levels, TCE concentrations, water level differences, TCE concentration gradients);
- The introduction of a new calibration target (between-well TCE differences) that added nearly 2,700 data points to the set of calibration targets and endeavored to help improve the simulation of plume movement, particularly at the plume's leading edge;

- Multiple calibrations of the groundwater flow and TCE transport model, with increased emphasis on downgradient monitoring well observations of groundwater levels, TCE concentrations, and associated gradients;
- Evaluation of the kriging-based and ensemble Kalman filter-Based (EKF-Based) data assimilation tools to determine the superior method for predicting TCE concentrations; and
- Analysis of the impact of TCE degradation on plume trends in key wells, using the flow and transport model.

The groundwater flow model was first calibrated to steady state conditions (March 2015) in order to confirm the validity of the conceptual model and provide the automated calibration of the transient numerical model a meaningful and well-informed starting point. Subsequently, a short-term (16-month) transient flow model that incorporated seasonal fluctuations in agricultural pumping and groundwater inflow was calibrated to continuously recorded water levels at 13 monitoring wells. The objective of these calibrations was to form the basis of the transport model and improve understanding of site hydrology. The steady-state conceptual model was significantly changed to facilitate a better match with measured flow gradients in the area at the extent of the NEB plume. Additionally, analysis of seasonal transient data supported the hypothesis that subsurface groundwater inflow can have a significant and fairly quick impact on water levels, especially at SE corner of model domain. This was important in the development of the transient model. Instead of adjusting recharge values, boundary conditions at the edge of the model boundary were adjusted to simulate transient groundwater levels.

The results of these flow model calibrations informed the construction of a long-term transient groundwater flow and TCE transport model that was calibrated to effectively match 75 years of hydrologic and water quality conditions at the site. The long-term transient simulation replicates regional flow patterns that may have affected TCE plume development from initial release to present. Special emphasis was placed on calibration of the evolution and trajectory of the main and Northeast Boundary (NEB) plumes that emanated from on-site TCE sources. Weights associated with both observed flow and transport targets at the boundary of the plume were revised from prior modeling analyses (and iteratively adjusted during the course of this year's analysis). Moreover, by accurately matching these downgradient targets, it is anticipated that the model accurately simulates flow and transport processes in upgradient areas. Three separate calibration efforts were conducted in order to optimize the weighting of calibration targets to produce a simulated TCE plume that both matches observed conditions and migrates in a manner consistent with the TCE transport conceptual model. With each successive calibration, the model's match to conditions along the leading edge of the plume improved. Only results of the final calibration are presented in this modeling report.

Additionally, an uncertainty analysis that builds on knowledge gained from both the current calibration analysis and as well as prior modeling analyses (HEC and GeoTrans, 2009, 2010; HEC and Tetra Tech, 2011, 2012, 2013; HEC & Tetra Tech, 2015, 2016) was also conducted in this analysis. In this analysis, model parameters are permitted to vary within reasonable bounds

of uncertainty; variability in resulting predictions of TCE plume migrations is assessed and reported in a probabilistic framework.

The EKF-based method of data assimilation was tested to help determine how well the EKF-based TCE plume predicts TCE concentrations. In this evaluation, observed and simulated TCE concentrations from late-2009 and early-2010 were assimilated into a single plume using EKF. Then, this plume was simulated forward in time using the 2016 calibrated model (the 2017 model calibration was not yet conducted); simulated concentrations were compared to those observed between 2010 and 2016 at site monitoring wells. The same was executed using the kriging-based method. Comparison of the two sets of simulation results indicates that while both methods simulated 2010 to 2016 TCE concentrations with commensurate accuracy, there are some key differences in the two representations of the TCE plume. The kriging-based plume better simulates initial and early-simulation concentrations, as well as lower magnitude concentrations. Conversely, the error associated with EKF-based plume predictions ultimately decreases over time; and, the EKF method is more accurate than the kriging-based method at simulating elevated concentrations. These results suggest that the kriging-based method may not be completely appropriate for defining TCE concentrations in areas away from monitoring wells. Specifically, the kriging-based method of plume characterization may not lead to the most accurate and/or conservative predictions of TCE breakthrough along management boundaries.

In conclusion, the 2017 model study provided several improvements from past efforts. An improved match between simulated and measured groundwater gradients at the extent of the NEB plume provided for a more accurate conceptualization of the flow system and contaminant transport.

4. Future Modeling Efforts

An abstract of each year's modeling activities shall be included in this permit attachment, not later than June 1 of each year (as specified in Table V-3 of Module V.F.1), in order to provide an overall summary of the modeling program. Specific details on modeling activities can be found in the referenced reports.

(HEC, 1999) U.S. Army Corps of Engineers, Hydrologic Engineering Center, 1998
Hydrogeologic Flow Model and Accompanying Solute Transport Model for Tooele Army Depot,
Utah, January 1999

(HEC, 2000) U.S. Army Corps of Engineers, Hydrologic Engineering Center, 1999
Hydrogeologic Flow Model and Accompanying Solute Transport Model for Tooele Army Depot,
Utah, January 2000

(HEC, 2000a) U.S. Army Corps of Engineers, Hydrologic Engineering Center, 2000
Groundwater Flow Model Recalibration Study

(HEC, 2001/2002) U.S. Army Corps of Engineers, Hydrologic Engineering Center, Tooele Army Depot Groundwater Flow Model, 2001/2002 Recalibration Study, April 2002

(HEC, 2003) U.S. Army Corps of Engineers, Hydrologic Engineering Center, Tooele Army Depot Groundwater Flow and Contaminant Transport Model – 2003, April 2003

(HEC/Geotrans, 2004) Tooele Army Depot Groundwater Flow and Contaminant Transport Model (2004), April 2004

(HEC/Geotrans, 2004a) Addendum to the Tooele Army Depot Flow and Contaminant Transport Model (2004) TCE Transport Sensitivity Analysis – May 26, 2004

(HEC/Geotrans, 2005) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, July 2005

(HEC/Geotrans, 2006) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, July 2006

(HEC/Geotrans, 2007) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, July 2007

(HEC/Geotrans, 2008) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2008

(HEC/Geotrans, 2009) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, October 2009

(HEC/Geotrans, 2010) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2010

(HEC/Geotrans, 2011) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2011

(HEC/Geotrans, 2012) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2012

(HEC/Geotrans, 2013) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2013

(HEC/Geotrans, 2014) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2014

(HEC/Geotrans, 2015) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2015

(HEC/Geotrans, 2016) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2016

(HEC/Geotrans, 2017) Tooele Army Depot Groundwater Flow and Contaminant Transport Model, September 2017