

**Utah Division of Water Quality**

**Statement of Basis**

**ADDENDUM**

**Wasteload Analysis and Antidegradation Level I Review - PRELIMINARY**

**Date:** February 28, 2017 

**Prepared by:** Dave Wham  
Standards and Technical Services

**Facility:** Pacificorp Deer Creek Mine; Discharge 003  
UPDES No. UT0023604

**Receiving water:** Huntington Creek (1C, 2B, 3A, 4)

This addendum summarizes the wasteload analysis that was performed to determine water quality based effluent limits (WQBEL) for this discharge. Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses (UAC R317-2-8). Projected concentrations are compared to numeric water quality standards to determine acceptability. The numeric criteria in this wasteload analysis may be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

Discharge

UPDES Discharge Point 003, Mine water discharge with an estimated mean monthly discharge of 0.72 MGD (1.12 cfs).

Receiving Water

Huntington Creek. Per UAC R317-2-13.1(b), the designated beneficial uses of Huntington Creek and tributaries from Highway 10 crossing to USFS boundary are 1C, 2B, 3A, 4.

- *Class 1C – Protected for domestic purposes with prior treatment by treatment processes as required by the Utah Division of Drinking Water.*
- *Class 2B - Protected for infrequent primary contact recreation. Also protected for secondary contact recreation where there is a low likelihood of ingestion of water or a low degree of bodily contact with the water. Examples include, but are not limited to, wading, hunting, and fishing.*
- *Class 3A - Protected for cold water species of game fish and other cold water aquatic life, including the necessary aquatic organisms in their food chain..*
- *Class 4 - Protected for agricultural uses including irrigation of crops and stock watering.*

Typically, the critical flow for the wasteload analysis is considered the lowest stream flow for seven consecutive days with a ten year return frequency (7Q10). Due to a lack of flow records, the 20th percentile of available flow measurements was calculated for the period of record to approximate the 7Q10 low flow condition. Flow data for the receiving water was obtained from Emery Water Conservancy District for their site *Huntington River below Power Plant* from the period 2012-2017. This station is below the Power Plant diversion but above other significant diversions like Huntington North Reservoir. Ambient water quality was characterized using data from DWQ station #4930530, Huntington Creek above UP&L Diversion from the period 2007-2013.

The critical low flow condition for discharges 003 is 12.1 cfs.

#### TMDL

According to the Utah's 2016 303(d) Water Quality Assessment, the assessment unit for this section of Huntington Creek, Huntington Creek and tributaries from Highway 10 crossing to USFS boundary (UT14060009-004) was listed as impaired for pH (Classes 1C, 2B, 3A, 4), dissolved oxygen (Class 3A), temperature (Class 3A) and total dissolved solids (Class 4).

Review of the listing data show that the temperature impairment was based on results from stations located in Bear Creek, a tributary to Huntington Creek located upstream from the proposed discharge. As a result, the proposed discharge cannot cause or contribute to that impairment.

Data from two monitoring stations above and below Deer Creek on Huntington Creek show impairments for pH and dissolved oxygen (DO). As a result, the proposed discharge must meet applicable Water Quality Standards (WQS) at end of pipe for these constituents (6.5 mg/l DO, and pH 6.5-9.0 pH).

Review of the listing data show that the total dissolved solids (TDS) impairment was based on results from the Huntington Creek at U10 crossing monitoring station. In order to protect downstream uses, and to avoid causing or contributing to that impairment, effluent limits for TDS should be set at the WQS of 1200 mg/l TDS.

#### Mixing Zone

The maximum allowable mixing zone is 15 minutes of travel time for acute conditions, not to exceed 50% of stream width, and 2,500 feet for chronic conditions, per UAC R317-2-5. Water quality standards must be met at the end of the mixing zone.

Mixing zone modeling showed 100 % mixing within 15 minutes travel time, and acute limits defaulted to 50% of the seasonal critical low flow.

#### Parameters of Concern

The potential parameters of concern identified for the discharge/receiving water were temperature, pH, dissolved oxygen, TDS, and iron, as determined in consultation with the

UPDES Permit Writer.

#### WET Limits

The percent of effluent in the receiving water in a fully mixed condition, and acute and chronic dilution in a not fully mixed condition are calculated in the WLA in order to generate WET limits. The LC<sub>50</sub> (lethal concentration, 50%) percent effluent for acute toxicity and the IC<sub>25</sub> (inhibition concentration, 25%) percent effluent for chronic toxicity, as determined by the WET test, needs to be below the WET limits, as determined by the WLA.

LC50 WET Limits for Outfall 003 should be based on 61.4% effluent.

IC25 WET limits for Outfalls 003 should be based on 8.4% effluent.

#### Wasteload Allocation Methods

Effluent limits were determined for conservative constituents using a simple mass balance mixing analysis (UDWQ 2012). The mass balance analysis is summarized in the Wasteload Addendums.

The water quality standard for chronic ammonia toxicity is dependent on temperature and pH, and the water quality standard for acute ammonia toxicity is dependent on pH. The AMMTOX Model developed by University of Colorado and adapted by Utah DWQ and EPA Region VIII was used to determine ammonia effluent limits (Lewis et al. 2002). The analysis is summarized in the Wasteload Addendum.

Models and supporting documentation are available for review upon request.

#### Antidegradation Level I Review

The objective of the Level I ADR is to ensure the protection of existing uses, defined as the beneficial uses attained in the receiving water on or after November 28, 1975. No evidence is known that the existing uses deviate from the designated beneficial uses for the receiving water. Therefore, the beneficial uses will be protected if the discharge remains below the WQBELs presented in this wasteload.

An amended Level II Antidegradation Review (ADR) is required for this facility. The receiving stream for the proposed discharge is a Class 1C drinking water source.

#### Documents:

WLA Document: *DeerCk\_003\_WLADoc\_2-27-17.docx*

Wasteload Analysis and Addendums: *DeerCk\_003\_WLA\_2-27-17.xlsm*

#### References:

Emery County Water Conservancy District. <http://www.ewcd.org/canals/huntington-drainage/>  
Utah Division of Water Quality. 2012. *Utah Wasteload Analysis Procedures Version 1.0.*

## WASTELOAD ANALYSIS [WLA] Addendum: Statement of Basis SUMMARY

**Discharging Facility:** Deer Creek 003 Discharge

UPDES No: UT-0023604  
Current Flow: 0.72 MGD Design Flow  
Design Flow 0.72 MGD

**Receiving Water:** Huntington Creek

Stream Classification: 1C, 2B, 3A, 4  
Stream Flows [cfs]:  
12.10 Summer (July-Sept) 20th Percentile  
12.10 Fall (Oct-Dec) 20th Percentile  
12.10 Winter (Jan-Mar) 20th Percentile  
12.10 Spring (Apr-June) 20th Percentile  
50.0 Average  
Stream TDS Values:  
213.0 Summer (July-Sept) Average  
265.0 Fall (Oct-Dec) Average  
307.0 Winter (Jan-Mar) Average  
230.0 Spring (Apr-June) Average

**Effluent Limits:**

Flow, MGD: 0.72 MGD Design Flow  
BOD, mg/l: 25.0 Summer 5.0 Indicator  
Dissolved Oxygen, mg/l: 6.5 Summer 6.5 30 Day Average  
TNH<sub>3</sub>, Chronic, mg/l: 16.2 Summer Varies Function of pH and Temperature  
TDS, mg/l: 11922.1 Summer 1200.0

**WQ Standard:**

**Modeling Parameters:**

Acute River Width: 50.0%  
Chronic River Width: 100.0%

**Level 1 Antidegradation Level Completed: Amended Level II Review required.**

Date: 2/27/2017

Permit Writer:

WLA by:

WQM Sec. Approval:

TMDL Sec. Approval:



3/30/17

**Utah Division of Water Quality  
Salt Lake City, Utah**

**WASTELOAD ANALYSIS [WLA]  
Addendum: Statement of Basis**

<b>27-Feb-17</b>
<b>4:00 PM</b>

**Facilities:** Deer Creek 003 Discharge  
**Discharging to:** Huntington Creek

**UPDES No: UT-0023604**

**I. Introduction**

Wasteload analyses are performed to determine point source effluent limitations necessary to maintain designated beneficial uses by evaluating projected effects of discharge concentrations on in-stream water quality. The wasteload analysis also takes into account downstream designated uses [R317-2-8, UAC]. Projected concentrations are compared to numeric water quality standards to determine acceptability. The anti-degradation policy and procedures are also considered. The primary in-stream parameters of concern may include metals (as a function of hardness), total dissolved solids (TDS), total residual chlorine (TRC), un-ionized ammonia (as a function of pH and temperature, measured and evaluated in terms of total ammonia), and dissolved oxygen.

Mathematical water quality modeling is employed to determine stream quality response to point source discharges. Models aid in the effort of anticipating stream quality at future effluent flows at critical environmental conditions (e.g., low stream flow, high temperature, high pH, etc).

The numeric criteria in this wasteload analysis may always be modified by narrative criteria and other conditions determined by staff of the Division of Water Quality.

**II. Receiving Water and Stream Classification**

Huntington Creek :	1C, 2B, 3A, 4
Antidegradation Review:	Level I review completed. Amended Level II review required.

**III. Numeric Stream Standards for Protection of Aquatic Wildlife**

Total Ammonia (TNH3)	Varies as a function of Temperature and pH Rebound. See Water Quality Standards
Chronic Total Residual Chlorine (TRC)	0.011 mg/l (4 Day Average) 0.019 mg/l (1 Hour Average)
Chronic Dissolved Oxygen (DO)	6.50 mg/l (30 Day Average) 5.00 mg/l (7Day Average) 4.00 mg/l (1 Day Average)
Maximum Total Dissolved Solids	1200.0 mg/l

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Acute and Chronic Heavy Metals (Dissolved)**

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aluminum	87.00 ug/l**	0.523 lbs/day	750.00	ug/l	4.511 lbs/day
Arsenic	190.00 ug/l	1.143 lbs/day	340.00	ug/l	2.045 lbs/day
Cadmium	0.52 ug/l	0.003 lbs/day	5.25	ug/l	0.032 lbs/day
Chromium III	178.07 ug/l	1.071 lbs/day	3725.58	ug/l	22.410 lbs/day
Chromium VI	11.00 ug/l	0.066 lbs/day	16.00	ug/l	0.096 lbs/day
Copper	19.89 ug/l	0.120 lbs/day	32.26	ug/l	0.194 lbs/day
Iron			1000.00	ug/l	6.015 lbs/day
Lead	9.83 ug/l	0.059 lbs/day	252.25	ug/l	1.517 lbs/day
Mercury	0.0120 ug/l	0.000 lbs/day	2.40	ug/l	0.014 lbs/day
Nickel	110.39 ug/l	0.664 lbs/day	992.91	ug/l	5.973 lbs/day
Selenium	4.60 ug/l	0.028 lbs/day	20.00	ug/l	0.120 lbs/day
Silver	N/A ug/l	N/A lbs/day	17.38	ug/l	0.105 lbs/day
Zinc	253.86 ug/l	1.527 lbs/day	253.86	ug/l	1.527 lbs/day

\* Allowed below discharge

\*\*Chronic Aluminum standard applies only to waters with a pH < 7.0 and a Hardness < 50 mg/l as CaCO<sub>3</sub>

Metals Standards Based upon a Hardness of 242.57 mg/l as CaCO<sub>3</sub>

**Organics [Pesticides]**

Parameter	4 Day Average (Chronic) Standard		1 Hour Average (Acute) Standard		
	Concentration	Load*	Concentration		Load*
Aldrin			1.500	ug/l	0.009 lbs/day
Chlordane	0.004 ug/l	0.306 lbs/day	1.200	ug/l	0.007 lbs/day
DDT, DDE	0.001 ug/l	0.071 lbs/day	0.550	ug/l	0.003 lbs/day
Dieldrin	0.002 ug/l	0.135 lbs/day	1.250	ug/l	0.008 lbs/day
Endosulfan	0.056 ug/l	3.988 lbs/day	0.110	ug/l	0.001 lbs/day
Endrin	0.002 ug/l	0.164 lbs/day	0.090	ug/l	0.001 lbs/day
Guthion			0.010	ug/l	0.000 lbs/day
Heptachlor	0.004 ug/l	0.271 lbs/day	0.260	ug/l	0.002 lbs/day
Lindane	0.080 ug/l	5.698 lbs/day	1.000	ug/l	0.006 lbs/day
Methoxychlor			0.030	ug/l	0.000 lbs/day
Mirex			0.010	ug/l	0.000 lbs/day
Parathion			0.040	ug/l	0.000 lbs/day
PCB's	0.014 ug/l	0.997 lbs/day	2.000	ug/l	0.012 lbs/day
Pentachlorophenol	13.00 ug/l	925.894 lbs/day	20.000	ug/l	0.120 lbs/day
Toxephene	0.0002 ug/l	0.014 lbs/day	0.7300	ug/l	0.004 lbs/day

**Utah Division of Water Quality  
Salt Lake City, Utah**

**IV. Numeric Stream Standards for Protection of Agriculture**

<b>4 Day Average (Chronic) Standard</b>		<b>1 Hour Average (Acute) Standard</b>	
	<b>Concentration</b>	<b>Concentration</b>	<b>Load*</b>
Arsenic		100.0 ug/l	lbs/day
Boron		750.0 ug/l	2.26 lbs/day
Cadmium		10.0 ug/l	0.03 lbs/day
Chromium		100.0 ug/l	lbs/day
Copper		200.0 ug/l	lbs/day
Lead		100.0 ug/l	lbs/day
Selenium		50.0 ug/l	lbs/day
TDS, Summer		1200.0 mg/l	3.61 tons/day

**V. Numeric Stream Standards for Protection of Human Health (Class 1C Waters)**

<b>4 Day Average (Chronic) Standard</b>		<b>1 Hour Average (Acute) Standard</b>	
<b>Metals</b>	<b>Concentration</b>	<b>Concentration</b>	<b>Load*</b>
Arsenic		50.0 ug/l	3.561 lbs/day
Barium		1000.0 ug/l	71.223 lbs/day
Cadmium		10.0 ug/l	0.712 lbs/day
Chromium		50.0 ug/l	3.561 lbs/day
Lead		50.0 ug/l	3.561 lbs/day
Mercury		2.0 ug/l	0.142 lbs/day
Selenium		10.0 ug/l	0.712 lbs/day
Silver		50.0 ug/l	3.561 lbs/day
Fluoride (3)		1.4 ug/l	0.100 lbs/day
to		2.4 ug/l	0.171 lbs/day
Nitrates as N		10.0 ug/l	0.712 lbs/day

**Chlorophenoxy Herbicides**

2,4-D	100.0 ug/l	7.122 lbs/day
2,4,5-TP	10.0 ug/l	0.712 lbs/day
Endrin	0.2 ug/l	0.014 lbs/day
ocyclohexane (Lindane)	4.0 ug/l	0.285 lbs/day
Methoxychlor	100.0 ug/l	7.122 lbs/day
Toxaphene	5.0 ug/l	0.356 lbs/day

**VI. Numeric Stream Standards the Protection of Human Health from Water & Fish Consumption [Toxics]**

Maximum Conc., ug/l - Acute Standards				
	Class 1C		Class 3A, 3B	
Toxic Organics	[2 Liters/Day for 70 Kg Person over 70 Yr.]		[6.5 g for 70 Kg Person over 70 Yr.]	
Acenaphthene	1200.00 ug/l	85.47 lbs/day	2700.0 ug/l	192.30 lbs/day
Acrolein	320.00 ug/l	22.79 lbs/day	780.0 ug/l	55.55 lbs/day
Acrylonitrile	0.06 ug/l	0.00 lbs/day	0.7 ug/l	0.05 lbs/day
Benzene	1.20 ug/l	0.09 lbs/day	71.0 ug/l	5.06 lbs/day
Benzidine	0.00012 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Carbon tetrachloride	0.25 ug/l	0.02 lbs/day	4.4 ug/l	0.31 lbs/day
Chlorobenzene	680.00 ug/l	48.43 lbs/day	21000.0 ug/l	1495.67 lbs/day
1,2,4-Trichlorobenzene				
Hexachlorobenzene	0.00075 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Dichloroethane	0.38 ug/l	0.03 lbs/day	99.0 ug/l	7.05 lbs/day

**Utah Division of Water Quality  
Salt Lake City, Utah**

1,1,1-Trichloroethane				
Hexachloroethane	1.90 ug/l	0.14 lbs/day	8.9 ug/l	0.63 lbs/day
1,1-Dichloroethane				
1,1,2-Trichloroethane	0.61 ug/l	0.04 lbs/day	42.0 ug/l	2.99 lbs/day
1,1,2,2-Tetrachloroethane	0.17 ug/l	0.01 lbs/day	11.0 ug/l	0.78 lbs/day
Chloroethane			0.0 ug/l	0.00 lbs/day
Bis(2-chloroethyl) ether	0.03 ug/l	0.00 lbs/day	1.4 ug/l	0.10 lbs/day
2-Chloroethyl vinyl ether	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
2-Chloronaphthalene	1700.00 ug/l	121.08 lbs/day	4300.0 ug/l	306.26 lbs/day
2,4,6-Trichlorophenol	2.10 ug/l	0.15 lbs/day	6.5 ug/l	0.46 lbs/day
p-Chloro-m-cresol			0.0 ug/l	0.00 lbs/day
Chloroform (HM)	5.70 ug/l	0.41 lbs/day	470.0 ug/l	33.47 lbs/day
2-Chlorophenol	120.00 ug/l	8.55 lbs/day	400.0 ug/l	28.49 lbs/day
1,2-Dichlorobenzene	2700.00 ug/l	192.30 lbs/day	17000.0 ug/l	1210.78 lbs/day
1,3-Dichlorobenzene	400.00 ug/l	28.49 lbs/day	2600.0 ug/l	185.18 lbs/day
1,4-Dichlorobenzene	400.00 ug/l	28.49 lbs/day	2600.0 ug/l	185.18 lbs/day
3,3'-Dichlorobenzidine	0.04 ug/l	0.00 lbs/day	0.1 ug/l	0.01 lbs/day
1,1-Dichloroethylene	0.06 ug/l	0.00 lbs/day	3.2 ug/l	0.23 lbs/day
1,2-trans-Dichloroethylene	700.00 ug/l	49.86 lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dichlorophenol	93.00 ug/l	6.62 lbs/day	790.0 ug/l	56.27 lbs/day
1,2-Dichloropropane	0.52 ug/l	0.04 lbs/day	39.0 ug/l	2.78 lbs/day
1,3-Dichloropropylene	10.00 ug/l	0.71 lbs/day	1700.0 ug/l	121.08 lbs/day
2,4-Dimethylphenol	540.00 ug/l	38.46 lbs/day	2300.0 ug/l	163.81 lbs/day
2,4-Dinitrotoluene	0.11 ug/l	0.01 lbs/day	9.1 ug/l	0.65 lbs/day
2,6-Dinitrotoluene	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
1,2-Diphenylhydrazine	0.04 ug/l	0.00 lbs/day	0.5 ug/l	0.04 lbs/day
Ethylbenzene	3100.00 ug/l	220.79 lbs/day	29000.0 ug/l	2065.46 lbs/day
Fluoranthene	300.00 ug/l	21.37 lbs/day	370.0 ug/l	26.35 lbs/day
4-Chlorophenyl phenyl ether				
4-Bromophenyl phenyl ether				
Bis(2-chloroisopropyl) ether	1400.00 ug/l	99.71 lbs/day	170000.0 ug/l	12107.84 lbs/day
Bis(2-chloroethoxy) methane	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Methylene chloride (HM)	4.70 ug/l	0.33 lbs/day	1600.0 ug/l	113.96 lbs/day
Methyl chloride (HM)	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Methyl bromide (HM)	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Bromoform (HM)	4.30 ug/l	0.31 lbs/day	360.0 ug/l	25.64 lbs/day
Dichlorobromomethane	0.27 ug/l	0.02 lbs/day	22.0 ug/l	1.57 lbs/day
Chlorodibromomethane	0.41 ug/l	0.03 lbs/day	34.0 ug/l	2.42 lbs/day
Hexachlorobutadiene(c)	0.44 ug/l	0.03 lbs/day	50.0 ug/l	3.56 lbs/day
Hexachlorocyclopentadiene	240.00 ug/l	17.09 lbs/day	17000.0 ug/l	1210.78 lbs/day
Isophorone	8.40 ug/l	0.60 lbs/day	600.0 ug/l	42.73 lbs/day
Naphthalene				
Nitrobenzene	17.00 ug/l	1.21 lbs/day	1900.0 ug/l	135.32 lbs/day
2-Nitrophenol	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
4-Nitrophenol	0.00 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
2,4-Dinitrophenol	70.00 ug/l	4.99 lbs/day	14000.0 ug/l	997.12 lbs/day
4,6-Dinitro-o-cresol	13.00 ug/l	0.93 lbs/day	765.0 ug/l	54.49 lbs/day
N-Nitrosodimethylamine	0.00069 ug/l	0.00 lbs/day	8.1 ug/l	0.58 lbs/day
N-Nitrosodiphenylamine	5.00 ug/l	0.36 lbs/day	16.0 ug/l	1.14 lbs/day
N-Nitrosodi-n-propylamine	0.01 ug/l	0.00 lbs/day	1.4 ug/l	0.10 lbs/day
Pentachlorophenol	0.28 ug/l	0.02 lbs/day	8.2 ug/l	0.58 lbs/day



**Utah Division of Water Quality**  
**Salt Lake City, Utah**

Phenol	2.10E+04 ug/l	1.50E+03 lbs/day	4.6E+06 ug/l	3.28E+05 lbs/day
Bis(2-ethylhexyl)phthala	1.80 ug/l	0.13 lbs/day	5.9 ug/l	0.42 lbs/day
Butyl benzyl phthalate	3000.00 ug/l	213.67 lbs/day	5200.0 ug/l	370.36 lbs/day
Di-n-butyl phthalate	2700.00 ug/l	192.30 lbs/day	12000.0 ug/l	854.67 lbs/day
Di-n-octyl phthlate				
Diethyl phthalate	23000.00 ug/l	1638.12 lbs/day	120000.0 ug/l	8546.71 lbs/day
Dimethyl phthlate	3.13E+05 ug/l	2.23E+04 lbs/day	2.9E+06 ug/l	2.07E+05 lbs/day
Benzo(a)anthracene (P/	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(a)pyrene (PAH)	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(b)fluoranthene (F	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Benzo(k)fluoranthene (F	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Chrysene (PAH)	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Acenaphthylene (PAH)				
Anthracene (PAH)	9600.00 ug/l	683.74 lbs/day	0.0 ug/l	0.00 lbs/day
Dibenzo(a,h)anthracene	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Indeno(1,2,3-cd)pyrene	0.0028 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Pyrene (PAH)	960.00 ug/l	68.37 lbs/day	11000.0 ug/l	783.45 lbs/day
Tetrachloroethylene	0.80 ug/l	0.06 lbs/day	8.9 ug/l	0.63 lbs/day
Toluene	6800.00 ug/l	484.31 lbs/day	200000 ug/l	14244.52 lbs/day
Trichloroethylene	2.70 ug/l	0.19 lbs/day	81.0 ug/l	5.77 lbs/day
Vinyl chloride	2.00 ug/l	0.14 lbs/day	525.0 ug/l	37.39 lbs/day
			0.0	0.00 lbs/day
<b>Pesticides</b>			0.0	0.00 lbs/day
Aldrin	0.0001 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Dieldrin	0.0001 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Chlordane	0.0006 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDT	0.0006 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDE	0.0006 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
4,4'-DDD	0.0008 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
alpha-Endosulfan	0.9300 ug/l	0.07 lbs/day	2.0 ug/l	0.14 lbs/day
beta-Endosulfan	0.9300 ug/l	0.07 lbs/day	2.0 ug/l	0.14 lbs/day
Endosulfan sulfate	0.9300 ug/l	0.07 lbs/day	2.0 ug/l	0.14 lbs/day
Endrin	0.7600 ug/l	0.05 lbs/day	0.8 ug/l	0.06 lbs/day
Endrin aldehyde	0.7600 ug/l	0.05 lbs/day	0.8 ug/l	0.06 lbs/day
Heptachlor	0.0002 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
Heptachlor epoxide				
<b>PCB's</b>				
PCB 1242 (Arochlor 124	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1254 (Arochlor 125	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1221 (Arochlor 122	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1232 (Arochlor 123	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1248 (Arochlor 124	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1260 (Arochlor 126	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
PCB-1016 (Arochlor 101	0.000044 ug/l	0.00 lbs/day	0.0 ug/l	0.00 lbs/day
<b>Pesticide</b>				
Toxaphene	0.000750 ug/l	0.00	0.0 ug/l	0.00 lbs/day
<b>Dioxin</b>				
Dioxin (2,3,7,8-TCDD)	1.30E-08 ug/l	0.00 lbs/day	1.40E-08	0.00

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Metals**

Antimony	14.0 ug/l	1.00 lbs/day		
Arsenic	50.0 ug/l	3.56 lbs/day	4300.00 ug/l	306.26 lbs/day
Asbestos	7.00E+06 ug/l	4.99E+05 lbs/day		
Beryllium				
Cadmium				
Chromium (III)				
Chromium (VI)				
Copper				
Cyanide	1.30E+03 ug/l	92.59 lbs/day	2.2E+05 ug/l	15668.97 lbs/day
Lead	700.0 ug/l	49.86 lbs/day		
Mercury			0.15 ug/l	0.01 lbs/day
Nickel			4600.00 ug/l	327.62 lbs/day
Selenium	0.1 ug/l	0.01 lbs/day		
Silver	610.0 ug/l	43.45 lbs/day		
Thallium			6.30 ug/l	0.45 lbs/day
Zinc				

**There are additional standards that apply to this receiving water, but were not considered in this modeling/waste load allocation analysis.**

## **VII. Mathematical Modeling of Stream Quality**

Model configuration was accomplished utilizing standard modeling procedures. Data points were plotted and coefficients adjusted as required to match observed data as closely as possible.

The modeling approach used in this analysis included one or a combination of the following models.

(1) The Utah River Model, Utah Division of Water Quality, 1992. Based upon STREAMDO IV (Region VIII) and Supplemental Ammonia Toxicity Models; EPA Region VIII, Sept. 1990 and QUAL2E (EPA, Athens, GA).

(2) Utah Ammonia/Chlorine Model, Utah Division of Water Quality, 1992.

(3) AMMTOX Model, University of Colorado, Center of Limnology, and EPA Region 8

(4) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al.  
Harper Collins Publisher, Inc. 1987, pp. 644.

Coefficients used in the model were based, in part, upon the following references:

(1) Rates, Constants, and Kinetics Formulations in Surface Water Quality Modeling. Environmental Research Laboratory, Office of Research and Development, U.S. Environmental Protection Agency, Athens Georgia. EPA/600/3-85/040 June 1985.

**Utah Division of Water Quality  
Salt Lake City, Utah**

(2) Principles of Surface Water Quality Modeling and Control. Robert V. Thomann, et.al.  
Harper Collins Publisher, Inc. 1987, pp. 644.

### VIII. Modeling Information

The required information for the model may include the following information for both the upstream conditions at low flow and the effluent conditions:

Flow, Q, (cfs or MGD)	D.O. mg/l
Temperature, Deg. C.	Total Residual Chlorine (TRC), mg/l
pH	Total NH3-N, mg/l
BOD5, mg/l	Total Dissolved Solids (TDS), mg/l
Metals, ug/l	Toxic Organics of Concern, ug/l

### Other Conditions

In addition to the upstream and effluent conditions, the models require a variety of physical and biological coefficients and other technical information. In the process of actually establishing the permit limits for an effluent, values are used based upon the available data, model calibration, literature values, site visits and best professional judgement.

### Model Inputs

The following is upstream and discharge information that was utilized as inputs for the analysis. Dry washes are considered to have an upstream flow equal to the flow of the discharge.

### Current Upstream Information

	Stream Critical Low								
	Flow	Temp.	pH	T-NH3	BOD5	DO	TRC	TDS	
	cfs	Deg. C		mg/l as N	mg/l	mg/l	mg/l	mg/l	
Summer (Irrig. Season)	12.10	12.0	8.5	0.01	0.05	7.64	0.00	213.0	
Fall	12.10	2.1	8.4	0.01	0.05	-----	0.00	265.0	
Winter	12.10	1.0	8.3	0.01	0.05	-----	0.00	307.0	
Spring	12.10	7.3	8.4	0.01	0.05	-----	0.00	230.0	
Dissolved	Al	As	Cd	CrIII	CrVI	Copper	Fe	Pb	
Metals	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l	
All Seasons	13.67	0.50	0.06	1.77	3.975*	0.95	15.2	0.35	
Dissolved	Hg	Ni	Se	Ag	Zn	Boron			
Metals	ug/l	ug/l	ug/l	ug/l	ug/l	ug/l			
All Seasons	0.0000	2.50	0.92	0.25	7.12	20.1			* ~80% MDL

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Projected Discharge Information**

Season	Flow, MGD	Temp.	TDS mg/l	TDS tons/day
Summer	0.72000	13.9	542.00	1.62697
Fall	0.72000	13.9		
Winter	0.72000	13.9		
Spring	0.72000	13.9		

All model numerical inputs, intermediate calculations, outputs and graphs are available for discussion, inspection and copy at the Division of Water Quality.

**IX. Effluent Limitations**

Current State water quality standards are required to be met under a variety of conditions including in-stream flows targeted to the 7-day, 10-year low flow (R317-2-9).

Other conditions used in the modeling effort coincide with the environmental conditions expected at low stream flows.

**Effluent Limitation for Flow based upon Water Quality Standards**

In-stream criteria of downstream segments will be met with an effluent flow maximum value as follows:

Season	Daily Average	
Summer	0.720 MGD	1.114 cfs
Fall	0.720 MGD	1.114 cfs
Winter	0.720 MGD	1.114 cfs
Spring	0.720 MGD	1.114 cfs

**Flow Requirement or Loading Requirement**

The calculations in this wasteload analysis utilize the maximum effluent discharge flow of 0.72 MGD. If the discharger is allowed to have a flow greater than 0.72 MGD during 7Q10 conditions, and effluent limit concentrations as indicated, then water quality standards will be violated. In order to prevent this from occurring, the permit writers must include the discharge flow limitation as indicated above; or, include loading effluent limits in the permit.

**Effluent Limitation for Whole Effluent Toxicity (WET) based upon WET Policy**

Effluent Toxicity will not occur in downstream segments if the values below are met.

WET Requirements	LC50 >	61.4% Effluent	[Acute]
	IC25 >	8.4% Effluent	[Chronic]

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Effluent Limitation for Biological Oxygen Demand (BOD) based upon Water Quality Standards or Regulations**

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent BOD limitation as follows:

Season	Concentration	
Summer	25.0 mg/l as BOD5	150.1 lbs/day
Fall	25.0 mg/l as BOD5	150.1 lbs/day
Winter	25.0 mg/l as BOD5	150.1 lbs/day
Spring	25.0 mg/l as BOD5	150.1 lbs/day

**Effluent Limitation for Dissolved Oxygen (DO) based upon Water Quality Standards**

In-stream criteria of downstream segments for Dissolved Oxygen will be met with an effluent D.O. limitation as follows:

Season	Concentration
Summer	6.50
Fall	6.50
Winter	6.50
Spring	6.50

**Effluent Limitation for Total Ammonia based upon Water Quality Standards**

In-stream criteria of downstream segments for Total Ammonia will be met with an effluent limitation (expressed as Total Ammonia as N) as follows:

Season		Concentration	Load
Summer	4 Day Avg. - Chronic	16.2 mg/l as N	97.1 lbs/day
	1 Hour Avg. - Acute	25.5 mg/l as N	153.2 lbs/day
Fall	4 Day Avg. - Chronic	18.2 mg/l as N	109.0 lbs/day
	1 Hour Avg. - Acute	25.0 mg/l as N	150.3 lbs/day
Winter	4 Day Avg. - Chronic	19.9 mg/l as N	119.2 lbs/day
	1 Hour Avg. - Acute	28.7 mg/l as N	172.2 lbs/day
Spring	4 Day Avg. - Chronic	17.2 mg/l as N	103.2 lbs/day
	1 Hour Avg. - Acute	25.0 mg/l as N	150.3 lbs/day

Acute limit calculated with an Acute Zone of Initial Dilution (ZID) to be equal to 50. %.

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Effluent Limitation for Total Residual Chlorine based upon Water Quality Standards**

In-stream criteria of downstream segments for Total Residual Chlorine will be met with an effluent limitation as follows:

Season		Concentration		Load	
Summer	4 Day Avg. - Chronic	0.119	mg/l	0.72	lbs/day
	1 Hour Avg. - Acute	0.117	mg/l	0.70	lbs/day
Fall	4 Day Avg. - Chronic	0.119	mg/l	0.72	lbs/day
	1 Hour Avg. - Acute	0.117	mg/l	0.70	lbs/day
Winter	4 Day Avg. - Chronic	0.119	mg/l	0.72	lbs/day
	1 Hour Avg. - Acute	0.117	mg/l	0.70	lbs/day
Spring	4 Day Avg. - Chronic	0.119	mg/l	0.00	lbs/day
	1 Hour Avg. - Acute	0.117	mg/l	0.00	lbs/day

**Effluent Limitations for Total Dissolved Solids based upon Water Quality Standards**

Season		Concentration		Load	
Summer	Maximum, Acute	11922.1	mg/l	35.79	tons/day
Fall	Maximum, Acute	11357.2	mg/l	34.09	tons/day
Winter	Maximum, Acute	10900.9	mg/l	32.72	tons/day
Spring	4 Day Avg. - Chronic	11737.4	mg/l	35.23	tons/day

Colorado Salinity Forum Limits      Determined by Permitting Section

**Effluent Limitations for Total Recoverable Metals based upon  
Water Quality Standards**

In-stream criteria of downstream segments for Dissolved Metals will be met with an effluent limitation as follows (based upon a hardness of 242.57 mg/l):

	4 Day Average		Load	1 Hour Average		Load
	Concentration			Concentration		
Aluminum*	N/A		N/A	4,749.5	ug/l	28.6 lbs/day
Arsenic*	2,248.60	ug/l	8.7 lbs/day	2,184.0	ug/l	13.1 lbs/day
Cadmium	5.55	ug/l	0.0 lbs/day	33.5	ug/l	0.2 lbs/day
Chromium III	2,093.33	ug/l	8.1 lbs/day	23,952.1	ug/l	144.1 lbs/day
Chromium VI*	87.31	ug/l	0.3 lbs/day	81.3	ug/l	0.5 lbs/day
Copper	225.72	ug/l	0.9 lbs/day	202.4	ug/l	1.2 lbs/day
Iron*	N/A		N/A	7,072.1	ug/l	42.5 lbs/day
Lead	112.87	ug/l	0.4 lbs/day	1,620.5	ug/l	9.7 lbs/day
Mercury*	0.14	ug/l	0.0 lbs/day	15.4	ug/l	0.1 lbs/day
Nickel	1,282.47	ug/l	5.0 lbs/day	6,372.5	ug/l	38.3 lbs/day
Selenium*	44.61	ug/l	0.2 lbs/day	123.7	ug/l	0.7 lbs/day
Silver	N/A	ug/l	N/A lbs/day	110.4	ug/l	0.7 lbs/day

**Utah Division of Water Quality  
Salt Lake City, Utah**

Zinc	2,934.28 ug/l	11.4 lbs/day	1,594.1 ug/l	9.6 lbs/day
Cyanide*	61.69 ug/l	0.2 lbs/day	141.5 ug/l	0.9 lbs/day

\*Limits for these metals are based on the dissolved standard.

**Effluent Limitations for Heat/Temperature based upon  
Water Quality Standards**

Summer	35.7 Deg. C.	96.3 Deg. F
Fall	25.8 Deg. C.	78.5 Deg. F
Winter	24.7 Deg. C.	76.5 Deg. F
Spring	31.0 Deg. C.	87.8 Deg. F

**Effluent Limitations for Organics [Pesticides]  
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Organics [Pesticides]  
will be met with an effluent limit as follows:

	4 Day Average		1 Hour Average	
	Concentration	Load	Concentration	Load
Aldrin			1.5E+00 ug/l	1.40E-02 lbs/day
Chlordane	4.30E-03 ug/l	2.58E-02 lbs/day	1.2E+00 ug/l	1.12E-02 lbs/day
DDT, DDE	1.00E-03 ug/l	6.00E-03 lbs/day	5.5E-01 ug/l	5.12E-03 lbs/day
Dieldrin	1.90E-03 ug/l	1.14E-02 lbs/day	1.3E+00 ug/l	1.16E-02 lbs/day
Endosulfan	5.60E-02 ug/l	3.36E-01 lbs/day	1.1E-01 ug/l	1.02E-03 lbs/day
Endrin	2.30E-03 ug/l	1.38E-02 lbs/day	9.0E-02 ug/l	8.38E-04 lbs/day
Guthion	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02 ug/l	9.31E-05 lbs/day
Heptachlor	3.80E-03 ug/l	2.28E-02 lbs/day	2.6E-01 ug/l	2.42E-03 lbs/day
Lindane	8.00E-02 ug/l	4.80E-01 lbs/day	1.0E+00 ug/l	9.31E-03 lbs/day
Methoxychlor	0.00E+00 ug/l	0.00E+00 lbs/day	3.0E-02 ug/l	2.79E-04 lbs/day
Mirex	0.00E+00 ug/l	0.00E+00 lbs/day	1.0E-02 ug/l	9.31E-05 lbs/day
Parathion	0.00E+00 ug/l	0.00E+00 lbs/day	4.0E-02 ug/l	3.72E-04 lbs/day
PCB's	1.40E-02 ug/l	8.41E-02 lbs/day	2.0E+00 ug/l	1.86E-02 lbs/day
Pentachlorophenol	1.30E+01 ug/l	7.80E+01 lbs/day	2.0E+01 ug/l	1.86E-01 lbs/day
Toxephene	2.00E-04 ug/l	1.20E-03 lbs/day	7.3E-01 ug/l	6.79E-03 lbs/day

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Effluent Targets for Pollution Indicators  
Based upon Water Quality Standards**

In-stream criteria of downstream segments for Pollution Indicators will be met with an effluent limit as follows:

	<b>1 Hour Average</b>	
	Concentration	Loading
Gross Beta (pCi/l)	50.0 pCi/L	
BOD (mg/l)	5.0 mg/l	30.1 lbs/day
Nitrates as N	4.0 mg/l	24.1 lbs/day
Total Phosphorus as P	0.05 mg/l	0.3 lbs/day
Total Suspended Solids	90.0 mg/l	541.4 lbs/day

Note: Pollution indicator targets are for information purposes only.

**Effluent Limitations for Protection of Human Health [Toxics Rule]  
Based upon Water Quality Standards (Most stringent of 1C or 3A & 3B as appropriate.)**

In-stream criteria of downstream segments for Protection of Human Health [Toxics] will be met with an effluent limit as follows:

	<b>Maximum Concentration</b>	
	Concentration	Load
<b>Toxic Organics</b>		
Acenaphthene	1.42E+04 ug/l	8.55E+01 lbs/day
Acrolein	3.80E+03 ug/l	2.28E+01 lbs/day
Acrylonitrile	7.00E-01 ug/l	4.20E-03 lbs/day
Benzene	1.42E+01 ug/l	8.55E-02 lbs/day
Benzidine	ug/l	lbs/day
Carbon tetrachloride	2.97E+00 ug/l	1.78E-02 lbs/day
Chlorobenzene	8.07E+03 ug/l	4.84E+01 lbs/day
1,2,4-Trichlorobenzene		
Hexachlorobenzene	8.90E-03 ug/l	5.34E-05 lbs/day
1,2-Dichloroethane	4.51E+00 ug/l	2.71E-02 lbs/day
1,1,1-Trichloroethane		
Hexachloroethane	2.25E+01 ug/l	1.35E-01 lbs/day
1,1-Dichloroethane		
1,1,2-Trichloroethane	7.24E+00 ug/l	4.34E-02 lbs/day
1,1,2,2-Tetrachloroethane	2.02E+00 ug/l	1.21E-02 lbs/day
Chloroethane		
Bis(2-chloroethyl) ether	3.68E-01 ug/l	2.21E-03 lbs/day
2-Chloroethyl vinyl ether		
2-Chloronaphthalene	2.02E+04 ug/l	1.21E+02 lbs/day
2,4,6-Trichlorophenol	2.49E+01 ug/l	1.50E-01 lbs/day
p-Chloro-m-cresol		
Chloroform (HM)	6.76E+01 ug/l	4.06E-01 lbs/day
2-Chlorophenol	1.42E+03 ug/l	8.55E+00 lbs/day
1,2-Dichlorobenzene	3.20E+04 ug/l	1.92E+02 lbs/day
1,3-Dichlorobenzene	4.75E+03 ug/l	2.85E+01 lbs/day



**Utah Division of Water Quality  
Salt Lake City, Utah**

1,4-Dichlorobenzene	4.75E+03 ug/l	2.85E+01 lbs/day
3,3'-Dichlorobenzidine	4.75E-01 ug/l	2.85E-03 lbs/day
1,1-Dichloroethylene	6.76E-01 ug/l	4.06E-03 lbs/day
1,2-trans-Dichloroethylene1		
2,4-Dichlorophenol	1.10E+03 ug/l	6.62E+00 lbs/day
1,2-Dichloropropane	6.17E+00 ug/l	3.70E-02 lbs/day
1,3-Dichloropropylene	1.19E+02 ug/l	7.12E-01 lbs/day
2,4-Dimethylphenol	6.41E+03 ug/l	3.85E+01 lbs/day
2,4-Dinitrotoluene	1.30E+00 ug/l	7.83E-03 lbs/day
2,6-Dinitrotoluene		
1,2-Diphenylhydrazine	4.75E-01 ug/l	2.85E-03 lbs/day
Ethylbenzene	3.68E+04 ug/l	2.21E+02 lbs/day
Fluoranthene	3.56E+03 ug/l	2.14E+01 lbs/day
4-Chlorophenyl phenyl ether		
4-Bromophenyl phenyl ether		
Bis(2-chloroisopropyl) ether	1.66E+04 ug/l	9.97E+01 lbs/day
Bis(2-chloroethoxy) methane		
Methylene chloride (HM)	5.58E+01 ug/l	3.35E-01 lbs/day
Methyl chloride (HM)		
Methyl bromide (HM)		
Bromoform (HM)	5.10E+01 ug/l	3.06E-01 lbs/day
Dichlorobromomethane(HM)	3.20E+00 ug/l	1.92E-02 lbs/day
Chlorodibromomethane (HM)	4.86E+00 ug/l	2.92E-02 lbs/day
Hexachlorocyclopentadiene	2.85E+03 ug/l	1.71E+01 lbs/day
Isophorone	9.97E+01 ug/l	5.98E-01 lbs/day
Naphthalene		
Nitrobenzene	2.02E+02 ug/l	1.21E+00 lbs/day
2-Nitrophenol		
4-Nitrophenol		
2,4-Dinitrophenol	8.30E+02 ug/l	4.99E+00 lbs/day
4,6-Dinitro-o-cresol	1.54E+02 ug/l	9.26E-01 lbs/day
N-Nitrosodimethylamine	8.19E-03 ug/l	4.91E-05 lbs/day
N-Nitrosodiphenylamine	5.93E+01 ug/l	3.56E-01 lbs/day
N-Nitrosodi-n-propylamine	5.93E-02 ug/l	3.56E-04 lbs/day
Pentachlorophenol	3.32E+00 ug/l	1.99E-02 lbs/day
Phenol	2.49E+05 ug/l	1.50E+03 lbs/day
Bis(2-ethylhexyl)phthalate	2.14E+01 ug/l	1.28E-01 lbs/day
Butyl benzyl phthalate	3.56E+04 ug/l	2.14E+02 lbs/day
Di-n-butyl phthalate	3.20E+04 ug/l	1.92E+02 lbs/day
Di-n-octyl phthlate		
Diethyl phthalate	2.73E+05 ug/l	1.64E+03 lbs/day
Dimethyl phthlate	3.71E+06 ug/l	2.23E+04 lbs/day
Benzo(a)anthracene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Benzo(a)pyrene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Benzo(b)fluoranthene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Benzo(k)fluoranthene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Chrysene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Acenaphthylene (PAH)		
Anthracene (PAH)		
Dibenzo(a,h)anthracene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day
Indeno(1,2,3-cd)pyrene (PAH)	3.32E-02 ug/l	1.99E-04 lbs/day

**Utah Division of Water Quality  
Salt Lake City, Utah**

Pyrene (PAH)	1.14E+04 ug/l	6.84E+01 lbs/day
Tetrachloroethylene	9.49E+00 ug/l	5.70E-02 lbs/day
Toluene	8.07E+04 ug/l	4.84E+02 lbs/day
Trichloroethylene	3.20E+01 ug/l	1.92E-01 lbs/day
Vinyl chloride	2.37E+01 ug/l	1.42E-01 lbs/day

**Pesticides**

Aldrin	1.54E-03 ug/l	9.26E-06 lbs/day
Dieldrin	1.66E-03 ug/l	9.97E-06 lbs/day
Chlordane	6.76E-03 ug/l	4.06E-05 lbs/day
4,4'-DDT	7.00E-03 ug/l	4.20E-05 lbs/day
4,4'-DDE	7.00E-03 ug/l	4.20E-05 lbs/day
4,4'-DDD	9.85E-03 ug/l	5.91E-05 lbs/day
alpha-Endosulfan	1.10E+01 ug/l	6.62E-02 lbs/day
beta-Endosulfan	1.10E+01 ug/l	6.62E-02 lbs/day
Endosulfan sulfate	1.10E+01 ug/l	6.62E-02 lbs/day
Endrin	9.02E+00 ug/l	5.41E-02 lbs/day
Endrin aldehyde	9.02E+00 ug/l	5.41E-02 lbs/day
Heptachlor	2.49E-03 ug/l	1.50E-05 lbs/day
Heptachlor epoxide		

**PCB's**

PCB 1242 (Arochlor 1242)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1254 (Arochlor 1254)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1221 (Arochlor 1221)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1232 (Arochlor 1232)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1248 (Arochlor 1248)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1260 (Arochlor 1260)	5.22E-04 ug/l	3.13E-06 lbs/day
PCB-1016 (Arochlor 1016)	5.22E-04 ug/l	3.13E-06 lbs/day

**Pesticide**

Toxaphene	8.66E-03 ug/l	5.20E-05 lbs/day
-----------	---------------	------------------

**Metals**

Antimony	166.09 ug/l	1.00 lbs/day
Arsenic	587.73 ug/l	3.53 lbs/day
Asbestos	8.30E+07 ug/l	4.99E+05 lbs/day
Beryllium		
Cadmium		
Chromium (III)		
Chromium (VI)		
Copper	15422.32 ug/l	92.59 lbs/day
Cyanide	8304.32 ug/l	49.86 lbs/day
Lead	0.00	0.00
Mercury	1.66 ug/l	0.01 lbs/day
Nickel	7236.63 ug/l	43.45 lbs/day
Selenium	0.00	0.00
Silver	0.00	0.00
Thallium	20.17 ug/l	0.12 lbs/day
Zinc		

**Utah Division of Water Quality  
Salt Lake City, Utah**

**Dioxin**

Dioxin (2,3,7,8-TCDD)

1.54E-07 ug/l

9.26E-10 lbs/day

**Metals Effluent Limitations for Protection of All Beneficial Uses  
Based upon Water Quality Standards and Toxics Rule**

	<b>Class 4 Acute Agricultural ug/l</b>	<b>Class 3 Acute Aquatic Wildlife ug/l</b>	<b>Acute Toxics Drinking Water Source ug/l</b>	<b>Acute Toxics Wildlife ug/l</b>	<b>1C Acute Health Criteria ug/l</b>	<b>Acute Most Stringent ug/l</b>	<b>Class 3 Chronic Aquatic Wildlife ug/l</b>
Aluminum		4749.5				4749.5	N/A
Antimony			166.1	51012.3		166.1	
Arsenic	1186.3	2184.0	587.7		0.0	587.7	2248.6
Barium					11863.3	11863.3	
Beryllium						0.0	
Cadmium	118.0	33.5			0.0	33.5	5.5
Chromium (III)		23952.1			0.0	23952.1	2093.3
Chromium (VI)	1167.2	81.3			0.0	81.32	87.31
Copper	2362.4	202.4	15422.3			202.4	225.7
Cyanide		141.5	2609930.3			141.5	61.7
Iron		7072.1				7072.1	
Lead	1182.6	1620.5			0.0	1182.6	112.9
Mercury		15.44	1.7	1.78	0.0	1.66	0.142
Nickel		6372.5	7236.6	54571.3		6372.5	1282.5
Selenium	583.2	123.7			0.0	123.7	44.6
Silver		110.4			0.0	110.4	
Thallium			20.2	74.7		20.2	
Zinc		1594.1				1594.1	2934.3
Boron	8679.1					8679.1	
Sulfate	23726.6					23726.6	

**Summary Effluent Limitations for Metals [Wasteload Allocation, TMDL]**

[If Acute is more stringent than Chronic, then the Chronic takes on the Acute value.]

	<b>WLA Acute ug/l</b>	<b>WLA Chronic ug/l</b>	
Aluminum	4749.5	N/A	
Antimony	166.09		
Arsenic	587.7	2248.6	Acute Controls
Asbestos	8.30E+07		
Barium			
Beryllium			
Cadmium	33.5	5.5	
Chromium (III)	23952.1	2093	
Chromium (VI)	81.3	87.3	Acute Controls
Copper	202.4	225.7	Acute Controls

**Utah Division of Water Quality  
Salt Lake City, Utah**

Cyanide	141.5	61.7	
Iron	7072.1		
Lead	1182.6	112.9	
Mercury	1.661	0.142	
Nickel	6372.5	1282	
Selenium	123.7	44.6	
Silver	110.4	N/A	
Thallium	20.2		
Zinc	1594.1	2934.3	Acute Controls
Boron	8679.14		
Sulfate	23726.6		N/A at this Waterbody

Other Effluent Limitations are based upon R317-1.

E. coli 126.0 organisms per 100 ml

#### **X. Antidegradation Considerations**

The Utah Antidegradation Policy allows for degradation of existing quality where it is determined that such lowering of water quality is necessary to accommodate important economic or social development in the area in which the waters are protected [R317-2-3]. It has been determined that certain chemical parameters introduced by this discharge will cause an increase of the concentration of said parameters in the receiving waters. Under no conditions will the increase in concentration be allowed to interfere with existing instream water uses.

The antidegradation rules and procedures allow for modification of effluent limits less than those based strictly upon mass balance equations utilizing 100% of the assimilative capacity of the receiving water. Additional factors include considerations for "Blue-ribbon" fisheries, special recreational areas, threatened and endangered species, and drinking water sources.

An Antidegradation Level I Review was conducted on this discharge and its effect on the receiving water. Based upon that review, it has been determined that an Antidegradation Level II Review is required because the receiving water for the discharge is a Class 1C Drinking Water Source.

#### **XI. Colorado River Salinity Forum Considerations**

Discharges in the Colorado River Basin are required to have their discharge at a TDS loading of less than 1.00 tons/day unless certain exemptions apply. Refer to the Forum's Guidelines for additional information allowing for an exceedence of this value.

#### **XII. Summary Comments**

The mathematical modeling and best professional judgement indicate that violations of receiving water beneficial uses with their associated water quality standards, including important downstream segments, will not occur for the evaluated parameters of concern as discussed above if the effluent limitations indicated above are met.