

DWQ-2018-014333_{CH}

STATE OF UTAH
DEPARTMENT OF ENVIRONMENTAL QUALITY
DIVISION OF WATER QUALITY

Appendix I.P

**Authorization to Discharge Under the
Utah Pollutant Discharge Elimination System (UPDES)**

**Multi-Sector General Permit (MSGP) for Storm Water
Discharges Associated with Industrial Activities**

GROUP 1

Sector P. Motor Freight Transportation Facilities, Passenger Transportation Facilities, Petroleum Bulk Oil Stations and Terminals the United States Postal Service or Railroad Transportation Facilities.

In compliance with the provisions of the *Utah Water Quality Act, Title 19, Chapter 5, Utah Code Annotated 2004*, as amended, operators of storm water discharges associated with industrial activity are authorized to discharge industrial storm water from the specified industrial site to waters of the State in accordance with the eligibility and Notice of Intent (NOI) requirements, discharge point(s), effluent limitations, inspection and monitoring requirements, and other conditions set forth in this Permit.

This permit shall become effective on January 1, 2019.

This permit and the authorization to discharge shall expire at midnight, December 31, 2023.

Signed this 31st day of December, 2018.



Erica Brown Gaddis, PhD
Director

- P. Storm Water Discharges Associated With Industrial Activity From Motor Freight Transportation Facilities, Passenger Transportation Facilities, Petroleum Bulk Oil Stations and Terminals, Railroad Transportation Facilities, and United States Postal Service Transportation Facilities.

1. Coverage of This Section.

- a. Discharges Covered Under This Section. Storm water discharges from ground transportation facilities and railroad transportation facilities (generally identified by Standard Industrial Classification (SIC) codes 40, 41, 42, 43, and 5171), that have vehicle and equipment maintenance shops (vehicle and equipment rehabilitation, mechanical repairs, painting, fueling and lubrication) and/or equipment cleaning operations are eligible for coverage under this section. Also covered under this section are facilities found under SIC codes 4221-4225 (public warehousing and storage) that do not have vehicle and equipment maintenance shops and/or equipment cleaning operations but have areas (exclusive of access roads and rail lines) where material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products or industrial machinery are exposed to storm water.
- b. Co-Located Industrial Activity. When an industrial facility, described by the above coverage provisions of this section, has industrial activities being conducted onsite that meet the description(s) of industrial activities in another section(s), that industrial facility shall comply with any and all applicable monitoring and pollution prevention plan requirements of the other section(s) in addition to all applicable requirements in this section. The monitoring and pollution prevention plan terms and conditions of this multi-sector permit are additive for industrial activities being conducted at the same industrial facility. The operator of the facility shall determine which other monitoring and pollution prevention plan section(s) of this permit (if any) are applicable to the facility.

2. Storm Water Pollution Prevention Plan Requirements.

- a. Deadlines for Plan Preparation and Compliance. There are no additional deadlines for plan preparation and compliance, other than those stated in *Part III.A.*
- b. Contents of the Plan. The plan shall include, at a minimum, the following items:
- 1) Pollution Prevention Team. Each plan shall identify a specific individual or individuals within the facility organization as members of a storm water Pollution Prevention Team who are responsible for developing the storm water pollution prevention plan and assisting the facility or plant manager in its implementation, maintenance, and revision. The plan shall clearly identify the responsibilities of

APPENDIX I.P

Permit No. : UTR000000

each team member. The activities and responsibilities of the team shall address all aspects of the facility's storm water pollution prevention plan.

- 2) Description of Potential Pollutant Sources. Each plan shall provide a description of potential sources which may reasonably be expected to add significant amounts of pollutants to storm water discharges or which may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Each plan shall identify all activities and significant materials which may potentially be significant pollutant sources. Each plan shall include, at a minimum:
 - a) Drainage. A site map indicating the location of each point of discharge of storm water associated with industrial activity, an outline of the portions of the drainage area of each storm water outfall that are within the facility boundaries (with a prediction of the direction of flow), each existing structural control measure to reduce pollutants in storm water runoff, surface water bodies, locations where significant materials are exposed to precipitation, locations where major spills or leaks identified under paragraph 2.b.(2)(c) (Spills and Leaks) of this section have occurred, and the locations of the following activities: fueling stations, vehicle and equipment maintenance and/or cleaning areas, storage areas for vehicles and equipment with actual or potential fluid leaks loading/unloading areas, locations used for the treatment, storage or disposal of wastes, liquid storage tanks, processing areas, storage areas, and all monitoring locations. The site map must also indicate the types of discharges contained in the drainage areas of the outfalls (e.g., storm water and air conditioner condensate). In order to increase the readability of the map, the inventory of the types of discharges contained in each outfall may be kept as an attachment to the site map.
 - b) Inventory of Exposed Materials. An inventory of the types of materials handled at the site that potentially may be exposed to precipitation. Such inventory shall include a narrative description of significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to storm water between the time of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this permit and the present; method and location of onsite storage or disposal; dirt or gravel parking areas for storage of vehicles to be maintained; materials management practices employed to minimize contact of materials with storm water runoff between the time of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this permit and the present; the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of any treatment

APPENDIX I.P

Permit No. : UTR000000

the storm water receives.

- c) Spills and Leaks. A list of significant spills and significant leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a storm water conveyance at the facility after the date of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this permit. Such list shall be updated as appropriate during the term of the permit.
 - d) Sampling Data. A summary of existing discharge sampling data describing pollutants in storm water discharges from the facility, including a summary of sampling data collected during the term of this permit.
 - e) Summary of Potential Pollutant Sources. A narrative description of the potential pollutant sources from the following activities associated with vehicle and equipment maintenance and equipment cleaning: fueling stations; maintenance shops; equipment or vehicle cleaning areas; paved dirt or gravel parking areas for vehicles to be maintained; loading and unloading operations; outdoor storage activities; outdoor manufacturing or processing activities; significant dust or particulate generating processes; and onsite waste disposal practices. The description shall specifically list any significant potential source of pollutants at the site and for each potential source, any pollutant or pollutant parameter (e.g., oil and grease, etc.) of concern shall be identified.
- 3) Measures and Controls. Each facility covered by this permit shall develop a description of storm water management controls appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in a plan shall reflect identified potential sources of pollutants at the facility. The description of storm water management controls shall address the following minimum components, including a schedule for implementing such controls:
- a) Good Housekeeping. All areas that may contribute pollutants to storm water discharges shall be maintained in a clean, orderly manner. The following areas must be specifically addressed:
 - (1) Vehicle and Equipment Storage Areas. The storage of vehicles and equipment awaiting maintenance with actual or potential fluid leaks must be confined to designated areas (delineated on the site map). The plan must describe measures that prevent or minimize contamination of the storm water runoff from these areas. The facility shall consider the

APPENDIX I.P

Permit No. : UTR000000

use of drip pans under vehicles and equipment, indoor storage of the vehicles and equipment, installation of berming and diking of this area, use of absorbents, roofing or covering storage areas, cleaning pavement surface to remove oil and grease, or other equivalent methods.

- (2) Fueling Areas. The plan must describe measures that prevent or minimize contamination of the storm water runoff from fueling areas. The facility shall consider covering the fueling area, using spill and overflow protection and cleanup equipment, minimizing runoff of storm water to the fueling area, using dry cleanup methods, collecting the storm water runoff and providing treatment or recycling, or other equivalent measures.
- (3) Material Storage Areas. Storage units of all materials (e.g., used oil, used oil filters, spent solvents, paint wastes, radiator fluids, transmission fluids, hydraulic fluids) must be maintained in good condition, so as to prevent contamination of storm water, and clearly labeled (e.g., "used oil," "spent solvents," etc.). The plan must describe measures that prevent or minimize contamination of the storm water runoff from such storage areas. The facility shall consider indoor storage of the materials, installation of berming and diking of the area, minimizing runoff of storm water to the areas, using dry cleanup methods, collecting the storm water runoff and providing treatment, or other equivalent methods.
- (4) Vehicle and Equipment Cleaning Areas. The plan must describe measures that prevent or minimize contamination of the storm water runoff from all areas used for vehicle and equipment cleaning. The facility shall consider performing all cleaning operations indoors, covering the cleaning operation, ensuring that all washwaters drain to the intended collection system (i.e., not the storm water drainage system unless *UPDES* permitted), collecting the storm water runoff from the cleaning area and providing treatment or recycling, or other equivalent measures. The discharge of vehicle and equipment wash waters, including tank cleaning operations, are not authorized by this permit and must be covered under a separate *UPDES* permit or discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.
- (5) Vehicle and Equipment Maintenance Areas. The plan must describe measures that prevent or minimize contamination of the storm water

APPENDIX I.P

Permit No. : UTR000000

runoff from all areas used for vehicle and equipment maintenance. The facility shall consider performing all maintenance activities indoors, using drip pans, maintaining an organized inventory of materials used in the shop, draining all parts of fluids prior to disposal, prohibiting wet clean up practices where the practices would result in the discharge of pollutants to storm water drainage systems, using dry cleanup methods, collecting the storm water runoff from the maintenance area and providing treatment or recycling, minimizing runoff of storm water areas or other equivalent measures.

- (6) Locomotive Sanding (loading sand for traction) Areas. The plan must describe measures that prevent or minimize contamination of the storm water runoff from areas used for locomotive sanding. The facility shall consider covering sanding areas, minimizing storm water runoff, appropriate sediment removal practices to minimize the offsite transport of sanding material by storm water, or other equivalent measures.
- (7) Preventive Maintenance. A preventive maintenance program shall include timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators, catch basins, drip pans, vehicle-mounted drip containment devices) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters, and ensuring appropriate maintenance of such equipment and systems.
- b) Spill Prevention and Response Procedures. Areas where potential spills could contribute pollutants to storm water discharges, and their accompanying drainage points, shall be identified clearly in the storm water pollution prevention plan. Where appropriate, specifying material handling procedures, storage requirements, and use of equipment such as diversion valves in the plan should be considered. Procedures and equipment for cleaning up spills shall be identified in the plan and made available to the appropriate personnel.
- c) Inspections. Qualified facility personnel shall be identified to inspect designated equipment and areas of the facility on a quarterly basis. The following areas shall be included in all inspections: storage area for vehicles and equipment awaiting maintenance, fueling areas, vehicle and equipment maintenance areas (both indoors and outdoors), material storage areas,

APPENDIX I.P

Permit No. : UTR000000

vehicle and equipment cleaning areas, and loading and unloading areas. Follow-up procedures shall be used to ensure that appropriate actions are taken in response to the inspections. Records of inspections shall be maintained. The use of a checklist should be considered by the facility.

- d) Employee Training. Employee training programs shall inform personnel responsible for implementing activities identified in the storm water pollution prevention plan or otherwise responsible for storm water management of the components and goals of the storm water pollution prevention plan. Training should address topics such as spill response, good housekeeping and material management practices. The pollution prevention plan shall identify how often training will take place; at a minimum, training must be held annually (once per calendar year). Employee training must, at a minimum, address the following areas when applicable to a facility: summary of the facility's pollution prevention plan requirements; used oil management; spent solvent management; spill prevention, response and control; fueling procedures; general good housekeeping practices; proper painting procedures; and used battery management.
- e) Recordkeeping and Internal Reporting Procedures. A description of incidents (such as spills, or other discharges), along with other information describing the quality and quantity of storm water discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan.
- f) Non-storm Water Discharges.
 - (1) Certification. The plan shall include a certification that the discharge has been tested or evaluated for the presence of non-storm water discharges. The certification shall include the identification of potential significant sources of non-storm water at the site, a description of the results of any test and/or evaluation for the presence of non-storm water discharges, the evaluation criteria or testing method used, the date of any testing and/or evaluation, and the onsite drainage points that were directly observed during the test. Certifications shall be signed in accordance with *Part VI.G*. (Signatory Requirements) of this permit. Such certification may not be practical if the facility operating the storm water discharge associated with industrial activity does not have access to an outfall, manhole, or other point of access to the ultimate conduit which receives the discharge. In such cases, the

APPENDIX I.P

Permit No. : UTR000000

source identification section of the storm water pollution prevention plan shall indicate why the certification required by this part was not practical, along with the identification of potential significant sources of non-storm water at the site. A discharger that is unable to provide the certification required by this paragraph must notify the *Director* in accordance with paragraph 2.b.(3)(g)(iv) (Failure to Certify) of this section.

- (2) **Exceptions.** Except for flows from emergency/unplanned fire fighting activities, sources of non-storm water listed in *Part II.A.2. (Prohibition of Non-storm Water Discharges)* of this permit that are combined with storm water discharges associated with industrial activity must be identified in the plan. The plan shall identify and ensure the implementation of appropriate pollution prevention measures for the non-storm water component(s) of the discharge.
- (3) A copy of the *UPDES* permit issued for vehicle and equipment washwaters or, if a *UPDES* permit has not yet been issued, a copy of the pending application must be attached to or referenced in the plan. For facilities that discharge vehicle and equipment washwaters to the sanitary sewer system, the operator of the sanitary system and associated treatment plant must be notified. In such cases, a copy of the notification letter must be attached to the plan. If an industrial user permit is issued under a pretreatment program, a copy of that permit must be attached in the plan. In all cases, any permit conditions or pretreatment requirements must be considered in the plan. If the washwaters are handled in another manner (e.g., hauled offsite), the disposal method must be described and all pertinent documentation (e.g., frequency, volume, destination, etc.) must be attached to the plan.
- (4) **Failure to Certify.** Any facility that is unable to provide the certification required (testing for non-storm water discharges), must notify the *Director* within 180 days after submitting a notice of intent to be covered by this permit. If the failure to certify is caused by the inability to perform adequate tests or evaluations, such notification shall describe: the procedure of any test conducted for the presence of non-storm water discharges; the results of such test or other relevant observations; potential sources of non-storm water discharges to the storm sewer; and why adequate tests for such storm sewers were not feasible. Non-storm water discharges to waters of the State which are not authorized by a *UPDES* permit are unlawful, and must be

APPENDIX I.P

Permit No. : UTR000000

terminated

- g) Sediment and Erosion Control. The plan shall identify areas which, due to topography, activities, or other factors, have a high potential for significant soil erosion, and identify structural, vegetative, and/or stabilization measures to be used to limit erosion.
 - h) Management of Runoff. The plan shall contain a narrative consideration of the appropriateness of storm water management practices (practices other than those which control the generation or source(s) of pollutants) used to divert, infiltrate, reuse, or otherwise manage storm water runoff in a manner that reduces pollutants in storm water discharges from the site. The plan shall provide for the implementation and maintenance of measures that the permittee determines to be reasonable and appropriate. The potential of various sources at the facility to contribute pollutants to storm water discharges associated with industrial activity [see paragraph 2.b.(2) (description of potential pollutant sources) of this permit] shall be considered when determining reasonable and appropriate measures. Appropriate measures or other equivalent measures may include: vegetative swales and practices, reuse of collected storm water (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), snow management activities, infiltration devices, and wet detention/retention devices.
- 4) Comprehensive Site Compliance Evaluation. Qualified personnel shall conduct comprehensive site compliance evaluations at appropriate intervals specified in the plan, but, in no case less than once a year. Such evaluations shall provide:
- a) Areas contributing to a storm water discharge associated with industrial activity shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural storm water management measures, sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as spill response equipment, shall be made.
 - b) Based on the results of the evaluation, the description of potential pollutant

APPENDIX I.P

Permit No. : UTR000000

sources identified in the plan in accordance with paragraph *2.b.(2)* (Description of Potential Pollutant Sources) of this section and pollution prevention measures and controls identified in the plan in accordance with paragraph *2.b.(3)* (Measures and Controls) of this section shall be revised as appropriate within 2 weeks of such evaluation and shall provide for implementation of any changes to the plan in a timely manner, but in no case more than 12 weeks after the evaluation.

- c) A report summarizing the scope of the evaluation, personnel making the evaluation, the date(s) of the evaluation, major observations relating to the implementation of the storm water pollution prevention plan, and actions taken in accordance with paragraph *2.b.(4)(b)* (above) of the section shall be made and retained as part of the storm water pollution prevention plan for at least 3 years after the date of the evaluation. The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with *Part VI.G.* (Signatory Requirements) of this permit.
 - d) Where compliance evaluation schedules overlap with inspections required under *2.b.(3)(d)*, the compliance evaluation may be conducted in place of one such inspection.
3. Numeric Effluent Limitations. There are no additional numeric effluent limitations beyond those described in *Part IV.B.* of this permit.
4. Monitoring and Reporting Requirements.
- a. Quarterly Visual Examination of Storm Water Quality. Facilities shall perform and document a visual examination of a storm water discharge associated with industrial activity from each outfall, except discharges exempted under paragraph (3) below. The examination(s) must be made at least once in each designated period [described in (1), below] during facility operation in the daylight hours unless there is insufficient rainfall or snow melt to produce a runoff event.
 - 1) Sampling Periods. Examinations shall be conducted in each of the following periods for the purposes of visually inspecting storm water quality associated with storm water runoff or snow melt: January through March; April through June; July through September; and October through December.

APPENDIX I.P

Permit No. : UTR000000

- 2) Sample and Data Collection. Examinations shall be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed one hour) of when the runoff or snowmelt begins discharging. The examinations shall document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution. The examination must be conducted in a well lit area. No analytical tests are required to be performed on the samples. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where practicable, the same individual will carry out the collection and examination of discharges for the life of the permit.
- 3) Adverse Conditions. When a discharger is unable to collect samples over the course of the visual examination period as a result of adverse climatic conditions, the discharger must document the reason for not performing the visual examination and retain this documentation onsite with the records of the visual examinations. Adverse weather conditions which may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricanes, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).
- 4) Visual Storm Water Discharge Examination Reports. Visual examination reports must be maintained onsite in the pollution prevention plan. The report shall include the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the storm water discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution), and probable sources of any observed storm water contamination.
- 5) Representative Discharge. When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may collect a sample of effluent of one of such outfalls and report that the examination data also applies to the substantially identical outfalls provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explaining in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square

APPENDIX I.P

Permit No. : UTR000000

feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan.

- 6) Inactive and Unstaffed Site. When a discharger is unable to conduct visual storm water examinations at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirement as long as the facility remains inactive and unstaffed. The facility must maintain a certification with the pollution prevention plan stating that the site is inactive and unstaffed so that performing visual examinations during a qualifying event is not feasible.