STATE OF UTAH DIVISION OF WATER QUALITY DEPARTMENT OF ENVIRONMENTAL QUALITY SALT LAKE CITY, UTAH

Section 401 Water Quality Certification No. DWQ-2022-08001

Project Proponents: Timothy Gribben, Process Control Manager

US Magnesium LLC 238 North 2200 West Salt Lake City, UT 84116

Project: US Magnesium LLC (Project Proponent) proposes to extend two intake canals in the Gilbert Bay

of the Great Salt Lake to reach open water. The extension would maintain connectivity with the necessary source water for the evaporation facility. The project would utilize hydraulic dredging to extend the canals. The canals would be extended to a bottom elevation of 4,185 feet. The construction corridor would be limited to 300-ft wide. The proposed project would be an initial phase in establishing long-term access to water from the Great Salt Lake. The dredging activity would be conducted adjacent to the existing canals to minimize impacts. Dredged materials will be

placed into the lakebed adjacent to the construction corridor to mimic existing conditions.

Location: The proposed project is located on the Great Salt Lake in Grantsville, Tooele County, Utah. The

project is approximately located at 40.951716, -112.514961.

Watercourse(s): Gilbert Bay- The Great Salt Lake

USACE Section 404: SPK-2008-01773

Effective Date: Month, Day, Year

Table of Contents

I.	<u>Definitions</u>	3
II.	Acronyms	3
III.	Executive Summary	4
IV.	Background	4
V.	Aquatic Resource Impacts	5
VI.	Certification Conditions	6
VII.	Condition Justification and Citation	7
VIII.	<u>Disclaimers</u>	10
IX.	Public Notice and Comments	10

I. Definitions

- A. <u>Designated Beneficial Uses</u> means a water's present most reasonable uses, grouped by use classes to protect the uses against controllable pollution. Beneficial uses designated within each class are described in Utah Administrative Code (UAC) R317-2-6 and waterbodies beneficial uses can be found in UAC R317-2-13. For the purposes of this document, the term "designated beneficial uses" will be used to describe all uses required to be protected by Utah water quality standards and antidegradation policy.
- B. <u>Category 1 Waters</u> are "Waters which have been determined by the Board to be of exceptional recreational or ecological significance or have been determined to be a State or National resource requiring protection, shall be maintained at existing high quality through designation, by the Board after public hearing, as Category 1 Waters." UAC R317-2-3.2
- C. <u>Category 2 Waters</u> "are designated surface water segments which are treated as Category 1 Waters except that a point source discharge may be permitted provided that the discharge does not degrade existing water quality." UAC R317-2-3.3
- D. <u>Designated Beneficial Uses</u> means a water's present most reasonable uses, grouped by use classes to protect the uses against controllable pollution. Beneficial uses designated within each class are described in Utah Administrative Code (UAC) R317-2-6 and waterbodies beneficial uses can be found in UAC R317-2-13.
- E. Existing Uses "means those uses actually attained in a water body on or after November 28, 1975, whether or not they are included in the water quality standards." UAC R317-1-1." If a situation is found where there is an existing use which is a higher use (i.e., more stringent protection requirements) than that current designated use, the Director will apply the water quality standards and anti-degradation policy to protect the existing use." UAC R317-2-3.
- F. <u>Level I Antidegradation Review (ADR):</u> "is conducted to insure that_existing uses will be maintained and protected." UAC R317-2-3.5
- G. <u>Level II Antidegradation Review (ADR)</u> is conducted to insure that water quality degradation is necessary and that the proposed activity is documented to be both economically and socially important. Level II ADRs are required for any activity that's impacts are not considered temporary and limited and is likely to result in degradation of water quality.
- H. Project Proponent "means the applicant for license or permit or entity seeking certification." 40 CFR §121.1.
- I. <u>Protection Category:</u> "Utah's surface waters are assigned to one of three protection categories that are determined by their existing biological, chemical and physical integrity, and by the interest of stakeholders in protecting current conditions." Utah Antidegradation Review Implementation Guidance (V 2.1)
- J. <u>Total Maximum Daily Load (TMDL)</u> "means the maximum amount of a particular pollutant that a waterbody can receive and still meet state water quality standards, and an allocation of that amount to the pollutant's sources." UAC R317-1-1
- K. Waters of the United States (WOTUS) means waterbodies subject to the provisions of the Clean Water Act.
- L. <u>303(d) list</u> is a state's list of impaired and threatened waters, including but not limited to; streams, lakes, and reservoirs adopted to implement the Clean Water Act Section 303(d).

II. Acronyms

AU – Assessment Unit

BMPs – Best Management Practices

CFR – Code of Federal Regulations

CWA - Clean Water Act

DEQ – Utah Department of Environmental Quality

DWQ – Utah Division of Water Quality

EIS – Environmental Impact Statement

EPA – Environmental Protection Agency

mg/L – milligrams per liter

MS4 – Municipal Separate Storm Sewer System

NOI – Notice of Intent

NTU – Nephelometric Turbidity Units ROW – right of way

SWPPP – stormwater pollution prevention plan

TMDL - Total Maximum Daily Load

TSS – total suspended solids

UAC – Utah Administrative Code

UPDES – Utah Pollutant Discharge Elimination System

USACE – U.S. Army Corps of Engineers

WQC - Water Quality Certification

WQS – Utah Water Quality Standards

WOTUS – Waters of the United States

III. Executive Summary

Pursuant to Section 401 of the CWA 33 U.S.C. Section 1251 et seq., the DWQ grants Water Quality Certification (Certification) to US Magnesium for the proposed US Magnesium Canal Continuation Project (Project) in Grantsville, Tooele County, Utah. Certification is subject to the conditions outlined in this document and adherence to any U.S. Army Corps of Engineers (USACE) Section 404 Permit Conditions. The conditions outlined in this Certification are necessary to assure compliance with effluent limitations, monitoring requirements, and/or other applicable laws and regulations adopted for state primacy of the CWA.

DWQ's conditions are based on and are necessary to comply with applicable state rules. Specifically, the following Utah rules represent overarching considerations that require the conditions outlined by this document to apply to the USACE Section 404 Permit: Utah's rules promulgating standards of quality for waters of the State affirm "it shall be unlawful and a violation of these rules for any person to discharge or place any wastes or other substances in such manner as may interfere with designated uses protected by assigned classes or to cause any of the applicable standards to be violated" UAC R317-2-7.1.a. Additionally, "all actions to control waste discharges under these rules shall be modified as necessary to protect downstream designated uses" UAC R317-2-8. As stated in UAC R317-15-6.1 the Director will ordinarily consider whether the proposed discharge "impairs the designated beneficial use classifications (e.g., aquatic life, drinking water, recreation) in Section R317-2-6" UAC R317-15-6.1.A.2. or "fails to meet the antidegradation (ADR) requirements of Section R317-2-7" UAC R317-15-6.1.A.3.

The DWQ attended a pre-filing meeting with the project proponent on May 18, 2022. Timothy Gribben of US Magnesium LLC submitted a 401 Water Quality application on August 30, 2022. The application was deemed incomplete. On September 2, 2022 a corrected application was submitted and DWQ deemed the application to be complete.

IV. Background

The Project Proponent proposes to extend two intake canals at the US Magnesium Facility in Gilbert Bay of the Great Salt Lake. The purpose of the project is to ensure continued operation of the US Magnesium facility. The project would maintain connectivity with the source water for the evaporation facility. Diminishing lake levels have isolated the two intake canals from the Great Salt Lake which has limited the ability of the facility to operate. The project will utilize hydraulic dredging to reinstate the connection between the lake and the intake canals and would modify limited portions of the lake bed. The proposed project would extend the canals to a bottom elevation of 4,185 ft. The existing P-0 Canal will be extending from 2.6 miles to 5.6 miles with a 40 ft bottom width and maximum top width of 62 ft. The existing P-North Canal will be extended from 1.1 miles long to 1.8 miles with a 40 ft bottom width and a maximum top width of 55 ft. The project would maintain a conveyance of lake water

intake flow of 100,000 gallons per minute from the Great Salt Lake. The project would take place adjacent to the existing canal to minimize impacts. The construction corridor will be restricted to 300 ft wide. The dredged material would be placed within approximately 126.8 acres of lakebed. The dredged material would be discharged utilizing the aerial broadcast technique adjacent to the canals. The dredged material applied will not exceed 2 ft in height in order to mimic the natural variations of the lakebed. This proposed project is intended to be the first step in a long-term process to ensure access to water from the Great Salt Lake.

The Great Salt Lake would be the only waterbody that would be impacted during the course of the proposed project. No streams or wetlands are located within the proposed project boundaries. The proposed application of the dredged material adjacent to the canals will not have a significant impact on the chemical, physiological, or biological composition of the existing lakebed. The project would not affect any threatened or endangered species or their critical habitat.

The proposed project would not result in permanent loss of any Waters of the United States (WOTUS) nor change the function of the existing lakebed. The management of dredged material would mimic natural lakebed conditions which would have a less significant impact then disposing of the material in an upland area. The construction would take place along and adjacent to the existing canals to reduce impacts. Canal extension plans and discharge areas would be adjusted to avoid impacts to sensitive microbialites if possible. The project proponent provided two alternatives to dredging, facility modifications and a floating pipe system. Facility modifications have been ongoing to try to maintain operations with lowered lake levels. The facility has been relying on stockpiled surplus to supplement the declining intake capacity but the surplus is anticipated to be gone by next year. The floating pipe alternative would require additional infrastructure including barges, pumps, and anchoring systems. This alternative would be at a higher cost and would be dependent on resource availability.

V. Aquatic Resource Impacts

All Waters of the State of Utah (defined in UAC R317-1-1) are protected from pollutant discharges that affect water quality by narrative standards (see UAC R317-2-7.2); broadly, discharges should not become offensive or cause undesirable conditions in human health effects or aquatic life. In addition, some particularly sensitive classes of water are further protected from deleterious effects of specific pollutants by application of numeric criteria to designated beneficial uses of that waterbody. Listed below are the water features, grouped by AUs, impacted by the Project, their associated designated beneficial uses (see UAC R317-2-6 and UAC R317-2-13) and any impairments:

A. Gilbert Bay UT-L-16020310-001 00 (The Great Salt Lake)

1. Beneficial Use Designations

a. Class 5: The Great Salt Lake--Protected for infrequent primary and secondary contact recreation, waterfowl, shore birds and other water-oriented wildlife including their necessary food chain.

2. Impairments and Total Maximum Daily Loads (TMDLs)

Results from the current water quality assessment, as documented in Utah's Final 2022 Integrated Report[1], indicated insufficient data (Assessment Category 3) were available to assess the Gilbert Bay AU.

3. Antidegradation Review

Waters within the Gilbert Bay AU are considered Category 3 waters for antidegradation purposes. Category 3 waters in Utah are waters where "point source discharges are allowed and degradation may

¹ Integrated Report https://deq.utah.gov/water-quality/2022-integrated-report.

occur, pursuant to the conditions and review procedures outlined in Section 3.5", as described in UAC R317-2-3.4. The antidegradation policy allows for discharges where the water quality effects of the proposed Project are determined to be temporary and limited after consideration of the factors identified in UAC R317-2-3.5.b.4., and where best management practices (BMPs) would be employed to minimize pollution effects.

VI. Certification Conditions

- A. All activities with a potential discharge to WOTUS must implement and maintain BMPs to fully protect the waterbodies assigned beneficial use(s).
- B. All activities shall not cause further degradation of impaired waterbodies, as defined in DWQ's most recent 303(d) list, regardless of whether a TMDL has been completed. The Project Proponent must review impairments on the waterbodies where the Project has the potential to discharge and is responsible for ensuring that water quality standards are not exceeded and designated beneficial uses are not impaired
- C. Hazardous and otherwise deleterious materials (e.g. oil, gasoline, chemicals, trash, sawdust, etc.) shall not be stored, disposed of, or accumulated or conveyed through adjacent to or in immediate vicinity WOTUS unless adequate measures and controls are provided to ensure those materials would not enter WOTUS in the State of Utah. Any spill or discharge of oil or other substance which may cause pollution to WOTUS in the State of Utah, including wetlands, must be immediately reported to the Utah DEQ Hotline at (801) 536-4123, a 24-hour phone number.
- D. All activities conducted in WOTUS in the State of Utah shall be conducted in the "dry" to the maximum extent practicable, by diverting flow utilizing cofferdams, berms constructed of sandbags, clean rock (containing no fine sediment) or other non-erodible, non-toxic material. All diversion materials shall be removed at the completion of the work. The Project Proponent shall consider conducting instream work during low flow conditions and work shall not be conducted during spawning season. Additionally, construction machinery shall not be operated within WOTUS in the State of Utah unless it is unavoidable, in which case it shall be conducted in the "dry" as stated above. The work shall be conducted in a manner to minimize the duration of the disturbance, turbidity increases, substrate disturbance, and minimize the removal of riparian vegetation. Construction machinery shall be clean to prevent the transfer of aquatic invasive species.
- E. Project Activities shall not increase water turbidity by more than 10 Nephelometric Turbidity Units (NTUs) in waterbodies classified as beneficial use class 2B for recreation and 3A for cold water aquatic life. Project activities shall not cause an increase in water turbidity by more than 15 NTUS in waterbodies classified as beneficial use class 3D. Project Proponents must continuously monitor turbidity during instream construction to ensure turbidity increases are within the limits listed above. The Project Proponents must provide monthly reports to DWQ during instream construction in waterbodies with class 2B, 3A, and 3D beneficial use designations that include at a minimum: baseline (reference) turbidity measurements in each waterbody where instream construction is occurring.
- F. Construction activities that disturb either greater than one acre of land, or less than one acre of land and is part of a larger common plan of development that would disturb greater than one acre, are required to obtain coverage under the Utah Pollutant Discharge Elimination System (UPDES) Storm Water General Permit for

Construction Activities (Permit No. UTRC00000[²]). The permit requires the development of a Storm Water Pollution Prevention Plan (SWPPP) to be implemented and updated from the commencement of any soil disturbing activities at the site, until final stabilization of the project. The SWPPP should include, but not be limited to, final site maps and legible plans, location of storm water outfalls/discharges, and information pertaining to any storm water retention requirements.

G. Dewatering activities, if necessary during construction, may require coverage under the UPDES General Permit for Construction Dewatering (Permit No. UTG070000[³]) applies to the construction dewatering of uncontaminated groundwater or surface water sources due to construction activities; hydrostatic testing of pipelines or other fluids vessels; water used in disinfection of drinking water vessels; and other similar discharges in the State of Utah that have no discharge of process wastewater. The permit requires submission of a Notice of Intent (NOI); maintenance of a discharge log; development and implementation of a dewatering control plan; and monitoring for Flow, Oil & Grease, pH, Total Suspended Solids (TSS), and Chlorine (required when chlorinated water is used and discharged to a stream with a chlorine standard). Discharge Monitoring Reports (DMRs) are required to be submitted monthly, regardless of whether a site discharges in a particular month.

VII. Condition Justification and Citation

A. Implementation of BMPs. Project approval is conditioned on implementation of BMPs, which are required to be implemented by the antidegradation policy in UAC R317-2-3, water quality standards may be violated unless appropriate BMPs are incorporated to minimize the erosion-sediment and nutrient load. Violations of water quality standards could cause a waterbody to fail to meet its designated beneficial uses. As required by Utah's antidegradation policy UAC R317-2-3.1 "Existing instream water uses shall be maintained and protected. No water quality degradation is allowable which would interfere with or become injurious to existing instream water uses." As stated in UAC R317-15-6.1 the Director will ordinarily consider whether the proposed discharge "impairs the designated beneficial use classifications (e.g., aquatic life, drinking water, recreation) in Section R317-2-6" UAC R317-15-6.1.A.1., "exceeds water quality criteria, either narrative or numeric, in Section R317-2-7" UAC R317-15-6.1.A.2. or "fails to meet the antidegradation (ADR) requirements of Section R317-2-7" UAC R317-15-6.1.A.3 when making a Certification decision. If appropriate BMPs are incorporated, there is assurance that the Project will not violate water quality standards or impair a waterbody's beneficial use.

Citation(s): UAC R317-2-3.1, UAC R317-15-6.1, UAC R317-15-6.1.A.1., UAC R317-15-6.1.A.2., UAC R317-15-6.1.A.3.

B. Proper Storage of Hazardous and Otherwise Deleterious Materials. Project approval is conditioned on proper storage of hazardous and otherwise deleterious materials, and notification of any discharge of those materials, to assure that water quality and narrative standards are not violated. When projects are occurring in or around waterbodies, there is a chance for pollutants to inadvertently be spilled/discharged into waterbodies due to increased risk from project related activities (e.g. presence of machinery, onsite chemical and gas storage, improper waste storage, and failure to use proper BMPs). To prevent or reduce the possibility that hazardous and otherwise deleterious materials are inadvertently discharged into a waterbody, Project Proponents must not store, dispose of, or accumulated such materials adjacent to or in immediate vicinity of WOTUS unless adequate measures and controls are provided to ensure those materials would not

²¹¹ https://documents.deg.utah.gov/water-quality/stormwater/construction/DWO-2020-013890.pdf

³¹² https://documents.deg.utah.gov/water-quality/permits/updes/DWO-2019-005143.pdf

enter waters of the State. If there is a discharge to WOTUS in the State of Utah, it must be immediately reported to the DEQ, as stated in Utah Code Section 19-5-114. An inadvertent discharge of pollutants can cause violations with Utah's Narrative Standards, which states "It shall be unlawful, and a violation of these rules, for any person to discharge or place any waste or other substance in such a way as will be or may become offensive such as unnatural deposits, floating debris, oil, scum or other nuisances such as color, odor or taste; or cause conditions which produce undesirable aquatic life or which produce objectionable tastes in edible aquatic organisms; or result in concentrations or combinations of substances which produce undesirable physiological responses in desirable resident fish, or other desirable aquatic life, or undesirable human health effects, as determined by bioassay or other tests performed in accordance with standard procedures; or determined by biological assessments in Subsection R317-2-7.3" UAC R317-3-7.2. Utah's rules promulgating standards of quality for waters of the State affirm "it shall be unlawful and a violation of these rules for any person to discharge or place any wastes or other substances in such manner as may interfere with designated uses protected by assigned classes or to cause any of the applicable standards to be violated" UAC R317-2-7.1.a. Discharges of pollutants, even inadvertently, could cause both a violation of applicable water quality standards and possibly interfere with a waterbodies designated uses.

Citation(s): Utah Code § 19-5-114, UAC R317-3-7.2, UAC R317-2-7.1.A, UAC R317-15-6.1., UAC R317-15-6.1.A.1., UAC R317-15-6.1A.2.

C. Dry Conditions to the Maximum Extent Practicable. Project approval is conditioned on conducting activities under dry conditions to the maximum extent practicable to assure that water quality standards are not exceeded. Construction machinery used within a waterbody can cause significant impacts to water quality if adequate precautions are not taken. When it is unavoidable to operate construction machinery within the waterbody the Project Proponent should focus on minimizing the duration of the disturbance, turbidity increase, substrate disturbance, removal of riparian vegetation, and work shall be conducted in the "dry" to the maximum extent practicable. Minimizing the duration of impact reduces the chance that the impacts will accumulate and cause significant impacts to water quality. Minimizing turbidity increases is important because the State of Utah has numeric water quality criteria for turbidity in certain use designations, which could be violated if the Project Proponent does not take proper steps to minimize the increases. Water quality criteria for turbidity will be violated if there is an increase of 10 NTUs in waterbodies with designated uses related to recreation and if there is an increase of 10 NTUs (class 3A and 3B) or 15 NTUs (class 3C and 3D) in waterbodies with aquatic wildlife designated uses. UAC R317-2-14.1 and UAC R317-2-14.2. Conducting work in the "dry" to the maximum extent practicable will help reduce the risk of the numeric criteria for turbidity to be exceeded, as well as reduce the risk of a significant sediment load being transported downstream. Discharges of sediment can not only violate numeric criteria, but also, risk violating Utah's narrative standard "It shall be unlawful, and a violation of these rules, for any person to discharge or place any waste or other substance in such a way as will be or may become offensive such as unnatural deposits, floating debris, oil, scum or other nuisances such as color, odor or taste; or cause conditions which produce undesirable aquatic life or which produce objectionable tastes in edible aquatic organisms; or result in concentrations or combinations of substances which produce undesirable physiological responses in desirable resident fish, or other desirable aquatic life, or undesirable human health effects, as determined by bioassay or other tests performed in accordance with standard procedures; or determined by biological assessments in Subsection R317-2-7.3." UAC R317-2-7.2. Violations of numeric and narrative criteria could cause a waterbody not to meet its designated beneficial use and a transport of sediment downstream could prevent a downstream waterbody from meeting its designated beneficial uses. As required by Utah's antidegradation policy UAC R317-2-3.1 "Existing instream water uses shall be maintained and protected. No water quality degradation is allowable which would interfere with or become injurious to existing instream water uses". Additionally, "All actions to control waste discharges under these rules shall be

modified as necessary to protect downstream designated uses" UAC R317-2-8. As stated in UAC R317-15-6.1 the Director will ordinarily consider whether the proposed discharge "impairs the designated beneficial use classifications (e.g., aquatic life, drinking water, recreation) in Section R317-2-6" UAC R317-15-6.1.A.1., "exceeds water quality criteria, either narrative or numeric, in Section R317-2-7" UAC R317-15-6.1.A.2. or "fails to meet the antidegradation (ADR) requirements of Section R317-2-7" UAC R317-15-6.1.A.3 when making a certification decision.

Citation(s): UAC R317-2-3.5., UAC R317-2-7.1.A., UAC R317-2-14.1, UAC R317-2-14.2., UAC R317-2-7.1.a., UAC R317-2-7.2., UAC R317-2-3.1, UAC R317-2-8., UAC R317-15-6.1, UAC R317-15-6.1.A.1, UAC R317-15-6.1A.2., UAC R317-15-6.1.A.3.

D. Turbidity Increases and Instream Construction Monitoring. Beneficial uses associated with recreation and aquatic life have been assigned numeric criteria for turbidity. An increase of more than 10 NTUs in class 2B and 3A waterbodies above the turbidity of that waterbody would be a violation of instream criteria for waterbodies that have recreation or aquatic life uses. Similarly, an increase of more than 15 NTUs in class 3D waterbodies above the turbidity of that waterbody would be a violation of instream criteria for waterbodies that have aquatic life uses. UAC R317-2-14.1 and UAC R317-2-14.2. Therefore, turbidity increases above those allowed by this Certification could cause the waterbody to fail to meet its designated beneficial use classes. Turbidity monitoring during instream construction in waterbodies with class 2B, 3A and 3D beneficial uses designations will ensure turbidity increases do not violate Utah's water quality standards. Utah's antidegradation policy states "existing instream water uses shall be maintained and protected. No water quality degradation is allowable which would interfere with or become injurious to existing instream water uses" UAC R317-2-3.1. Failure to minimize turbidity increases that result in the failure to maintain beneficial use class 2B or 3A would be considered a violation of Utah's rules and promulgated standards of quality for waters of the State, specifically Utah's antidegradation policy found at UAC R317-2-3. The Director will ordinarily consider whether the proposed discharge "impairs the designated beneficial use classifications (e.g., aquatic life, drinking water, recreation) in Section R317-2-6" UAC R317-15-6.1.A.1., "exceeds water quality criteria, either narrative or numeric, in Section R317-2-7" UAC R317-15-6.1A.2. or "fails to meet the antidegradation (ADR) requirements of Section R317-2-7" UAC R317-15-6.1.A.3 when making a certification decision.

Citations: UAC R317-2-3.1, UAC R317-2-3, UAC R317-2-14.1, UAC R317-2-14.2 R317-15-6.1, UAC R317-15-6.1.A.1, UAC R317-15-6.1A.2., UAC R317-15-6.1.A.3.

E. <u>UPDES Storm Water General Permit for Construction Activities (Permit No. UTRC00000)</u>. UAC R317-8-2.5, gives the Director authority to issue general permits to cover specific categories of discharges, including storm water and construction dewatering that is discharged to a surface water. According to UAC R317-8-3.9 (6)(d), construction activities that result in a land disturbance of equal to or greater than one acre, including clearing, grading, and excavation are "industrial activities" under UAC R317-8-3.9(1)(a) and are therefore required to obtain and comply with a UPDES Permit for storm water discharges. This only applies to projects that meet or exceed one acre of disturbance.

Citation(s): UAC R317-8-3.9(6)(d) and UAC R317-8-3.9(1)(a)

F. <u>UPDES General Permit for Construction Dewatering (Permit No. UTG070000)</u>. UAC R317-8-2.5, gives the Director authority to issue general permits to cover specific categories of discharges, including storm water and construction dewatering that is discharged to a surface water. Under the authority granted by UAC R317-8-2.5, the Director issued the General Permit for Construction Dewatering and Hydrostatic Testing,

UPDES Permit No. UTG070000 renewed and effective as of February 1, 2020. UPDES Permit No. UTG070000 applies to construction dewatering of uncontaminated groundwater or surface water sources due to construction activities, hydrostatic testing of pipelines or other fluids vessels, water used in disinfection of drinking water vessels and other similar discharges in the State of Utah that have no discharge of process wastewater. This only applies to projects that require dewatering and discharge to surface water.

Citation(s): UAC R317-8-2.5

VIII. Disclaimers

A. Fees

1. The legislatively-mandated fee for the 2022 fiscal year is \$110.00/hour for review and issuance of the Section 401 Water Quality Certification. A quarterly invoice will be sent and your payment is due within 30 days.

B. Disclaimers

- 1. The Project Proponent must acquire all necessary easements, access authorizations and permits to ensure they are able to implement the Project. This Section 401 Certification does not convey any property rights or exclusive privileges, nor does it authorize access or injury to private property.
- 2. This Section 401 Certification does not preclude the Project Proponent's responsibility of complying with all applicable Federal, State or local laws, regulations or ordinances, including water quality standards. Permit coverage does not release the project proponent from any liability or penalty, should violations to the permit terms and conditions or Federal or State Laws occur.
- 3. A Project within a Municipal Separate Storm Sewer System (MS4) jurisdiction, must comply with all the conditions required in that UPDES MS4 Permit and associated ordinances. No condition of this Section 401 Certification shall reduce or minimize any requirements provided in the MS4 Permit. In the case of conflicting requirements, the most stringent criteria shall apply.

IX. Public Notice and Comments

As in UAC R317-15-5., this Certification decision is subject to a 30 public notice period. After considering public comment, the Director may execute the Certification issuance, revise it, or abandon it.

- A. Public Notice Dates
- B. Public Notice Comments/Response
- C. During finalization of the Certification certain dates, spelling edits, and minor language or formatting corrections may have been completed. Due to the nature of these changes they were not considered major and the Certification will not be Public Noticed again.

X. Water Quality Certification

The Utah DWQ certifies that if the Project Proponents adhere to the conditions outlined in this Certification and adheres to any USACE Section 404 Permit Conditions, then the Project will comply with water quality requirements and applicable provisions of the CWA sections 301 (Effluent Limitations), 302 (Water Quality Related Effluent Limitations), 303 (Water Quality Standards and Implementation Plans), 306 (National Standards of Performance), and 307 (Toxic and Pretreatment Effluent Standards).

John K. Mackey P.E., Director	Date	
DWQ-2022-027626		